

EIR (Equipment Identity Register)

Overview

The HSS includes a built-in EIR (Equipment Identity Register) that provides equipment identity verification for mobile devices. The EIR validates IMEI (International Mobile Equipment Identity) numbers to determine if mobile equipment is authorized, stolen, or under observation before allowing network access.

Key Capabilities

- **S13 Interface:** Equipment identity checking via Diameter protocol
- **IMEI Validation:** Verify equipment identity using IMEI/IMEISV
- **Flexible Matching:** Regex-based pattern matching for IMEI, IMEISV, and IMSI
- **Three-Tier Classification:** Whitelist, blacklist, and greylist support
- **Configurable Policies:** Customizable behavior for unknown equipment
- **REST API:** Full CRUD operations for EIR rule management

Architecture

Diameter Interface

Interface	Application ID	Peer	Purpose
S13	16,777,252	MME/SGSN	Equipment identity verification

Equipment Rules Database

The EIR uses a flexible rule-based matching system:

EIR_RULE		
int	id	PK
string	action	
string	regex	
timestamp	inserted_at	
timestamp	updated_at	

Rule Actions:

- `whitelist` - Allow equipment
- `blacklist` - Block equipment
- `greylist` - Monitor equipment

Regex Patterns: Match against IMEI, IMEISV, or IMSI

Equipment Status Values

Status	Code	Meaning	Network Action
Whitelist	0	Equipment approved	Allow network access
Blacklist	1	Equipment stolen/blocked	Deny network access
Greylist	2	Equipment under observation	Allow with monitoring

S13 Interface

Supported Operations

Equipment Identity Check Request (ECR) / Equipment Identity Check Answer (ECA)

Direction: MME/SGSN → HSS (EIR)

Trigger: MME verifies equipment identity during attach or tracking area update

Request AVPs:

- Session-Id
- Origin-Host, Origin-Realm
- Destination-Realm
- Auth-Session-State
- Terminal-Information
 - IMEI (15 digits)
 - Software-Version (2 digits, optional)
- User-Name (IMSI, optional)
- Vendor-Specific-Application-Id

EIR Actions:

1. Extract IMEI, Software-Version (if present), and IMSI (if present)

2. If IMSI provided:
 - Validate subscriber exists and is enabled
 - Update subscriber state with last seen information
3. Attempt equipment lookup in priority order:
 - **IMEISV match** (IMEI + Software-Version concatenated)
 - **IMEI match** (IMEI only)
 - **IMSI match** (if provided in request)
 - **Unknown equipment policy** (configured default behavior)
4. Return equipment status

Response AVPs:

- Session-Id (echoed from request)
- Result-Code: 2001 (success)
- Equipment-Status: 0 (whitelist) / 1 (blacklist) / 2 (greylist)

Error Responses:

- Experimental-Result: 5422 (equipment/subscriber not found)
- Experimental-Result: 5012 (general error)

Equipment Matching Logic

Priority Order

The EIR uses a cascading lookup strategy to maximize matching flexibility:

1. IMEISV (IMEI + Software-Version)
 - ↓ (if no match)
2. IMEI only
 - ↓ (if no match)
3. IMSI (if provided in request)
 - ↓ (if no match)
4. Unknown Equipment Policy

Matching Algorithm

Step 1: IMEISV Matching

- Concatenate IMEI + Software-Version: "35979139461611" + "08" = "3597913946161108"
- Test against all EIR rule regex patterns
- Return action ("whitelist", "blacklist", "greylist") of first matching rule

Step 2: IMEI Matching (fallback)

- Use IMEI only: "35979139461611"
- Test against all EIR rule regex patterns
- Return action of first matching rule

Step 3: IMSI Matching (fallback if IMSI provided)

- Use IMSI from request: "999999876543210"
- Test against all EIR rule regex patterns
- Return action of first matching rule
- **Use case:** Block all equipment for a specific subscriber

Step 4: Unknown Equipment Policy (final fallback)


- Configuration setting: eir_unknown_equipment_behaviour
- Options:
 - :whitelist - Allow unknown equipment (permissive)
 - :blacklist - Block unknown equipment (restrictive)
 - :greylist - Observe unknown equipment (moderate)
 - :reject_unknown_equipment - Return error 5422 (strict)

Regex Pattern Examples


Pattern	Matches	Use Case
"35979139461650"	Exact IMEI	Single device whitelist/blacklist
"3597913946165.*"	IMEI prefix wildcard	Manufacturer/model range
"3597913946161108"	Exact IMEISV	Specific device with software version
"999999876543210"	IMSI	Block all equipment for subscriber
"359791.*"	TAC wildcard	Entire device type allocation

Common Message Flows


Flow 1: Equipment Check - Known Whitelisted IMEI




Flow 2: Equipment Check - Blacklisted IMEI (Stolen Device)




Flow 3: Equipment Check - Unknown Equipment (Whitelist Policy)




Flow 4: Equipment Check - Unknown Equipment (Reject Policy)




Flow 5: Equipment Check - Unknown Subscriber



Flow 6: Equipment Check - IMEISV Match



Flow 7: Equipment Check - IMSI Blocking



REST API

EIR Rule Management

Base path: `/api/eir/rule`

List All EIR Rules

Request:

```
GET /api/eir/rule
```

Response (HTTP 200):

```
{
  "data": [
    {
      "id": "e7f6a5b4-c3d2-4e1f-8a9b-0c1d2e3f4a5b",
      "action": "whitelist",
      "regex": "3597913946165.*",
      "inserted_at": "2025-01-15T10:30:00Z",
      "updated_at": "2025-01-15T10:30:00Z"
    },
    {
      "id": "f8a7b6c5-d4e3-4f2a-9b0c-1d2e3f4a5b6c",
      "action": "blacklist",
      "regex": "35979139461640",
      "inserted_at": "2025-01-16T14:20:00Z",
      "updated_at": "2025-01-16T14:20:00Z"
    }
  ]
}
```

Get Specific EIR Rule

Request:

```
GET /api/eir/rule/{id}
```

Response (HTTP 200):

```
{
  "data": {
    "id": "e7f6a5b4-c3d2-4e1f-8a9b-0c1d2e3f4a5b",
    "action": "whitelist",
    "regex": "3597913946165.*"
  }
}
```

Create EIR Rule

Request:

```
POST /api/eir/rule
Content-Type: application/json

{
  "action": "blacklist",
  "regex": "35979139461640"
}
```

Validation:

- `action`: Required, must be "whitelist", "blacklist", or "greylist"
- `regex`: Required, must be valid regex pattern, unique across all rules

Response (HTTP 201):

```
{
  "data": {
    "id": "0362b7ab-9bd6-4d8a-8b1a-2f4c6e8d0a1c",
    "action": "blacklist",
    "regex": "35979139461640"
  }
}
```

Error Response (HTTP 400):

```
{
  "errors": {
    "regex": ["has already been taken"]
  }
}
```

Update EIR Rule (Partial)

Request:

```
PATCH /api/eir/rule/{id}
Content-Type: application/json
```

```
{
  "action": "greylist"
}
```

Response (HTTP 200):

```
{
  "data": {
    "id": "0362b7ab-9bd6-4d8a-8b1a-2f4c6e8d0a1c",
    "action": "greylist",
    "regex": "35979139461640"
  }
}
```

Replace EIR Rule

Request:

```
PUT /api/eir/rule/{id}
Content-Type: application/json
```

```
{
  "action": "whitelist",
  "regex": "359791394616.*"
}
```

Response (HTTP 200):

```
{
  "data": {
    "id": "0362b7ab-9bd6-4d8a-8b1a-2f4c6e8d0a1c",
    "action": "whitelist",
    "regex": "359791394616.*"
  }
}
```

Delete EIR Rule

Request:

```
DELETE /api/eir/rule/{id}
```

Response (HTTP 204 No Content)

Configuration

Diameter Service Setup

S13 Application (`config/runtime.exs`):

```
%{  
  application_name: :s13,  
  application_dictionary: :diameter_gen_3gpp_s13,  
  vendor_specific_application_ids: [  
    %{vendor_id: 10415, auth_application_id: 16_777_252}  
  ]  
}
```

Unknown Equipment Behavior

Configure the default behavior for equipment not matching any rules in `config/runtime.exs`:

Example:

```
config :hss, :eir,  
  unknown_equipment_behaviour: :whitelist
```

Valid Values:

- `:whitelist` - Allow unknown equipment (default, permissive)
- `:blacklist` - Block unknown equipment (restrictive)

- `:greylist` - Monitor unknown equipment (moderate)
- `:reject_unknown_equipment` - Return Diameter error 5422 (strict)

Use Cases:

- **Development/Testing:** `:whitelist` - Allow all devices
- **Production (permissive):** `:whitelist` - Only block known bad devices
- **Production (moderate):** `:greylist` - Log unknown devices for review
- **Production (strict):** `:reject_unknown_equipment` - Only allow registered devices

Error Handling

Result Code	Type	Meaning	Cause
2001	Success	DIAMETER_SUCCESS	Equipment check complete
5422	Experimental	DIAMETER_ERROR_EQUIPMENT_UNKNOWN	Subscriber not found or unknown equipment rejected
5012	Experimental	DIAMETER_ERROR_UNKNOWN	Processing error

Use Cases

1. Stolen Device Management

Scenario: Device reported stolen

Action:

```
POST /api/eir/rule
{
  "action": "blacklist",
  "regex": "35979139461640" # Exact IMEI
}
```

Result: Device denied network access on next attachment

2. Manufacturer Whitelist

Scenario: Pre-approve entire device model range

Action:

```
POST /api/eir/rule
{
  "action": "whitelist",
  "regex": "359791394.*" # TAC for manufacturer/model
}
```

Result: All devices in TAC range approved

3. Subscriber Equipment Lock

Scenario: Block all equipment for specific subscriber (SIM lock)

Action:

```
POST /api/eir/rule
{
  "action": "blacklist",
  "regex": "999999876543210" # IMSI
}
```

Result: Any equipment used with this SIM is blocked

4. Test Equipment Greylist

Scenario: Monitor test equipment in production

Action:

```
POST /api/eir/rule
{
  "action": "greylist",
  "regex": "35979139.*" # Test equipment TAC range
}
```

Result: Equipment allowed but flagged for monitoring

5. Software Version Control

Scenario: Block specific vulnerable firmware version

Action:

```
POST /api/eir/rule
{
  "action": "blacklist",
  "regex": "359791394616.*05" # IMEI range + Software Version 05
}
```

Result: Only devices with Software-Version "05" in IMEI range blocked

Implementation Details

Internal Components

The EIR functionality is implemented using several internal modules:

- **S13 Protocol Handler** - ECR/ECA message processing
- **Equipment Matching Engine** - Regex-based IMEI/IMEISV/IMSI matching
- **EIR Rules Database** - Pattern storage and lookup
- **REST API Controller** - Rule management endpoints

Equipment Status Lookup Function

The equipment status lookup follows this cascading logic:

1. **IMEISV Matching**: Check IMEI + Software-Version concatenated
2. **IMEI Matching**: Check IMEI only
3. **IMSI Matching**: Check IMSI (if provided)
4. **Unknown Equipment**: Apply configured default policy

Possible Results:

- `whitelist` - Equipment allowed
- `blacklist` - Equipment blocked
- `greylist` - Equipment under observation
- `reject_unknown_equipment` - Strict rejection

Security Considerations

IMEI Privacy

IMEI numbers are sensitive identifiers. The EIR:

- Does not log IMEI values in plaintext by default
- Uses hashed database lookups (if configured)

- Restricts API access to authenticated administrators

Rule Ordering

EIR rules are evaluated in database order (by ID). For conflicting patterns:

```
Rule 1: regex "359791.*" action "whitelist" (broad)
Rule 2: regex "35979139461640" action "blacklist" (specific)
```

Recommendation: Create specific rules before broad wildcards to ensure blacklist takes precedence.

Rate Limiting

Consider implementing rate limiting on:

- S13 ECR requests from untrusted peers
- REST API EIR rule modifications
- IMEI lookup queries to prevent enumeration attacks

Related Documentation

- [Diameter Protocols](#) - S13 protocol specification
- [API Reference](#) - Complete API documentation
- [Architecture](#) - Overall HSS architecture
- [Operations Guide](#) - Operational procedures

Appendix: IMEI Structure

IMEI Format (15 digits)

```
35 9791 394616 1
|   |   |           └─ Check digit (Luhn algorithm)
|   |   └─ Serial Number (6 digits)
|   └─ FAC (Final Assembly Code, 4 digits)
└─ TAC (Type Allocation Code, 8 digits total including RBI)
    └─ RBI (Reporting Body Identifier, 2 digits)
        └─ Manufacturer/Model (6 digits)
```

IMEISV Format (16 digits)

```
35 9791 394616 1 08
|   |   |   |   └─ Software Version (2 digits)
└─ IMEI (15 digits)
```

Example Patterns

IMEI/IMEISV	Pattern	Matches
359791394616108	3597913946161.*	All devices with TAC+FAC+Serial 359791394616*
359791394616140	35979139461614.	All check digits for Serial 359791394616141-9
35979139461640	35979139461640	Exact IMEI match
3597913946163008	3597913946163008	Exact IMEISV (IMEI + SV) match

PCRF (Policy and Charging Rules Function)

Overview

The HSS includes a built-in PCRF (Policy and Charging Rules Function) that provides policy control and charging rules for mobile data sessions. The PCRF controls Quality of Service (QoS) policies, bandwidth allocation, and charging rules for both default and dedicated bearers in LTE networks.

Key Capabilities

- **Gx Interface:** Policy control for PGW/PCEF (Packet Data Network Gateway / Policy and Charging Enforcement Function)
- **Rx Interface:** Authorization and QoS for IMS (IP Multimedia Subsystem) media flows
- **Sy Interface:** Subscriber spending limit control against an external OCS - see [Sy Interface](#)
- **Dynamic Policy Management:** Real-time policy updates via Re-Auth Requests (RAR)
- **VoLTE Support:** Dedicated bearer creation for voice calls with guaranteed QoS
- **Charging Rules:** Define charging behavior and speed profiles using Traffic Flow Templates (TFTs)
- **REST API:** Programmatic control of policy enforcement and rule management


Architecture

Diameter Interfaces

Interface	Application ID	Peer	Purpose
Gx	16,777,238	PGW (PCEF)	PDN session management, QoS enforcement, charging rules
Rx	16,777,236	P-CSCF (AF)	IMS media authorization, bandwidth reservation
Sy	16,777,302	OCS	Subscriber spending limit status, spend-driven policy - see Sy Interface

Session State Management

The PCRF maintains session state for active PDN connections and VoLTE calls:



Gx Interface

Supported Operations

1. Credit Control Request - Initial (CCR-I)

Trigger: PGW creates new PDN connection for subscriber

Request AVPs:

- Session-Id
- Origin-Host, Origin-Realm
- Subscription-Id (contains IMSI)
- Called-Station-Id (APN name)

- IP-CAN-Type (IP Connectivity Access Network type)
- RAT-Type (Radio Access Technology)
- Framed-IP-Address (UE IP address)

PCRF Actions:

1. Lookup subscriber by IMSI
2. Retrieve APN profile and QoS configuration
3. Create session tracking entry
4. Build QoS policies from APN profile

Response AVPs:

- Result-Code: 2001 (DIAMETER_SUCCESS)
- QoS-Information (APN aggregate bandwidth limits)
- Default-EPS-Bearer-QoS (QCI, ARP, priority)
- Bearer-Control-Mode
- Online / Offline (session-level default charging method - see [Session-Level Online/Offline Charging](#))

2. Credit Control Request - Update (CCR-U)

Trigger: PGW reports session changes (location update, RAT change, etc.)

PCRF Actions:

1. Locate existing session by session ID
2. Update session parameters (RAT type, location, etc.)
3. Return updated policies if needed

Response: Result-Code 2001 with optional policy updates

3. Credit Control Request - Terminate (CCR-T)

Trigger: PGW terminates PDN connection

PCRF Actions:

1. Locate session by session ID

2. Delete session and associated call records
3. Confirm termination

Response: Result-Code 2001


Session-Level Online/Offline Charging

The `Online` (AVP 1009) and `Offline` (AVP 1008) AVPs sent at the top level of a Gx CCA-I set the **default charging method for the whole IP-CAN session** (the default bearer), as defined in [3GPP TS 29.212](#). This is distinct from the per-rule `Online/Offline` carried *inside* a Charging-Rule-Definition, which only governs the traffic matched by that specific rule.

By default the PCRF **echoes** whichever values the PGW/PCEF advertised in the CCR-I. The APN QoS profile can instead **pin** the session-level charging method, overriding the echo. This is controlled by two optional fields on the APN QoS profile:

Field	Type	AVP	Effect
<code>online_charging_enabled</code>	Boolean	<code>Online</code> (1009)	<code>true</code> → <code>ENABLE_ONLINE (1)</code> , <code>false</code> → <code>DISABLE_ONLINE (0)</code>
<code>offline_charging_enabled</code>	Boolean	<code>Offline</code> (1008)	<code>true</code> → <code>ENABLE_OFFLINE (1)</code> , <code>false</code> → <code>DISABLE_OFFLINE (0)</code>

Each field is resolved independently:



Charging Method AVP Values (TS 29.212):

AVP	Code	Value	Name	Meaning
Online	1009	0	DISABLE_ONLINE	Online charging (OCS / Gy) not applied to the session
Online	1009	1	ENABLE_ONLINE	Online charging applied - credit must be granted before traffic flows
Offline	1008	0	DISABLE_OFFLINE	Offline charging (CDR / Gz) not applied to the session
Offline	1008	1	ENABLE_OFFLINE	Offline charging applied - usage recorded for billing

How it works: When `online_charging_enabled`/`offline_charging_enabled` are left unset (the default for every existing profile), behaviour is unchanged - the PCRF mirrors the PGW's request, so the network's existing charging posture is preserved. Setting either field forces that charging mode on every CCR-I for any APN using the profile, regardless of what the PGW advertises.

Use case: Pin online charging on for a prepaid APN (so the PGW must consult the OCS even if it requested offline), or force offline charging on a postpaid/IoT APN to guarantee CDR generation. Because the setting lives on the APN QoS profile, it applies uniformly to every APN that references that profile.

Note: This controls the *session default* only. Per-traffic charging is still governed by the `online_charging_enabled`/`offline_charging_enabled` fields on individual **Charging Rules**, which appear inside Charging-Rule-Definition AVPs.

4. Re-Auth Request (RAR)

Direction: PCRF → PGW (HSS initiates)

Trigger:

- IMS call setup (Rx AAR triggers Gx RAR)
- IMS call teardown (Rx STR triggers Gx RAR)
- Manual re-auth via REST API

RAR AVPs:

- Session-Id (PGW session ID)
- Auth-Application-Id: 16,777,238
- Re-Auth-Request-Type (0 = Authorize only)
- Charging-Rule-Install/Remove
- QoS-Information (for dedicated bearers)

PGW Actions: Create/modify/delete dedicated bearers based on charging rules

Charging Rules and Traffic Flow Templates

The PCRF supports defining charging rules with Traffic Flow Templates (TFTs) to control:

- **Service-specific charging** - Different rates for video, gaming, social media, etc.
- **Speed profiles** - Throttle or prioritize traffic matching specific patterns
- **Usage-based policies** - Apply different QoS based on traffic type or destination

Charging rules can be:

- Installed dynamically via Gx RAR based on application detection
- Pre-defined and triggered by specific conditions (time of day, location, quota)
- Associated with TFTs using packet filter rules (5-tuple: protocol, source/dest IP, source/dest port)

Common Use Cases:

- **Zero-rating** - Unlimited access to specific services (Spotify, WhatsApp, Facebook) without consuming data quota

- **Post-quota access** - Allow self-care portal and support sites even after subscriber exhausts data allowance
- **Tiered speed** - High-speed for premium services, throttled for standard content
- **Time-based policies** - Off-peak unlimited streaming, peak-time prioritization
- **Roaming policies** - Different charging for international vs domestic data usage
- **Enterprise SLAs** - Guaranteed QoS for business-critical applications

QoS Policy Structure

Default Bearer QoS (from APN profile):

```
{
  "QoS-Class-Identifier": 9,           // QCI (9 = default bearer)
  "APN-Aggregate-Max-Bitrate-UL": 50000, // kbps
  "APN-Aggregate-Max-Bitrate-DL": 100000, // kbps
  "Allocation-Retention-Priority": {
    "Priority-Level": 8,
    "Pre-emption-Capability": 1,       // May preempt
    "Pre-emption-Vulnerability": 1    // May be preempted
  }
}
```

Dedicated Bearer QoS (for VoLTE):

```
{
  "QoS-Class-Identifier": 1,           // QCI 1 = Conversational
  Voice
  "Max-Requested-Bandwidth-UL": 128000, // bps
  "Max-Requested-Bandwidth-DL": 128000, // bps
  "Guaranteed-Bitrate-UL": 128000,
  "Guaranteed-Bitrate-DL": 128000
}
```

Rx Interface

Supported Operations

1. AA Request (AAR) / AA Answer (AAA)

Trigger: P-CSCF requests authorization for IMS media session (VoLTE call setup)

Request AVPs:

- Session-Id (P-CSCF session identifier)
- Subscription-Id (IMSI or SIP URI)
- Media-Component-Description
 - Media-Type (audio, video)
 - Max-Requested-Bandwidth-UL/DL
 - Codec-Data
 - Flow-Description (5-tuple packet filters)
- AF-Application-Identifier

PCRF Actions:

1. Lookup subscriber by IMSI or SIP URI
2. Find active IMS session
3. Extract media parameters (codec, bandwidth, flow rules)
4. Create call tracking entry
5. **Trigger Gx RAR to PGW** to create dedicated bearer
6. Wait for Gx RAA response
7. Return Rx AAA with authorization result

Response AVPs:

- Result-Code: 2001 (success) or 5063 (service not authorized)

Emergency (SOS) calls, including unauthenticated / SIM-less callers

Emergency calls (`urn:service:sos`) are authorized even when the caller is not a known subscriber (a SIM-less device, or a roaming subscriber with no

credentials on file). This is required so that emergency calls always obtain the correct QoS (TS 23.167).

How the PCRF recognises and authorizes an emergency AAR:

1. **Emergency detection.** The request is treated as emergency if **either** the `Subscription-Id` is a SIP URI containing `sos`, **or** the AAR's `Framed-IP-Address` resolves to a PDN session that was already created as an emergency PDN by the Gx CCR-I (the Gx side flags emergency by the APN / `Called-Station-Id` containing `sos`). The second path is what lets an **anonymous** emergency INVITE (no usable identity) still be authorized.
2. **Subscriber resolution.** Looked up by `Subscription-Id`, else by `Framed-IP-Address`. An emergency **orphan PDN** (created by Gx for an unknown subscriber) has no subscriber (`subscriber_state_id: nil`); the AAR then takes the orphan path rather than the normal-subscriber path.
3. **SOS APN profile.** The dedicated-bearer QoS is taken from the SOS APN profile (see "Built-in default SOS APN profile" below).
4. A Gx RAR installs the dedicated voice bearer (QCI 1) on the (orphan) PDN, and the AAA returns `2001`.

Note: a `Framed-IP-Address` only yields authorization if it maps to a PDN that Gx already created **as emergency**. A non-emergency request from an unregistered UE is still rejected at the P-CSCF (it never reaches the PCRF as an emergency AAR).

Built-in default SOS APN profile. Emergency authorization no longer depends on an operator having pre-provisioned a `sos` APN profile in the database. The PCRF resolves the SOS APN profile as:

- an operator-defined APN profile whose APN identifier is `sos`, if one exists; otherwise
- a **built-in default** SOS APN profile supplied by OmniHSS.

The built-in default is a transient profile (no DB row, `apn_profile_id: nil` on the orphan PDN - the column is nullable) with emergency QoS:

Parameter	Value
Default SOS bearer QCI	5
Dedicated voice bearer QCI	1 (ARP priority 2)
Allocation-Retention-Priority	1
Pre-emption-Capability	enabled
Pre-emption-Vulnerability	disabled
APN-AMBR UL/DL	10000 kbps

To override these values (or to set per-operator charging rules via a PCRF profile), create a **sos** APN profile in the DB - it takes precedence over the built-in default.

2. Session Termination Request (STR) / Session Termination Answer (STA)

Trigger: P-CSCF terminates IMS session (call hangup)


PCRF Actions:

1. Locate call session by P-CSCF session ID
2. **Trigger Gx RAR to PGW** to remove dedicated bearer
3. Delete call tracking entry
4. Return STA confirmation


Response: Result-Code 2001

Common Message Flows


Flow 1: PDN Session Establishment




Flow 2: VoLTE Call Setup (Rx AAR → Gx RAR)




Flow 3: VoLTE Call Teardown (Rx STR → Gx RAR)




Flow 4: PDN Session Update



Flow 5: PDN Session Termination



Flow 6: Manual Re-Auth via REST API



REST API

PCRF Re-Auth Endpoint

Endpoint: `POST /api/operation/pcrf_re_auth`

Purpose: Manually trigger Gx Re-Auth Request to refresh policies

When to Use: This manual endpoint is typically used for troubleshooting or forcing policy refresh on specific subscribers. For routine policy updates (changing APN QoS profiles), the system automatically triggers re-auth for all affected sessions - no manual action needed.

Request Body:

```
{
  "imsi": "999999876543210",
  "apn": "ims"
}
```

Success Response (HTTP 200):

```
{
  "data": "Gx Re-Auth Request for 999999876543210 sent to
pgw.epc.mnc999.mcc999.3gppnetwork.org, Result-Code: 2001"
}
```

Error Response (HTTP 400):

```
{
  "error": "Unable to send Re-Auth Request for 999999876543210 on
APN ims, no active PDN Session found"
}
```

Policy Configuration API

The PCRF retrieves QoS policies from APN configurations stored in the database. These policies can be created and managed via REST API.

Automatic Policy Enforcement: When you update an APN QoS profile (e.g., change bandwidth limits or QCI), the system automatically sends Gx Re-Auth Requests (RAR) to all PGWs with active PDN sessions using that APN. This ensures policy changes are applied immediately to all connected subscribers without manual intervention.

Policy Architecture

Policies are defined through a three-tier structure:

APN Identifier → APN QoS Profile → APN Profile

↓ ↓ ↓
"internet" QCI, AMBR, ARP Links both together

1. Create APN Identifier

Define the APN name and IP version support.

Endpoint: POST /api/apn/identifier

Request Body:

```
{
  "apn_identifier": {
    "apn": "internet",
    "ip_version": "ipv4v6"
  }
}
```

IP Version Options:

- "ipv4" - IPv4 only
- "ipv6" - IPv6 only
- "ipv4v6" - Dual stack (both IPv4 and IPv6)
- "ipv4_or_ipv6" - Network decides (either IPv4 or IPv6)

Response (HTTP 201):

```
{
  "data": {
    "id": "4fa85f64-5717-4562-b3fc-2c963f66afa6",
    "apn": "internet",
    "ip_version": "ipv4v6"
  }
}
```

Validation:

- `apn`: Required, 1-254 characters, unique
- `ip_version`: Required, must be one of the four options above

List APN Identifiers: `GET /api/apn/identifier`

2. Create APN QoS Profile

Define the QoS parameters (bandwidth, QCI, priority).

Endpoint: `POST /api/apn/qos_profile`

Request Body:

```
{
  "apn_qos_profile": {
    "name": "Best Effort Internet",
    "qci": 9,
    "allocation_retention_priority": 8,
    "apn_ambr_dl_kbps": 100000,
    "apn_ambr_ul_kbps": 50000,
    "pre_emption_capability": false,
    "pre_emption_vulnerability": true,
    "online_charging_enabled": false,
    "offline_charging_enabled": true
  }
}
```

QoS Parameters:

Field	Type	Range	Description
name	string	1-254 chars	Profile name (unique)
qci	integer	1-254	QoS Class Identifier (1-4 = GBR, 5-9 = Non-GBR)
allocation_retention_priority	integer	1-15	ARP level (1 = highest priority)
apn_ambr_dl_kbps	integer	1-4,294,967,293	APN Aggregate Maximum Bit Rate Downlink (kbps)
apn_ambr_ul_kbps	integer	1-4,294,967,293	APN Aggregate Maximum Bit Rate Uplink (kbps)
pre_emption_capability	boolean	true/false	Can preempt lower priority bearers
pre_emption_vulnerability	boolean	true/false	Can be preempted by higher priority bearers

Field	Type	Range	Description
online_charging_enabled	boolean	true/false/null	Session-level Online AVP for the Gx CCA-I. null (default) echoes the PGW's CCR-I value. See Session-Level Online/Offline Charging
offline_charging_enabled	boolean	true/false/null	Session-level Offline AVP for the Gx CCA-I. null (default) echoes the PGW's CCR-I value. See Session-Level Online/Offline Charging

Common QCI Values:

- **1** - Conversational Voice (VoLTE) - GBR, 100ms delay budget
- **2** - Conversational Video - GBR, 150ms delay budget
- **5** - IMS Signaling - Non-GBR, 100ms delay budget
- **9** - Default Bearer (Internet) - Non-GBR, 300ms delay budget

Response (HTTP 201):

```
{
  "data": {
    "id": "8d8ac610-566d-4ef0-9c22-186b2a5ed793",
    "name": "Best Effort Internet",
    "qci": 9,
    "allocation_retention_priority": 8,
    "apn_ambr_dl_kbps": 100000,
    "apn_ambr_ul_kbps": 50000,
    "pre_emption_capability": false,
    "pre_emption_vulnerability": true,
    "online_charging_enabled": false,
    "offline_charging_enabled": true
  }
}
```

List QoS Profiles: GET /api/apn/qos_profile

3. Create APN Profile

Link the APN identifier with a QoS profile.

Endpoint: POST /api/apn/profile

Request Body:

```
{
  "apn_profile": {
    "name": "Internet APN",
    "apn_identifier_id": "4fa85f64-5717-4562-b3fc-2c963f66afa6",
    "apn_qos_profile_id": "8d8ac610-566d-4ef0-9c22-186b2a5ed793"
  }
}
```

Fields:

- `name`: Profile name (unique), used for reference
- `apn_identifier_id`: ID from [Create APN Identifier](#)
- `apn_qos_profile_id`: ID from [Create APN QoS Profile](#)

Response (HTTP 201):

```
{
  "data": {
    "id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "name": "Internet APN",
    "apn_identifier_id": "4fa85f64-5717-4562-b3fc-2c963f66afa6",
    "apn_qos_profile_id": "8d8ac610-566d-4ef0-9c22-186b2a5ed793"
  }
}
```

Constraints:

- `apn_identifier_id` and `apn_qos_profile_id` must reference existing records
- Each combination of APN identifier and QoS profile must be unique

List APN Profiles: `GET /api/apn/profile`

Complete Policy Configuration Example

Step 1: Create IMS APN Policy (VoLTE)

1. Create APN Identifier

```
curl -X POST https://hss.example.com:8443/api/apn/identifier \
-H "Content-Type: application/json" \
-d '{
  "apn_identifier": {
    "apn": "ims",
    "ip_version": "ipv4v6"
  }
}'
```

```
# Response: {"data": {"id": "2c3e4f5a-6b7c-4d8e-9f0a-1b2c3d4e5f6a", ...}}
```

2. Create QoS Profile (IMS Signaling)

```
curl -X POST https://hss.example.com:8443/api/apn/qos_profile \
-H "Content-Type: application/json" \
-d '{
  "apn_qos_profile": {
    "name": "IMS Signaling QoS",
    "qci": 5,
    "allocation_retention_priority": 2,
    "apn_ambr_dl_kbps": 5000,
    "apn_ambr_ul_kbps": 5000,
    "pre_emption_capability": true,
    "pre_emption_vulnerability": false
  }
}'
```

```
# Response: {"data": {"id": "7b44a3e0-27cc-4b21-8d7a-3f19e5c2b8d4", ...}}
```

3. Create APN Profile

```
curl -X POST https://hss.example.com:8443/api/apn/profile \
-H "Content-Type: application/json" \
-d '{
  "apn_profile": {
    "name": "IMS APN",
    "apn_identifier_id": "2c3e4f5a-6b7c-4d8e-9f0a-1b2c3d4e5f6a",
    "apn_qos_profile_id": "7b44a3e0-27cc-4b21-8d7a-3f19e5c2b8d4"
  }
}'
```

```
# Response: {"data": {"id": "91c2f3a4-5d6e-4f7a-8b9c-0d1e2f3a4b5c", ...}}
```

Step 2: Assign to Subscriber

Once created, the APN profile is assigned to subscribers via EPC profiles. See [API Reference](#) for linking APN profiles to subscribers.

Policy Update and Deletion

Update QoS Profile:

```
PATCH /api/apn/qos_profile/{id}
PUT /api/apn/qos_profile/{id}
```

Example - Increase Bandwidth for All Users:

```
# Update the QoS profile to increase bandwidth
curl -X PATCH
https://hss.example.com:8443/api/apn/qos_profile/8d8ac610-566d-
4ef0-9c22-186b2a5ed793 \
-H "Content-Type: application/json" \
-d '{
  "apn_qos_profile": {
    "apn_ambr_dl_kbps": 150000,
    "apn_ambr_ul_kbps": 75000
  }
}'
```

What Happens Automatically:

1. QoS profile is updated in the database
2. System identifies all active PDN sessions using APNs linked to this QoS profile
3. For each active session, a Gx RAR is sent to the corresponding PGW
4. PGWs update bearer QoS to reflect new bandwidth limits
5. All connected subscribers immediately receive the updated policy

Example Scenario: If 100 subscribers are currently connected on the "internet" APN using this QoS profile, all 100 will have their bandwidth limits

updated to 150 Mbps down / 75 Mbps up within seconds of the API call completing.

Note: When you update an APN QoS profile, the system **automatically triggers re-auth** for all active PDN sessions using that APN, applying the new policies immediately to attached subscribers. No manual re-auth is required.

Delete Resources:

```
DELETE /api/apn/identifier/{id}
DELETE /api/apn/qos_profile/{id}
DELETE /api/apn/profile/{id}
```

Deletion Constraints:

- Cannot delete APN identifiers or QoS profiles referenced by APN profiles
- Cannot delete APN profiles assigned to active subscribers

Policy Templates

High-Speed Internet (100 Mbps down / 50 Mbps up):

```
{
  "apn_qos_profile": {
    "name": "High Speed Internet",
    "qci": 9,
    "allocation_retention_priority": 8,
    "apn_ambr_dl_kbps": 100000,
    "apn_ambr_ul_kbps": 50000,
    "pre_emption_capability": false,
    "pre_emption_vulnerability": true
  }
}
```

Premium Internet (500 Mbps down / 100 Mbps up):

```
{
  "apn_qos_profile": {
    "name": "Premium Internet",
    "qci": 8,
    "allocation_retention_priority": 5,
    "apn_ambr_dl_kbps": 500000,
    "apn_ambr_ul_kbps": 100000,
    "pre_emption_capability": true,
    "pre_emption_vulnerability": false
  }
}
```

IoT/M2M (Low Bandwidth):

```
{
  "apn_qos_profile": {
    "name": "IoT M2M",
    "qci": 9,
    "allocation_retention_priority": 10,
    "apn_ambr_dl_kbps": 1024,
    "apn_ambr_ul_kbps": 512,
    "pre_emption_capability": false,
    "pre_emption_vulnerability": true
  }
}
```

Emergency Services (Highest Priority):

```
{
  "apn_qos_profile": {
    "name": "Emergency APN",
    "qci": 5,
    "allocation_retention_priority": 1,
    "apn_ambr_dl_kbps": 10000,
    "apn_ambr_ul_kbps": 10000,
    "pre_emption_capability": true,
    "pre_emption_vulnerability": false
  }
}
```


Configuration

Diameter Service Setup

Gx Application (`config/runtime.exs`):

```
%{  
  application_name: :gx,  
  application_dictionary: :diameter_gen_3gpp_gx,  
  vendor_specific_application_ids: [  
    %{vendor_id: 10415, auth_application_id: 16_777_238}  
  ]  
}
```

Rx Application (`config/runtime.exs`):

```
%{  
  application_name: :rx,  
  application_dictionary: :diameter_gen_3gpp_rx,  
  vendor_specific_application_ids: [  
    %{vendor_id: 10415, auth_application_id: 16_777_236}  
  ]  
}
```

QoS Parameters

QoS parameters are sourced from:

- **Default Bearer:** APN profile configuration in database
 - `apn_qos_profile.qci` (QoS Class Identifier)
 - `apn_qos_profile.apn_ambr_ul_kbps` (Aggregate Maximum Bit Rate Uplink)
 - `apn_qos_profile.apn_ambr_dl_kbps` (Aggregate Maximum Bit Rate Downlink)
 - `apn_qos_profile.priority_level` (Allocation Retention Priority)

- **Dedicated Bearer:** Extracted from Rx AAR Media-Component-Description
 - QCI: 1 (Conversational Voice)
 - Guaranteed Bitrate: From Max-Requested-Bandwidth AVPs
 - Flow filters: From Flow-Description AVPs

Error Handling

Result Code	Type	Meaning	Cause
2001	Success	DIAMETER_SUCCESS	Request processed successfully
5001	Experimental	User not found	IMSI not in subscriber database
5002	Experimental	Session not found	PDN session does not exist for update/terminate
5063	Experimental	Service not authorized	IMS media authorization denied

Implementation Details

Session Management

The PCRF tracks:

- **Active PDN Sessions** - One per APN, per subscriber
- **VoLTE Calls** - Multiple calls per IMS session (supports conference calling)
- **QoS Policies** - Applied dynamically based on APN configuration
- **Charging Rules** - Traffic flow templates and service-specific policies

Advanced Policy Features

The PCRF supports advanced policy control including:

- **Charging rule installation/removal** via Gx interface
- **Traffic Flow Template (TFT) matching** for service differentiation
- **Dynamic speed profiles** based on application or traffic type
- **Service-aware policies** triggered by network conditions or subscriber behavior

Contact your system administrator for information on configuring advanced charging rules and TFT-based policies.

Related Documentation

- [Sy Interface](#) - Subscriber spending limit control against an external OCS
- [Diameter Protocols](#) - Detailed protocol specifications
- [API Reference](#) - Complete API documentation
- [Architecture](#) - Overall HSS architecture
- [Data Mapping](#) - Database to Diameter AVP mappings

API Error Handling

[← Back to API Reference](#)

Table of Contents

- [Common Error Responses](#)
 - [Error Handling Flow](#)
-

Common Error Responses

400 Bad Request

```
{  
  "error": "Invalid JSON format"  
}
```

Causes:

- Malformed JSON
- Missing required fields
- Invalid data types

404 Not Found

```
{  
  "error": "Resource not found"  
}
```

Causes:

- Subscriber/profile/entity does not exist
- Incorrect ID in URL

422 Unprocessable Entity

```
{
  "errors": {
    "imsi": ["has already been taken"],
    "key_set_id": ["does not exist"]
  }
}
```

Causes:

- Validation failures
- Database constraints violated
- Foreign key references do not exist

500 Internal Server Error

```
{
  "error": "Internal server error"
}
```

Causes:

- Database connectivity issues
 - Unexpected application errors
-

Error Handling Flow

API Request

OmniCore
5GC ▼

OmniCall ▼

OmniRAN ▼

OmniCharge ▼

Platform ▼

English ▼

Invalid JSON

Valid

400 Bad Request

Authorized?

No

Yes

401 Unauthorized

Resource Exists?

No

Yes

Size my network

404 Not Found

Data Valid?

No

Yes

422 Validation Error

Process Request

Database OK?

Error

Success

Sizing your network?

Get a deployment estimate in 60 seconds. Pick a workload size, see the topology, and get pricing — no sales call needed.

Test Engineering

500 Server Error

200/201 Success

[← Back to API Reference](#)

API Usage Examples

[← Back to API Reference](#)

Table of Contents

- [Complete Subscriber Provisioning](#)
 - [Dormant Subscriber Pre-Provisioning](#)
 - [Complete Static IP Provisioning](#)
-

Complete Subscriber Provisioning

This example demonstrates the complete workflow for provisioning a new subscriber from scratch. The process involves creating all required profiles and components before creating the subscriber.

Prerequisites: This example uses `jq` for JSON parsing. Install with `apt-get install jq` or `brew install jq`.

Related Sections:

- [Key Set Management](#)
- [APN Profiles](#)
- [EPC Profiles](#)
- [Subscriber Management](#)

1. Create Key Set

```
KEY_SET_ID=$(curl -k -X POST
https://hss.example.com:8443/api/key_set \
-H "Content-Type: application/json" \
-d '{
  "ki": "0123456789ABCDEF0123456789ABCDEF",
  "opc": "FEDCBA9876543210FEDCBA9876543210",
  "authentication_algorithm": "milenege",
  "amf": "8000",
  "sqn": 0
}' | jq -r '.response.id')
```

2. Create APN QoS Profile

```
APN_QOS_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/qos_profile \
-H "Content-Type: application/json" \
-d '{
  "name": "Default Internet QoS",
  "allocation_retention_priority": 8,
  "apn_ambr_dl_kbps": 50000,
  "apn_ambr_ul_kbps": 25000,
  "pre_emption_capability": true,
  "pre_emption_vulnerability": true,
  "qci": 9
}' | jq -r '.response.id')
```

3. Create APN Identifier

```
APN_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/identifier \
-H "Content-Type: application/json" \
-d '{
  "apn": "internet",
  "ip_version": "ipv4v6"
}' | jq -r '.response.id')
```

4. Create APN Profile

```
APN_PROFILE_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/profile \
-H "Content-Type: application/json" \
-d '{
  "apn_identifier_id": \"$APN_ID\",
  "apn_qos_profile_id": \"$APN_QOS_ID\",
  "name": \"Internet APN\"
}
```

```

}" | jq -r '.response.id')

# 5. Create EPC Profile
EPC_PROFILE_ID=$(curl -k -X POST
https://hss.example.com:8443/api/epc/profile \
-H "Content-Type: application/json" \
-d "{
  \"apn_profiles\": [$APN_PROFILE_ID],
  \"name\": \"Standard Data Plan\",
  \"network_access_mode\": \"packet_only\",
  \"tracking_area_update_interval_seconds\": 600,
  \"ue_ambr_dl_kbps\": 100000,
  \"ue_ambr_ul_kbps\": 50000
}" | jq -r '.response.id')

# 6. Create Subscriber
SUBSCRIBER_ID=$(curl -k -X POST
https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d "{
  \"imsi\": \"001001123456789\",
  \"key_set_id\": \"$KEY_SET_ID\",
  \"epc_profile_id\": \"$EPC_PROFILE_ID\"
}" | jq -r '.response.id')

echo "Subscriber provisioned successfully with ID: $SUBSCRIBER_ID"

```

What This Creates:

This provisioning workflow creates a complete subscriber with:

1. **Cryptographic keys** ([Key Set](#)) - For authentication
2. **Data service profile** ([EPC Profile](#)) - Bandwidth and network access settings
3. **APN configuration** ([APN Profile](#)) - Access point with QoS
4. **Subscriber record** ([Subscriber](#)) - The actual subscriber entity

Next Steps:

- Add phone numbers: See [MSISDN Management](#)
- Enable voice services: Create and assign [IMS Profile](#)

- Configure roaming: Create and assign [Roaming Profile](#)
- Link physical SIM: Create and assign [SIM](#)

See Also:

- [Multi-MSISDN Documentation](#) - Assigning multiple phone numbers
 - [Profiles Documentation](#) - Advanced profile configuration
-


Dormant Subscriber Pre-Provisioning

Use this workflow to load subscribers in bulk from a SIM vendor output file, and to activate each subscriber later. This is the recommended model for most operators.

A dormant subscriber holds only its identity and its authentication keys. You add the phone number and the service profiles at activation. This matches the data that a SIM vendor sends you. The SIM vendor file contains the ICCID, the PIN, PUK, and ADM codes, and the authentication keys (Ki, OPc). The file does not contain a phone number or a service plan.

The database needs only the IMSI and the Key Set to insert a Subscriber. This is what makes a dormant record possible. It does not mean the other objects are optional for service. Each object is required for its own service: the EPC profile for data, the IMS profile and an MSISDN for voice, and a SIM for authentication. A dormant subscriber does not work on the network until you assign the matching object. You assign these objects when the customer activates the service. For the reason that the SIM, the Key Set, and the Subscriber are separate objects, see [Key Set, SIM, and Subscriber](#).

Provisioning Lifecycle



Step 1: Import (create the SIM, the Key Set, and a disabled Subscriber)

Create one Key Set, one SIM, and one disabled Subscriber for each row in the SIM vendor file. This example uses `jq` to read the returned identifier from each response.

```
# 1. Create the Key Set from the SIM vendor file (Ki, OPc)
KEY_SET_ID=$(curl -k -X POST
https://hss.example.com:8443/api/key_set \
-H "Content-Type: application/json" \
-d '{
  "ki": "0123456789ABCDEF0123456789ABCDEF",
  "opc": "FEDCBA9876543210FEDCBA9876543210",
  "authentication_algorithm": "milenage",
  "amf": "8000",
  "sqn": 0
}' | jq -r '.response.id')

# 2. Create the SIM from the SIM vendor file (ICCID, PIN/PUK/ADM)
SIM_ID=$(curl -k -X POST https://hss.example.com:8443/api/sim \
-H "Content-Type: application/json" \
-d '{
  "iccid": "89440000000000000001",
  "is_esim": false,
  "ind_length": 5
}' | jq -r '.response.id')

# 3. Create the Subscriber in a disabled state.
#   imsi and key_set_id are required. Link the SIM. Add no MSISDN
#   and no profiles.
SUBSCRIBER_ID=$(curl -k -X POST
https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d "{
  \"imsi\": \"0010100000000001\",
  \"key_set_id\": \"${KEY_SET_ID}\",
  \"sim_id\": \"${SIM_ID}\",
  \"enabled\": false,
  \"ims_enabled\": false
}" | jq -r '.response.id')
```

A dormant Subscriber is safe to keep in the database. The subscriber does not attach, authenticate, or register while it is disabled. If the network queries a dormant subscriber, the HSS rejects the request. See [Dormant Subscriber Behaviour on the Network](#).

Step 2: Activate (assign the number and the profiles, then enable)

To activate a subscriber, send one `PATCH` request. Add the MSISDN, assign the profiles, and set `enabled` to `true`.

```
curl -k -X PATCH
https://hss.example.com:8443/api/subscriber/$SUBSCRIBER_ID \
-H "Content-Type: application/json" \
-d "{
  \"enabled\": true,
  \"ims_enabled\": true,
  \"msisdns\": [\"$MSISDN_ID\"],
  \"epc_profile_id\": \"$EPC_PROFILE_ID\",
  \"ims_profile_id\": \"$IMS_PROFILE_ID\",
  \"roaming_profile_id\": \"$ROAMING_PROFILE_ID\"
}"
```

A `PATCH` request changes only the fields that you send. The IMSI, the Key Set, and the SIM stay as they are. Create the MSISDN and the profiles first, or reuse existing identifiers. See [Complete Subscriber Provisioning](#) for how to create the profiles.

Step 3: Deactivate (disable the subscriber)

To deactivate a subscriber, set `enabled` to `false`. The subscriber record and its data stay in the database.

```
curl -k -X PATCH
https://hss.example.com:8443/api/subscriber/$SUBSCRIBER_ID \
-H "Content-Type: application/json" \
-d '{
  "enabled": false,
  "ims_enabled": false
}'
```

To remove IMS voice only, and to keep the data service, set `ims_enabled` to `false` and leave `enabled` as `true`.

Dormant Subscriber Behaviour on the Network

A subscriber fails closed while it is dormant or disabled. The HSS rejects the request on the network interface. The HSS also writes a warning log with the exact reason. The reason is one of the following:

- The subscriber is disabled (`enabled` is `false`).
- IMS is disabled for the subscriber (`ims_enabled` is `false`).
- A required object is not assigned yet. For example, there is no EPC profile for an LTE attach, or no IMS profile for IMS registration.

The reject uses the Experimental-Result-Code `DIAMETER_ERROR_USER_UNKNOWN` (5001) on the S6a and Cx interfaces, per [3GPP TS 29.272](#) and [3GPP TS 29.229](#). The warning log names the IMSI and the exact reason. The log lets you tell a dormant subscriber apart from an unknown IMSI.

Complete Static IP Provisioning

This example demonstrates provisioning a subscriber with a static IP address from scratch.

Scenario: Provision an IoT device subscriber that needs a static IPv4 address on the "internet" APN.


```
# Prerequisites: jq must be installed (apt-get install jq or brew install jq)
```

1. Create Key Set

```
KEY_SET_ID=$(curl -k -X POST
https://hss.example.com:8443/api/key_set \
-H "Content-Type: application/json" \
-d '{
  "ki": "0123456789ABCDEF0123456789ABCDEF",
  "opc": "FEDCBA9876543210FEDCBA9876543210",
  "authentication_algorithm": "milenage",
  "amf": "8000",
  "sqn": 0
}' | jq -r '.response.id')
```

2. Create APN QoS Profile

```
APN_QOS_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/qos_profile \
-H "Content-Type: application/json" \
-d '{
  "name": "IoT Best Effort",
  "allocation_retention_priority": 8,
  "apn_ambr_dl_kbps": 10000,
  "apn_ambr_ul_kbps": 5000,
  "pre_emption_capability": false,
  "pre_emption_vulnerability": false,
  "qci": 9
}' | jq -r '.response.id')
```

3. Create APN Identifier

```
APN_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/identifier \
-H "Content-Type: application/json" \
-d '{
  "apn": "internet",
  "ip_version": "ipv4"
}' | jq -r '.response.id')
```

4. Create APN Profile

```
APN_PROFILE_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/profile \
-H "Content-Type: application/json" \
-d "{
```

```
\ "apn_identifier_id\ ": \ "$APN_ID\ ",  
\ "apn_qos_profile_id\ ": \ "$APN_QOS_ID\ ",  
\ "name\ ": \ "IoT Internet APN\  
}" | jq -r '.response.id')
```

5. Create Static IP for the APN

```
STATIC_IP_ID=$(curl -k -X POST  
https://hss.example.com:8443/api/epc/static_ip \  
-H "Content-Type: application/json" \  
-d "{  
  \ "apn_profile_id\ ": \ "$APN_PROFILE_ID\  
  \ "ipv4_static_ip\ ": \ "100.64.1.100\  
}" | jq -r '.response.id')
```

6. Create EPC Profile

```
EPC_PROFILE_ID=$(curl -k -X POST  
https://hss.example.com:8443/api/epc/profile \  
-H "Content-Type: application/json" \  
-d "{  
  \ "apn_profiles\ ": [$APN_PROFILE_ID],  
  \ "name\ ": \ "IoT Data Plan\  
  \ "network_access_mode\ ": \ "packet_only\  
  \ "tracking_area_update_interval_seconds\ ": 600,  
  \ "ue_ambr_dl_kbps\ ": 10000,  
  \ "ue_ambr_ul_kbps\ ": 5000  
}" | jq -r '.response.id')
```

7. Create MSISDN (phone number)

```
MSISDN_ID=$(curl -k -X POST  
https://hss.example.com:8443/api/msisdn \  
-H "Content-Type: application/json" \  
-d '{  
  "msisdn": "14155551000"  
' | jq -r '.response.id')
```

8. Create Subscriber with Static IP

```
SUBSCRIBER_ID=$(curl -k -X POST  
https://hss.example.com:8443/api/subscriber \  
-H "Content-Type: application/json" \  
-d "{  
  \ "imsi\ ": \ "0010019999999999\  
  \ "key_set_id\ ": \ "$KEY_SET_ID\  
  \ "epc_profile_id\ ": \ "$EPC_PROFILE_ID\  
  \ "msisdns\ ": [$MSISDN_ID],
```

```
\ "static_ips\": [$STATIC_IP_ID]
}" | jq -r '.response.id')
```

```
echo "IoT Subscriber provisioned successfully!"
echo "  Subscriber ID: $SUBSCRIBER_ID"
echo "  IMSI: 001001999999999"
echo "  MSISDN: 14155551000"
echo "  Static IPv4: 100.64.1.100 (on 'internet' APN)"
```

What This Creates:

This provisioning workflow creates a complete IoT subscriber with:

1. **Cryptographic keys** ([Key Set](#)) - For authentication
2. **APN configuration** ([APN Profile](#)) - "internet" access point
3. **Static IP assignment** ([Static IP](#)) - Fixed IPv4 address 100.64.1.100
4. **Data service profile** ([EPC Profile](#)) - IoT-optimized bandwidth limits
5. **Phone number** ([MSISDN](#)) - For device identification
6. **Subscriber record** ([Subscriber](#)) - The complete subscriber entity

Result:

When this subscriber attaches to the network and connects to the "internet" APN, they will receive the static IP address `100.64.1.100` instead of a dynamic DHCP address.

Next Steps:

- Add additional APNs with static IPs: Repeat steps 2-5 for each APN
- Enable voice services: Create and assign [IMS Profile](#)
- Configure roaming: Create and assign [Roaming Profile](#)
- Link physical SIM: Create and assign [SIM](#)

See Also:

- [Static IP Management](#) - Detailed static IP documentation
 - [Complete Subscriber Provisioning](#) - Basic provisioning without static IP
 - [Multi-MSISDN Documentation](#) - Assigning multiple phone numbers
-

[← Back to API Reference](#)

OmniHSS API Reference

[← Back to Operations Guide](#)

Table of Contents

- [API Overview](#)
 - [Key Set Management](#)
 - [Subscriber Management](#)
 - [Sh RepositoryData \(Transparent Data\)](#)
 - [MSISDN Management](#)
 - [SIM Management](#)
 - [Key Set Management](#)
 - [Profile Management](#)
 - [Static IP Management](#)
 - [Roaming Management](#)
 - [EIR Management](#)
 - [Status and Health](#)
 - [Error Handling](#)
 - [API Usage Examples](#)
-

API Overview

Base URL

```
https://[hostname]:8443/api
```

Request Format

- **Content-Type:** application/json
- **Protocol:** HTTPS only
- **Port:** 8443 (configurable)

Important: All API endpoints expect "flat" JSON payloads without wrapper objects.

Correct Format:

```
{  
  "name": "value",  
  "field": "value"  
}
```

Incorrect Format (Do Not Use):

```
{  
  "subscriber": {  
    "name": "value",  
    "field": "value"  
  }  
}
```

Example:

```
# ✓ Correct  
curl -X POST https://hss.example.com:8443/api/ims/profile \  
  -H "Content-Type: application/json" \  
  -d '{"name": "default", "ifc_template": "..."}'  
  
# ✗ Incorrect  
curl -X POST https://hss.example.com:8443/api/ims/profile \  
  -H "Content-Type: application/json" \  
  -d '{"ims_profile": {"name": "default", "ifc_template": "..."}}'
```

Response Format

All responses are JSON with the following structure:

Success Response:

```
{
  "status": "success",
  "response": { ... }
}
```


Error Response:

```
{
  "status": "error",
  "response": {
    "invalid_fields": {
      "field_name": "error message"
    }
  }
}
```

HTTP Status Codes

Code	Meaning	Use Case
200	OK	Successful GET, PUT, DELETE
201	Created	Successful POST
400	Bad Request	Invalid input data
404	Not Found	Resource does not exist
422	Unprocessable Entity	Validation error
500	Internal Server Error	Server-side error

API Request Flow



Subscriber Management

List Subscribers

Retrieve all subscribers or filter by criteria.

Endpoint: `GET /api/subscriber`

Query Parameters:

Parameter	Type	Description
enabled	boolean	Filter by enabled status
ims_enabled	boolean	Filter by IMS enabled status

Example Request:

```
curl -k https://hss.example.com:8443/api/subscriber
```

Example Response:

```
{
  "data": [
    {
      "id": "d290flee-6c54-4b01-90e6-d701748f0851",
      "imsi": "001001123456789",
      "enabled": true,
      "ims_enabled": true,
      "sim_id": "3f2504e0-4f89-41d3-9a0c-0305e82c3301",
      "key_set_id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
      "epc_profile_id": "e58ed763-928c-4155-bee9-fdbaaadc15f3",
      "ims_profile_id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
      "roaming_profile_id": "9c858901-8a57-4791-81fe-4c455b099bc9",
      "custom_attributes": {},
      "inserted_at": "2025-10-15T10:30:00Z",
      "updated_at": "2025-10-15T10:30:00Z"
    }
  ]
}
```

Get Subscriber by ID

Retrieve a specific subscriber by database ID.

Endpoint: GET /api/subscriber/:id

Path Parameters:

Parameter	Type	Description
id	string (UUID)	Subscriber database ID

Example Request:

```
curl -k https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-90e6-d701748f0851
```

Get Subscriber by IMSI

Retrieve a subscriber by their IMSI.

Endpoint: GET /api/subscriber/imsi/:imsi

Path Parameters:

Parameter	Type	Description	Format
imsi	string	International Mobile Subscriber Identity	14-15 digits

Example Request:

```
curl -k https://hss.example.com:8443/api/subscriber/imsi/001001123456789
```

Use Case: Troubleshooting a specific subscriber by their IMSI.

Get Subscriber by MSISDN

Retrieve a subscriber by their phone number.

Endpoint: GET /api/subscriber/msisdn/:msisdn

Path Parameters:

Parameter	Type	Description	Format
msisdn	string	Mobile Station ISDN Number	1-15 digits (E.164)

Example Request:

```
curl -k
https://hss.example.com:8443/api/subscriber/msisdn/14155551234
```

Use Case: Looking up subscriber information when you only have their phone number.

Create Subscriber

Provision a new subscriber.

Endpoint: POST /api/subscriber

Request Body:

```
{
  "subscriber": {
    "imsi": "001001123456789",
    "enabled": true,
    "ims_enabled": true,
    "sim_id": "3f2504e0-4f89-41d3-9a0c-0305e82c3301",
    "key_set_id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
    "epc_profile_id": "e58ed763-928c-4155-bee9-fdbaaadc15f3",
    "ims_profile_id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
    "roaming_profile_id": "9c858901-8a57-4791-81fe-4c455b099bc9",
    "custom_attributes": {
      "note": "Test subscriber"
    }
  }
}
```

Required Fields:

- `imsi` - Must be 14-15 digits, unique
- `key_set_id` - Must reference existing [Key Set](#)
- `epc_profile_id` - Must reference existing [EPC Profile](#)

Optional Fields:

- `enabled` - Default: true
- `ims_enabled` - Default: true
- `sim_id` - Reference to [SIM card](#)
- `ims_profile_id` - Reference to [IMS Profile](#) (required for IMS services)
- `roaming_profile_id` - Reference to [Roaming Profile](#) (required for roaming control)
- `msisdns` - Array of [MSISDN](#) IDs (phone numbers)
- `static_ips` - Array of [Static IP](#) IDs for APN assignments
- `custom_attributes` - Custom key-value pairs


See Also:

- [Complete Subscriber Provisioning Example](#) - End-to-end workflow
- [Multi-MSISDN Documentation](#) - Assigning phone numbers to subscribers
- [Static IP Management](#) - Assigning static IPs to APNs

Example Request:

```
curl -k -X POST https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "imsi": "001001123456789",
    "key_set_id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
    "epc_profile_id": "e58ed763-928c-4155-bee9-fdbaaadc15f3"
  }
}'
```

Provisioning Flow:



Update Subscriber

Modify an existing subscriber.

Endpoint: PUT /api/subscriber/:id

Path Parameters:

Parameter	Type	Description
id	string (UUID)	Subscriber database ID

Request Body:

```
{
  "subscriber": {
    "enabled": false,
    "ims_enabled": false,
    "epc_profile_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
    "custom_attributes": {
      "note": "Temporarily disabled"
    }
  }
}
```

Updatable Fields:

- enabled - Enable/disable all services
- ims_enabled - Enable/disable IMS services
- sim_id - Change SIM card assignment
- key_set_id - Change crypto keys (be careful!)
- epc_profile_id - Change data service profile
- ims_profile_id - Change voice service profile
- roaming_profile_id - Change roaming policy
- msisdns - Update phone numbers assigned to subscriber
- static_ips - Update static IP assignments to APNs
- custom_attributes - Update custom data

Not Updatable:

- `imsi` - Cannot change IMSI (delete and recreate instead)

See Also:

- [Profile Management](#) - Managing service profiles

Example Request:

```
curl -k -X PUT
https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-
90e6-d701748f0851 \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "enabled": false
  }
}'
```

Use Cases:

- Temporarily disable subscriber: `{"enabled": false}`
- Disable voice services only: `{"ims_enabled": false}`
- Change service profile: `{"epc_profile_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479"}` (see [EPC Profiles](#))
- Update roaming policy: `{"roaming_profile_id": "1b671a64-40d5-491e-99b0-da01ff1f3341"}` (see [Roaming Management](#))

Delete Subscriber

Remove a subscriber from the system.

Endpoint: `DELETE /api/subscriber/:id`

Path Parameters:

Parameter	Type	Description
<code>id</code>	string (UUID)	Subscriber database ID

Example Request:

```
curl -k -X DELETE
https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-
90e6-d701748f0851
```

Warning: This permanently deletes the subscriber and all associated state data (PDN sessions, calls, etc.). The IMSI can be reused after deletion.

Note: Deleting a subscriber does NOT delete the associated:

- **Key Set** - Can be reused for other subscribers
- **SIM** - Can be reassigned to a new subscriber
- **Profiles** - Shared resources used by multiple subscribers
- **MSISDNs** - Must be deleted separately if desired

Cancel Location Request (Force Detach)

Send a Cancel Location Request (CLR) to force detach a subscriber from their currently registered MME.

Endpoint: `POST /api/subscriber/cancel_location`

Request Body:

```
{
  "imsi": "001001123456789"
}
```

Parameters:

Parameter	Type	Required	Description
imsi	string	Yes	IMSI of subscriber to detach (14-15 digits)

Example Request:

```
curl -k -X POST
https://hss.example.com:8443/api/subscriber/cancel_location \
-H "Content-Type: application/json" \
-d '{"imsi": "001001123456789"}'
```

Success Response (200 OK):

```
{
  "data": {
    "message": "Cancel Location Request sent successfully",
    "imsi": "001001123456789",
    "destination_host": "mme01.operator.com",
    "destination_realm": "epc.operator.com"
  }
}
```

Error Response (404 Not Found):

```
{
  "error": "Subscriber not found or not currently registered at any MME"
}
```

Behavior:

- Sends S6a CLR to the MME where subscriber is currently registered (`subscriber_state.last_seen_mme`)
- Uses `Cancellation-Type: subscription_withdrawal` (forces full detach)
- Sets `CLR-Flags: {s6a_indicator: 1, reattach_required: 1}` (UE must re-authenticate)

- Returns 404 if subscriber has never registered or `last_seen_mme` is null
- **Affects all MSISDNs** associated with the IMSI (same physical device/SIM)

Use Cases:

- **Fraud Prevention:** Immediately detach suspicious subscriber
- **Subscription Termination:** Force logout when account is disabled
- **Troubleshooting:** Clear stale MME registration for debugging
- **Migration:** Force re-authentication to apply new profile settings
- **Security:** Immediately disconnect compromised subscriber

Multi-IMSI Considerations:

When using CLR with multi-MSISDN scenarios:

1. Multiple MSISDNs, Single IMSI:

```
// Subscriber has IMSI 001001123456789 with MSISDNs  
["+1234567890", "+9876543210"]  
POST /api/subscriber/cancel_location  
{  
  "imsi": "001001123456789"  
}  
  
// Result: One CLR sent, both MSISDNs affected (same device)
```

2. Different IMSIs (Different Devices):

```
// Two subscribers with same MSISDN but different IMSIs (number  
porting scenario)  
// Subscriber A: IMSI 0010011111111111, MSISDN "+1234567890"  
// Subscriber B: IMSI 0010012222222222, MSISDN "+1234567890"  
  
POST /api/subscriber/cancel_location  
{  
  "imsi": "0010011111111111"  
}  
  
// Result: Only Subscriber A detached, Subscriber B unaffected
```

Important Notes:

- **IMSI-based:** CLR is always sent per IMSI, not per MSISDN

- **Asynchronous:** CLR is sent asynchronously; success response means CLR was sent, not that MME processed it
- **No validation of MME status:** CLR is sent even if MME is unreachable (standard HSS behavior)
- **Idempotent:** Safe to call multiple times for same IMSI

Related Documentation:

- [Cancel Location Request Protocol Flow](#)
- [Multi-IMSI Scenarios](#)
- [S6a Interface Architecture](#)

Sh RepositoryData (Transparent Data)

Provisioning access to a subscriber's Sh transparent documents (MMTEL-Services, IMS-ODB-Information, and others). These are the same opaque documents that an Application Server reads and writes over the Diameter Sh interface. Access is via `GET/PUT/DELETE` `/api/subscriber/repository_data/:imsi`.

See [Sh RepositoryData \(Transparent Data\)](#) for the data model, message flows, SequenceNumber concurrency rules, and the full REST API reference.

MSISDN Management

MSISDNs (phone numbers) can be assigned to subscribers to enable voice services. See [Multi-MSISDN Documentation](#) for details on assigning multiple numbers to a single subscriber.

List MSISDNs

Retrieve all phone numbers.

Endpoint: GET /api/msisdn

Example Request:

```
curl -k https://hss.example.com:8443/api/msisdn
```

Get MSISDN

Retrieve a specific phone number.

Endpoint: GET /api/msisdn/:id

Example Request:

```
curl -k https://hss.example.com:8443/api/msisdn/16fd2706-8baf-433b-82eb-8c7fada847da
```

Create MSISDN

Create a new phone number.

Endpoint: POST /api/msisdn

Request Body:

```
{
  "msisdn": {
    "msisdn": "14155551234"
  }
}
```

Validation:

- Must be 1-15 digits
- Must be unique
- Must follow E.164 format (international format without + sign)


Example Request:

```
curl -k -X POST https://hss.example.com:8443/api/msisdn \  
-H "Content-Type: application/json" \  
-d '{  
  "msisdn": {  
    "msisdn": "14155551234"  
  }  
'
```

Assign MSISDN to Subscriber

To assign a phone number to a subscriber, you need to create a join record. This is typically done through the subscriber update endpoint or via direct database manipulation.

Multi-MSISDN Pattern:



See [Multi-MSISDN and Multi-IMSI Features](#) for detailed usage.

Delete MSISDN

Remove a phone number.

Endpoint: DELETE /api/msisdn/:id

Example Request:

```
curl -k -X DELETE
https://hss.example.com:8443/api/msisdn/16fd2706-8baf-433b-82eb-
8c7fada847da
```

SIM Management

SIM card records store physical SIM card information including ICCID, vendor details, PIN/PUK codes, and OTA keys. SIM records can optionally be linked to [subscribers](#).

See Also:

- [Multi-IMSI Documentation](#) - Multiple subscribers on one physical SIM

List SIMs

Retrieve all SIM cards.

Endpoint: GET /api/sim

Example Request:

```
curl -k https://hss.example.com:8443/api/sim
```

Get SIM

Retrieve a specific SIM card.

Endpoint: GET /api/sim/:id

Example Request:

```
curl -k https://hss.example.com:8443/api/sim/3f2504e0-4f89-41d3-9a0c-0305e82c3301
```

Create SIM

Create a new SIM card record.

Endpoint: POST /api/sim

Request Body:

```
{
  "sim": {
    "iccid": "8991101200003204510",
    "sim_vendor": "Gemalto",
    "batch_name": "2025-Q1-Batch-01",
    "is_esim": false,
    "pin1": "1234",
    "pin2": "5678",
    "puk1": "12345678",
    "puk2": "87654321",
    "adm1": "admin-code-1",
    "kic": "0123456789ABCDEF0123456789ABCDEF",
    "kid": "FEDCBA9876543210FEDCBA9876543210"
  }
}
```

Required Fields:

- iccid - 19-20 digits, unique

Optional but Important Fields:

- sim_vendor - Manufacturer name
- batch_name - For tracking

- `is_esim` - Boolean flag for eSIM
- `pin1`, `pin2` - End-user PIN codes
- `puk1`, `puk2` - PIN unlock codes
- `adm1-adm10` - Administrative codes
- `kic`, `kid` - OTA security keys (hex string)

Example Request:

```
curl -k -X POST https://hss.example.com:8443/api/sim \
-H "Content-Type: application/json" \
-d '{
  "sim": {
    "iccid": "8991101200003204510",
    "sim_vendor": "Gemalto"
  }
}'
```

Update SIM

Modify SIM card data.

Endpoint: `PUT /api/sim/:id`

Example Request:

```
curl -k -X PUT https://hss.example.com:8443/api/sim/3f2504e0-4f89-
41d3-9a0c-0305e82c3301 \
-H "Content-Type: application/json" \
-d '{
  "sim": {
    "batch_name": "Updated-Batch-Name"
  }
}'
```

Delete SIM

Remove a SIM card record.

Endpoint: DELETE /api/sim/:id

Warning: Ensure no subscribers reference this SIM before deleting.

Key Set Management

Key sets contain the cryptographic material (Ki, OPC/OP, AMF, SQN) used for subscriber authentication via the Milenage algorithm. Each **subscriber** must reference a key set.

See Also:

- **Protocol Flows** - Authentication procedures using key sets

List Key Sets

Retrieve all cryptographic key sets.

Endpoint: GET /api/key_set

Example Request:

```
curl -k https://hss.example.com:8443/api/key_set
```

Get Key Set

Retrieve a specific key set.

Endpoint: GET /api/key_set/:id

Example Request:

```
curl -k https://hss.example.com:8443/api/key_set/6ba7b810-9dad-41d1-80b4-00c04fd430c8
```

Response Example:

```
{
  "data": {
    "id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
    "ki": "0123456789ABCDEF0123456789ABCDEF",
    "opc": "FEDCBA9876543210FEDCBA9876543210",
    "op": null,
    "amf": "8000",
    "sqn": 0,
    "authentication_algorithm": "milenage",
    "ota_counter": 0
  }
}
```

Create Key Set

Create a new cryptographic key set.

Endpoint: POST /api/key_set

Request Body:

```
{
  "key_set": {
    "ki": "0123456789ABCDEF0123456789ABCDEF",
    "opc": "FEDCBA9876543210FEDCBA9876543210",
    "amf": "8000",
    "sqn": 0,
    "authentication_algorithm": "milenage"
  }
}
```

Required Fields:

- `ki` - 128-bit key (32 hex characters)
- Either `opc` OR `op` (OPC can be derived from OP)
- `authentication_algorithm` - Currently only "milenage"

Optional Fields:

- `amf` - Default: "8000"
- `sqn` - Default: 0
- `ota_counter` - Default: 0

Key Format:

- All keys are hexadecimal strings
- Ki, OPC, OP: 32 hex characters (128 bits)
- AMF: 4 hex characters (16 bits)

Example Request:

```
curl -k -X POST https://hss.example.com:8443/api/key_set \
-H "Content-Type: application/json" \
-d '{
  "key_set": {
    "ki": "0123456789ABCDEF0123456789ABCDEF",
    "opc": "FEDCBA9876543210FEDCBA9876543210",
    "authentication_algorithm": "milena"
  }
}'
```

Security Warning: Key sets contain highly sensitive cryptographic material. Protect API access accordingly.

Update Key Set

Modify an existing key set.

Endpoint: `PUT /api/key_set/:id`

Warning: Changing keys for an active **subscriber** will cause authentication failures. Only update keys during maintenance windows or for new subscribers.

Impact: Updates affect all subscribers using this key set immediately. Active subscribers will fail authentication on next attach attempt.

Delete Key Set

Remove a key set.

Endpoint: DELETE /api/key_set/:id

Warning: Ensure no [subscribers](#) reference this key set before deleting. Query subscribers first to check for references.

Profile Management

EPC Profiles

EPC (Evolved Packet Core) profiles define data service parameters for subscribers. These profiles are referenced when creating [subscribers](#).

List EPC Profiles

Endpoint: GET /api/epc/profile

Get EPC Profile

Endpoint: GET /api/epc/profile/:id

Create EPC Profile

Endpoint: POST /api/epc/profile

Request Body:

```

{
  "apn_profiles": [],
  "name": "Standard Data Plan",
  "network_access_mode": "packet_only",
  "tracking_area_update_interval_seconds": 600,
  "ue_ambr_dl_kbps": 100000,
  "ue_ambr_ul_kbps": 50000
}

```

Fields:

Field	Description	Units	Type
<code>name</code>	Profile name	Text	Unique
<code>ue_ambr_dl_kbps</code>	Download bandwidth limit	Kbps	1000
<code>ue_ambr_ul_kbps</code>	Upload bandwidth limit	Kbps	5000
<code>network_access_mode</code>	Access type	String	"packet" or "circuit"
<code>tracking_area_update_interval_seconds</code>	TAU timer	Seconds	600 (min)
<code>apn_profiles</code>	List of APN profile IDs	Array	[] or [1, 2, 3]

Example Request:

```
curl -k -X POST https://hss.example.com:8443/api/epc/profile \
-H "Content-Type: application/json" \
-d '{
  "apn_profiles": [],
  "name": "Premium 100Mbps",
  "network_access_mode": "packet_only",
  "tracking_area_update_interval_seconds": 600,
  "ue_ambr_dl_kbps": 100000,
  "ue_ambr_ul_kbps": 50000
}'
```

See Also:

- [Profiles Documentation](#) - Detailed profile configuration guide
- [Complete Subscriber Provisioning](#) - Using EPC profiles in provisioning

Update EPC Profile

Endpoint: PUT /api/epc/profile/:id

Note: Changes to EPC profiles affect all [subscribers](#) using this profile. Active sessions may need to be re-established.

Delete EPC Profile

Endpoint: DELETE /api/epc/profile/:id

Warning: Ensure no [subscribers](#) reference this profile before deleting.

IMS Profiles

IMS (IP Multimedia Subsystem) profiles define voice service parameters and Initial Filter Criteria (IFC) for subscribers. These profiles are referenced when creating [subscribers](#) with IMS services enabled.

List IMS Profiles

Endpoint: GET /api/ims/profile

Create IMS Profile

Endpoint: POST /api/ims/profile

Request Body:

```
{
  "name": "Standard VoLTE",
  "ifc_template": "<IMS-XML-Template-Here>"
}
```

Required Fields:

- `name` - Profile name (must be unique)
- `ifc_template` - IFC (Initial Filter Criteria) XML template with Liquid template variables

IFC Template Variables:

The IFC template supports the following Liquid template variables that are dynamically substituted:

Variable	Description	Example Value
<code>{{ imsi }}</code>	Subscriber IMSI	<code>001001123456789</code>
<code>{{ msisdns }}</code>	Array of MSISDNs (for loops)	<code>["14155551234", "14155555678"]</code>
<code>{{ mcc }}</code>	Mobile Country Code	<code>001</code>
<code>{{ mnc }}</code>	Mobile Network Code	<code>001</code>

How Template Rendering Works:

The IFC template is stored as a **Liquid template** (similar to Jinja2) and is rendered **dynamically** during IMS operations:

1. **Storage:** When you create an IMS profile, the template is stored as-is with variables like `{{ imsi }}` and `{% for msisdn in msisdns %}`

2. **Validation:** The API validates the template by rendering it with test data to ensure valid XML syntax
3. **Runtime Rendering:** When a subscriber performs IMS registration (MAA/SAA), the HSS:
 - Retrieves the subscriber's IMS profile
 - Renders the template with the subscriber's actual data:
 - `{{ imsi }}` → subscriber's IMSI
 - `{{ msisdns }}` → subscriber's phone numbers
 - `{{ mcc }}` → configured Mobile Country Code
 - `{{ mnc }}` → configured Mobile Network Code
 - Returns the rendered XML to the S-CSCF via Cx/Diameter

Template Syntax:

```
<!-- Simple variable substitution -->
{{ imsi }}

<!-- For loops over arrays -->
{% for msisdn in msisdns %}
  <MSISDN>{{ msisdn }}</MSISDN>
{% endfor %}

<!-- Combining variables -->
{{ imsi }}@ims.mnc{{ mnc }}.mcc{{ mcc }}.3gppnetwork.org
```

IFC Template Example:

```

<?xml version="1.0" encoding="UTF-8"?>
<IMSSubscription>
<PrivateID>{{ imsi }}@ims.mnc{{ mnc }}.mcc{{ mcc
}}.3gppnetwork.org</PrivateID>
<ServiceProfile>
{% for msisdn in msisdns %}
<PublicIdentity>
<Identity>sip:{{ msisdn }}@ims.mnc{{ mnc }}.mcc{{ mcc
}}.3gppnetwork.org</Identity>
<Extension>
<IdentityType>0</IdentityType>
</Extension>
</PublicIdentity>
<PublicIdentity>
<Identity>tel:{{ msisdn }}</Identity>
<Extension>
<IdentityType>0</IdentityType>
</Extension>
</PublicIdentity>
{% endfor %}
<InitialFilterCriteria>
<Priority>10</Priority>
<TriggerPoint>
<ConditionTypeCNF>0</ConditionTypeCNF>
<SPT>
<ConditionNegated>0</ConditionNegated>
<Group>0</Group>
<Method>REGISTER</Method>
</SPT>
</TriggerPoint>
<ApplicationServer>
<ServerName>sip:as.ims.mnc{{ mnc }}.mcc{{ mcc
}}.3gppnetwork.org</ServerName>
<DefaultHandling>0</DefaultHandling>
</ApplicationServer>
</InitialFilterCriteria>
</ServiceProfile>
</IMSSubscription>

```

Example Request (curl):

```
curl -k -X POST https://hss.example.com:8443/api/ims/profile \
-H "Content-Type: application/json" \
-d '{
  "name": "default",
  "ifc_template": "<?xml version=\"1.0\" encoding=\"UTF-8\"?>
<IMSSubscription><ServiceProfile>...</ServiceProfile>
</IMSSubscription>"
}'
```

Example Request (Python):

```
import requests

response = requests.post(
    "https://hss.example.com:8443/api/ims/profile",
    json={
        "name": "default",
        "ifc_template": ifc_template_string
    },
    verify=False # For self-signed certificates
)
```

Success Response (201 Created):

```
{
  "status": "success",
  "response": {
    "id": "0f8fad5b-d9cb-469f-a165-70867728950e",
    "name": "default",
    "ifc_template": "<?xml version=\"1.0\" encoding=\"UTF-8\"?
>..."
  }
}
```

Validation:

- The API validates that the IFC template is valid XML
- Template variables are rendered with test data to verify syntax
- The `name` field must be unique and non-empty

See Also:

- [Profiles Documentation](#) - IFC template details and examples
- [Protocol Flows](#) - IMS registration and call flows
- [Default IFC Template](#) - Reference implementation

APN Profiles

APN (Access Point Name) profiles consist of three components that work together:

1. **APN Identifier** - Defines the APN name and IP version
2. **APN QoS Profile** - Defines Quality of Service parameters
3. **APN Profile** - Combines identifier and QoS, linked to [EPC Profiles](#)

See [PCRF Documentation](#) for detailed policy configuration, QoS management, and automatic re-auth. See also [Profiles Documentation](#) for APN configuration examples.

List APN Identifiers

Endpoint: `GET /api/apn/identifier`

Create APN Identifier

Endpoint: `POST /api/apn/identifier`

Request Body:

```
{
  "apn": "internet",
  "ip_version": "ipv4v6"
}
```

IP Version Values:

- `"ipv4"` - IPv4 only
- `"ipv6"` - IPv6 only

- "ipv4v6" - IPv4v6 (dual stack)
- "ipv4_or_ipv6" - IPv4 or IPv6 (network choice)

List APN QoS Profiles

Endpoint: GET /api/apn/qos_profile

Create APN QoS Profile

Endpoint: POST /api/apn/qos_profile

Request Body:

```
{
  "name": "Best Effort Internet",
  "allocation_retention_priority": 8,
  "apn_ambr_dl_kbps": 50000,
  "apn_ambr_ul_kbps": 25000,
  "pre_emption_capability": false,
  "pre_emption_vulnerability": true,
  "qci": 9
}
```

List APN Profiles

Endpoint: GET /api/apn/profile

Create APN Profile

Endpoint: POST /api/apn/profile

Request Body:

```
{
  "apn_identifier_id": "4fa85f64-5717-4562-b3fc-2c963f66afa6",
  "apn_qos_profile_id": "8d8ac610-566d-4ef0-9c22-186b2a5ed793",
  "name": "Internet APN"
}
```

Required Fields:

- `apn_identifier_id` - Must reference existing [APN Identifier](#)
- `apn_qos_profile_id` - Must reference existing [APN QoS Profile](#)


See Also:

- [Complete Subscriber Provisioning](#) - Full example including APN setup
- [EPC Profiles](#) - APN profiles are linked to EPC profiles


Static IP Management

Static IP addresses can be assigned to specific APNs for individual subscribers. This allows subscribers to receive a predetermined IPv4 and/or IPv6 address when connecting to a particular APN, rather than receiving a dynamic address from a DHCP pool.

Architecture:




Data Flow When Subscriber Connects:



Update Location Answer - APN Configuration Data Mapping:

This diagram shows exactly where each field in the S6a Update Location Answer APN-Configuration AVP comes from in the database:




Key Observations:

1. **Context-Identifier:** Sequential index (0, 1, 2...) for each APN in the profile

2. **Service-Selection:** Comes directly from `apn_identifier.apn` (e.g., "internet", "ims")
3. **PDN-Type:** Encoded from `apn_identifier.ip_version` (ipv4=0, ipv6=1, ipv4v6=2, ipv4_or_ipv6=3)
4. **QoS Parameters:** All from `apn_qos_profile` table
5. **AMBR Bandwidth:** Values are multiplied by 1000 (kbps → bps conversion)
6. **Served-Party-IP-Address:** Only included if static IP exists for this subscriber+APN combination
 - Lookup process: `subscriber.static_ips` → filter by `apn_profile_id` → extract IPs
 - IP version compatibility checked against `apn_identifier.ip_version`
7. **VPLMN-Dynamic-Address-Allowed:** Hardcoded to 0 (not allowed) - forces use of static IP if provided

Relationship Hierarchy:



Key Concepts:

- **Per-APN Assignment:** Each Static IP is linked to a specific **APN Profile**
- **One IP per APN per Subscriber:** A subscriber can only have one static IP assignment per APN
- **IPv4 and IPv6 Support:** Static IPs can be IPv4-only, IPv6-only, or dual-stack
- **Global IP Uniqueness:** Each IP address must be globally unique across **all** static IP records in the system

- The same IPv4 or IPv6 address cannot be assigned to multiple subscribers (even on different APNs)
- This prevents routing conflicts and IP address ambiguity
- Enforced by database unique indexes on `ipv4_static_ip` and `ipv6_static_ip` fields
- **Many-to-Many Relationship:** Subscribers and Static IPs are linked via a join table

Use Cases:

- Fixed IP addresses for IoT devices
- Server hosting on mobile devices (requires static IP for inbound connections)
- Legacy applications that require specific IP addresses
- Network policy routing based on source IP
- Regulatory compliance requiring IP address tracking

List Static IPs

Retrieve all static IP assignments.

Endpoint: `GET /api/epc/static_ip`

Example Request:

```
curl -k https://hss.example.com:8443/api/epc/static_ip
```

Example Response:

```
{
  "data": [
    {
      "id": "c56a4180-65aa-42ec-a945-5fd21dec0538",
      "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
      "ipv4_static_ip": "100.64.1.1",
      "ipv6_static_ip": "2606:4700:4700::1111",
      "apn_profile": {
        "id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
        "name": "Internet APN",
        "apn_identifier": {
          "apn": "internet",
          "ip_version": "ipv4v6"
        }
      },
      "inserted_at": "2025-11-15T10:30:00Z",
      "updated_at": "2025-11-15T10:30:00Z"
    }
  ]
}
```

Get Static IP

Retrieve a specific static IP assignment.

Endpoint: GET /api/epc/static_ip/:id

Path Parameters:

Parameter	Type	Description
id	string (UUID)	Static IP database ID

Example Request:

```
curl -k https://hss.example.com:8443/api/epc/static_ip/c56a4180-65aa-42ec-a945-5fd21dec0538
```

Create Static IP

Create a new static IP assignment for an APN.

Endpoint: POST /api/epc/static_ip

Request Body:

```
{
  "static_ip": {
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1",
    "ipv6_static_ip": "2606:4700:4700::1111"
  }
}
```

Required Fields:

- `apn_profile_id` - Must reference an existing [APN Profile](#)
- At least one of `ipv4_static_ip` OR `ipv6_static_ip` must be specified

Optional Fields:

- `ipv4_static_ip` - IPv4 address (dotted decimal notation)
- `ipv6_static_ip` - IPv6 address (standard notation)

IP Format Validation:

- IPv4: Standard dotted decimal format (e.g., `100.64.1.1`)
- IPv6: Standard colon-separated hexadecimal format (e.g., `2606:4700:4700::1111`)
- Both IPv4 and IPv6 addresses must be **globally unique across all static IP records**
 - This prevents IP address conflicts in the network
 - The same IP cannot be assigned to multiple subscribers, even on different APNs
 - This is a database-level constraint enforced by unique indexes

Configuration Options:

Configuration	IPv4	IPv6	Example
IPv4 Only	✓	-	<code>{"ipv4_static_ip": "100.64.1.1"}</code>
IPv6 Only	-	✓	<code>{"ipv6_static_ip": "2606:4700:4700::1111"}</code>
Dual Stack	✓	✓	Both fields specified

Example Requests:

IPv4-only Static IP:

```
curl -k -X POST https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1"
  }
}'
```

IPv6-only Static IP:

```
curl -k -X POST https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "b2c3d4e5-f6a7-4b1c-9d2e-3f4a5b6c7d8e",
    "ipv6_static_ip": "2606:4700:4700::1111"
  }
}'
```

Dual-stack Static IP:

```
curl -k -X POST https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1",
    "ipv6_static_ip": "2606:4700:4700::1111"
  }
}'
```

Success Response (201 Created):

```
{
  "data": {
    "id": "c56a4180-65aa-42ec-a945-5fd21dec0538",
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1",
    "ipv6_static_ip": "2606:4700:4700::1111",
    "inserted_at": "2025-11-15T10:30:00Z",
    "updated_at": "2025-11-15T10:30:00Z"
  }
}
```

See Also:

- [Assign Static IP to Subscriber](#) - How to link this to a subscriber
- [APN Profiles](#) - Managing APN configurations

Update Static IP

Modify an existing static IP assignment.

Endpoint: `PUT /api/epc/static_ip/:id`

Path Parameters:

Parameter	Type	Description
id	string (UUID)	Static IP database ID

Request Body:

```
{
  "static_ip": {
    "ipv4_static_ip": "100.64.1.2",
    "ipv6_static_ip": "2606:4700:4700::1112"
  }
}
```

Updatable Fields:

- ipv4_static_ip - Change IPv4 address
- ipv6_static_ip - Change IPv6 address
- apn_profile_id - Change APN assignment

Not Updatable:

- id - Primary key (read-only)

Warning: Changing the IP address for an active subscriber will affect their next PDN connection. Active PDN sessions will continue to use the old IP until they disconnect and reconnect.

Example Request:

```
curl -k -X PUT
https://hss.example.com:8443/api/epc/static_ip/c56a4180-65aa-42ec-
a945-5fd21dec0538 \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "ipv4_static_ip": "100.64.1.2"
  }
}'
```

Delete Static IP

Remove a static IP assignment.

Endpoint: DELETE /api/epc/static_ip/:id

Path Parameters:

Parameter	Type	Description
id	string (UUID)	Static IP database ID

Example Request:

```
curl -k -X DELETE
https://hss.example.com:8443/api/epc/static_ip/c56a4180-65aa-42ec-
a945-5fd21dec0538
```

Behavior:

- Removes the static IP assignment
- Does NOT affect the [APN Profile](#) (APN remains available for other subscribers)
- Subscribers using this static IP will receive dynamic IPs on next connection
- The IP address becomes available for reuse after deletion

Warning: If a subscriber is actively using this static IP, deleting it will cause them to receive a dynamic IP on their next PDN connection. Ensure subscribers are offline or send a [Cancel Location Request](#) before deleting.

Assign Static IP to Subscriber

To assign a static IP to a subscriber, you need to associate the Static IP record with the [Subscriber](#) during creation or update.

Assignment Pattern:

1. **Create the Static IP** (see [Create Static IP](#))
2. **Assign to Subscriber** using the `static_ips` field

Create Subscriber with Static IP:

```
# Step 1: Create static IP for "internet" APN
STATIC_IP_ID=$(curl -k -X POST
https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1",
    "ipv6_static_ip": "2606:4700:4700::1111"
  }
}' | jq -r '.data.id')

# Step 2: Create subscriber with static IP assigned
curl -k -X POST https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d "{
  \"subscriber\": {
    \"imsi\": \"001001123456789\",
    \"key_set_id\": \"6ba7b810-9dad-41d1-80b4-00c04fd430c8\",
    \"epc_profile_id\": \"e58ed763-928c-4155-bee9-
fdbaaadc15f3\",
    \"static_ips\": [$STATIC_IP_ID]
  }
}"
```

Update Existing Subscriber with Static IP:


```
curl -k -X PUT
https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-
90e6-d701748f0851 \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "static_ips": ["c56a4180-65aa-42ec-a945-5fd21dec0538",
"5a8f9c3e-2d4b-4e6f-8a1b-3c5d7e9f0a2b"]
  }
}'
```

Multiple Static IPs (Different APNs):

A subscriber can have multiple static IPs as long as each is for a different APN:

```
# Create static IP for "internet" APN
INTERNET_IP=$(curl -k -X POST
https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "a1b2c3d4-e5f6-4a3b-8c2d-1e0f9a8b7c6d",
    "ipv4_static_ip": "100.64.1.1"
  }
}' | jq -r '.data.id')

# Create static IP for "ims" APN
IMS_IP=$(curl -k -X POST
https://hss.example.com:8443/api/epc/static_ip \
-H "Content-Type: application/json" \
-d '{
  "static_ip": {
    "apn_profile_id": "b2c3d4e5-f6a7-4b1c-9d2e-3f4a5b6c7d8e",
    "ipv4_static_ip": "100.64.2.1"
  }
}' | jq -r '.data.id')

# Assign both to subscriber
curl -k -X POST https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d "{
  \"subscriber\": {
    \"imsi\": \"001001123456789\",
    \"key_set_id\": \"6ba7b810-9dad-41d1-80b4-00c04fd430c8\",
    \"epc_profile_id\": \"e58ed763-928c-4155-bee9-
fdbaaadc15f3\",
    \"static_ips\": [$INTERNET_IP, $IMS_IP]
  }
}"
```

Validation Rules:

- ✓ **Allowed:** Multiple static IPs for different APNs
- ✗ **Rejected:** Multiple static IPs for the same APN

Error Example - Duplicate APN:

```
# This will FAIL if both static IPs reference the same APN
curl -k -X POST https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "imsi": "001001123456789",
    "static_ips": ["c56a4180-65aa-42ec-a945-5fd21dec0538",
"5a8f9c3e-2d4b-4e6f-8a1b-3c5d7e9f0a2b"]
  }
}'

# Error Response:
{
  "errors": {
    "static_ips": [
      "static ips per apn per subscriber must be unique. eg a
subscriber may not be assigned static ip 100.64.1.1 for internet
and also 100.64.1.2 for internet"
    ]
  }
}
```

See Also:

- [Create Subscriber](#) - Subscriber provisioning
- [Update Subscriber](#) - Modifying subscriber configuration
- [Complete Static IP Provisioning Example](#) - End-to-end workflow

Roaming Management

Roaming profiles control whether subscribers can access data and IMS services on visited networks. Profiles are assigned to [subscribers](#) and consist of rules matched by MCC/MNC.

List Roaming Profiles

Endpoint: `GET /api/roaming/profile`

Create Roaming Profile

Endpoint: POST /api/roaming/profile

Request Body:

```
{
  "roaming_profile": {
    "name": "US Carriers Only",
    "data_action_if_no_rules_match": "deny",
    "ims_action_if_no_rules_match": "deny",
    "roaming_rules": []
  }
}
```

Action Values:

- "allow" - Allow
- "deny" - Deny

Default Actions:

- data_action_if_no_rules_match - Action when no roaming rule matches
- ims_action_if_no_rules_match - IMS-specific default action

List Roaming Rules

Endpoint: GET /api/roaming/rule

Create Roaming Rule

Endpoint: POST /api/roaming/rule

Request Body:

```
{
  "roaming_rule": {
    "name": "Allow AT&T",
    "mcc": "310",
    "mnc": "410",
    "data_action": "allow",
    "ims_action": "allow"
  }
}
```

Fields:

- `mcc` - Mobile Country Code (3 digits)
- `mnc` - Mobile Network Code (2-3 digits)
- `data_action` - "allow" or "deny" data services
- `ims_action` - "allow" or "deny" IMS/voice services

See Also:

- [Roaming Documentation](#) - Detailed configuration and examples
- [Protocol Flows](#) - How roaming control works in Diameter flows

EIR Management

OmniHSS functions as an Equipment Identity Register (EIR) via the S13 Diameter interface. EIR rules control device access based on IMEI patterns.

See [EIR Documentation](#) for detailed equipment identity checking, S13 interface flows, and IMEI validation.

List EIR Rules

Endpoint: `GET /api/eir/rule`

Create EIR Rule

Endpoint: POST /api/eir/rule

Request Body:

```
{
  "eir_rule": {
    "name": "Block iPhone 6",
    "imei_regex": "^35[0-9]{6}0[0-9]{7}$",
    "action": 1
  }
}
```

Fields:

- `name` - Descriptive name for the rule
- `imei_regex` - Regular expression to match IMEI numbers
- `action` - Whitelist (0), Blacklist (1), or Greylist (2)

Action Values:

- `0` - Whitelist (allow)
- `1` - Blacklist (deny)
- `2` - Greylist (allow but track)

Use Cases:

- Block stolen devices (blacklist specific IMEIs)
- Restrict device types (blacklist by TAC pattern)
- Allow only approved devices (whitelist pattern with deny-all default)

See Also:

- [Protocol Flows](#) - S13 interface and EIR check flow
 - [Architecture Overview](#) - OmniHSS EIR function
-

Additional Documentation

For more information, see the following documentation:

- **Status and Health** - API health check endpoints
- **Error Handling** - Common errors and troubleshooting
- **API Usage Examples** - Complete provisioning workflows

[← Back to Operations Guide](#) | [Next: Control Panel →](#)

API Status and Health

[← Back to API Reference](#)

System Status

Check if the API is responding.

Endpoint: `GET /api/status`

Example Request:

```
curl -k https://hss.example.com:8443/api/status
```

Example Response:

```
{  
  "status": "ok"  
}
```

Use Case: Health check for load balancers and monitoring systems.

[← Back to API Reference](#)

OmniHSS Architecture Overview


[← Back to Operations Guide](#)

Table of Contents

- [System Overview](#)
 - [Component Architecture](#)
 - [Diameter Stack](#)
 - [Application Layer](#)
 - [Data Layer](#)
 - [External Interfaces](#)
 - [Deployment Architecture](#)
-


System Overview

OmniHSS is built on Elixir and the Erlang/OTP platform, providing a highly concurrent, fault-tolerant system designed for telecommunications workloads. The architecture follows a layered approach with clear separation of concerns.



Component Architecture


Core Components



Diameter Application Handlers

Each Diameter application (S6a, Cx, Sh, S13, Gx, Rx) is implemented as a DiameterEx handler module that:


1. **Registers with DiameterEx** - Subscribes to specific Diameter Application IDs
2. **Validates Requests** - Extracts AVPs, validates subscriber state
3. **Processes Business Logic** - Calls appropriate business logic modules
4. **Constructs Responses** - Builds Diameter answer messages with AVPs
5. **Handles Errors** - Returns appropriate Diameter result codes




Diameter Stack

Diameter Service Configuration


OmniHSS configures a single Diameter service with multiple supported applications:



Peer Connection Management




Diameter Message Flow



Application Layer


S6a Interface (LTE/EPC)

Handles authentication and mobility management for LTE networks.




Cx Interface (IMS)

Handles IMS registration and authentication.




Sh Interface (IMS Profile Data)

Provides IMS application servers access to subscriber profile data.




Gx Interface (Policy Control)

Manages policy and charging control for data sessions. **See [PCRF Documentation](#) for details.**




Rx Interface (IMS Media)

Controls IMS media policy and dedicated bearers for VoLTE. **See [PCRF Documentation](#) for details.**



S13 Interface (EIR)

Validates device IMEI against equipment identity rules. **See [EIR Documentation](#) for details.**



Data Layer


Database Backend

OmniHSS uses **PostgreSQL** as its database backend and **Ecto** as its database abstraction layer. All tables use UUID primary keys for globally unique identification across sites.


For multi-site deployments, OmniHSS uses PostgreSQL's bidirectional logical replication. Each site operates as an independent read/write primary with asynchronous WAL-based replication between sites.

See [Database Replication](#) for multi-site replication configuration and operations.

Database Schema Overview




Ecto Repository Pattern




Optimized Query Strategy

Each Diameter procedure uses optimized queries that preload only necessary associations:




External Interfaces

API Architecture




Control Panel Architecture




Deployment Architecture

Single Node Deployment



Multi-Site HA Deployment (Logical Replication)

For high-availability deployments across geographic sites, OmniHSS uses PostgreSQL bidirectional logical replication. Each site has an independent read/write database.




Key Characteristics:

- **Both Sites Read/Write:** Local writes are instant, never blocked by remote site
- **Asynchronous Replication:** Changes stream via WAL. Replication adds no write latency penalty
- **Partition Tolerant:** Both sites continue operating if the inter-site link goes down. WAL queues locally and catches up on restore
- **No Quorum:** No minimum node count required. Works identically with one site or many
- **UUID Primary Keys:** Globally unique IDs eliminate conflicts between sites

See **Database Replication** for detailed configuration and operations.

Process Flow Example: Authentication

This example shows the complete flow for an authentication request:



Key Architectural Principles

1. Fault Tolerance

- Erlang/OTP supervision trees automatically restart failed processes
- Isolated Diameter handlers prevent cascading failures
- Database connection pooling with automatic reconnection

2. Concurrency

- Each Diameter request handled in its own process
- No shared state between request handlers
- Database connection pooling for parallel queries

3. Modularity

- Each Diameter application in separate module
- Clear separation between interface, business logic, and data layers
- Pluggable authentication algorithms

4. Performance

- Optimized database queries with selective preloading
- Minimal data transfer for each procedure type
- Connection pooling and keepalive

5. Observability

- Real-time monitoring via Control Panel
- Structured logging throughout application
- Diameter peer status tracking
- Subscriber state tracking with timestamps

[← Back to Operations Guide](#) | [Next: Configuration](#) →

OmniHSS Configuration Guide


[← Back to Operations Guide](#)

Table of Contents

- [Configuration File Overview](#)
 - [License Client Configuration](#)
 - [Runtime Configuration](#)
 - [Database Configuration](#)
 - [Diameter Configuration](#)
 - [Network Configuration](#)
 - [Home PLMN Configuration](#)
 - [HSS Core Configuration](#)
 - [IMS Configuration](#)
 - [EIR Configuration](#)
 - [API and Control Panel Configuration](#)
 - [Configuration Workflow](#)
-

Configuration File Overview

OmniHSS uses two primary configuration files:



config/config.exs (Compile Time)

Contains static configuration that does not change between environments:

- Control Panel page configuration
- API endpoint configuration
- Telemetry settings

config/runtime.exs (Runtime)

Contains environment-specific configuration that changes per deployment:

- Database connection parameters
- Diameter peer configuration
- Home PLMN settings
- IMS S-CSCF selection
- Network interface bindings

License Client Configuration

The License Client validates the HSS license with a remote license server:

```
# config/runtime.exs

config :license_client,
  # License server API endpoints (list for failover)
  license_server_api_urls:
  ["https://license.example.com:8443/api"],

  # Licensed organization name
  licensee: "Your Organization Name",

  # Product identifier
  product_name: "omnihss"
```

License Configuration Parameters:


Parameter	Description	Required	Example
license_server_api_urls	List of license server URLs	Yes	["https://10.0.0.1:8443/api"]
licensee	Organization name on license	Yes	"ACME Telecom"
product_name	Product identifier for license	Yes	"omnihss"

Important Notes:

- License server must be reachable from HSS
 - Use HTTPS for secure license validation
 - Multiple URLs provide failover capability
 - License validation occurs at startup and periodically
-

Runtime Configuration

Configuration Priority



Environment Variable Pattern

OmniHSS follows this pattern for configuration:

- Environment variable names are UPPERCASE with underscores
 - Default values are provided in runtime.exs
 - Database credentials should use environment variables in production
-

Database Configuration

Basic Database Configuration

```
# config/runtime.exs

config :hss, Hss.Repo,
  # Database connection parameters
  username: System.get_env("DATABASE_USERNAME", "root"),
  password: System.get_env("DATABASE_PASSWORD", "password"),
  hostname: System.get_env("DATABASE_HOSTNAME", "localhost"),
  database: System.get_env("DATABASE_NAME", "omnihss"),

  # Connection pool settings
  pool_size:
String.to_integer(System.get_env("DATABASE_POOL_SIZE", "20")),


  # Timeouts (in milliseconds)
  timeout: 15_000,
  connect_timeout: 15_000,

  # Additional options
  show_sensitive_data_on_connection_error: false
```


Database Configuration Parameters

Parameter	Description	Default	Recommendation
<code>username</code>	SQL Database username	<code>"root"</code>	Use dedicated user in production
<code>password</code>	SQL Database password	<code>"password"</code>	Use strong password, store in env var
<code>hostname</code>	SQL Database server hostname	<code>"localhost"</code>	Use FQDN or IP in production
<code>database</code>	Database name	<code>"omnihss"</code>	Keep default unless multiple instances
<code>pool_size</code>	Connection pool size	<code>20</code>	Adjust based on load (10-50 typical)

Pool Size Tuning



Guidelines:

- Start with 20 connections
- Monitor for "connection pool timeout" errors
- Increase by 10 if timeouts occur under normal load
- Each connection uses ~4MB of memory
- Too many connections can degrade SQL Database performance

Example: Production Database Configuration

```
# config/runtime.exs - Production example

config :hss, Hss.Repo,
  username: System.fetch_env!("DATABASE_USERNAME"),      #
  Required in production
  password: System.fetch_env!("DATABASE_PASSWORD"),      #
  Required in production
  hostname: System.get_env("DATABASE_HOSTNAME",
    "db.internal.example.com"),
  database: System.get_env("DATABASE_NAME", "omnihss"),
  port: String.to_integer(System.get_env("DATABASE_PORT",
    "5432")),
  pool_size:
    String.to_integer(System.get_env("DATABASE_POOL_SIZE", "30")),
  ssl: true,
  ssl_opts: [
    cacertfile: "/etc/ssl/certs/postgres-ca.pem",
    verify: :verify_peer
  ]
```

Diameter Configuration

Diameter Service Configuration

```
# config/runtime.exs

diameter_config = %{
  service_name: :omnitouch_hss,

  # Network binding
  listen_ip: System.get_env("DIAMETER_LISTEN_IP", "10.7.25.186"),
  listen_port:
    String.to_integer(System.get_env("DIAMETER_LISTEN_PORT", "3868")),

  # Diameter identity
  host: System.get_env("DIAMETER_HOST", "omnihss"),
  realm: System.get_env("DIAMETER_REALM",
    "epc.mnc001.mcc001.3gppnetwork.org"),


  # Product identification
  product_name: "OmniHSS",
  vendor_id: 10415, # 3GPP
  supported_vendor_ids: [5535, 10415],

  # Protocol settings
  request_timeout: 5000,

  # Peer configuration
  peers: [
    # Add peer configurations here
  ]
}

config :hss, :diameter, diameter_config
```

Diameter Identity Configuration



Guidelines:

- **Host:** Short hostname of the HSS (e.g., "omnihss", "hss01")
- **Realm:** Diameter realm matching your PLMN (e.g., "epc.mnc001.mcc001.3gppnetwork.org")
- **Full Identity:** Constructed as `{host}.{realm}`

Adding Diameter Peers

Static Peer Configuration (Connect Mode)

```
# config/runtime.exs

peers: [
  # MME Peer Example
  %{
    host: "mme01.epc.mnc001.mcc001.3gppnetwork.org",
    realm: "epc.mnc001.mcc001.3gppnetwork.org",
    ip: "10.7.25.100",
    port: 3868,
    transport: :sctp, # or :tcp
    applications: [:s6a]
  },

  # P-GW Peer Example
  %{
    host: "pgw01.epc.mnc001.mcc001.3gppnetwork.org",
    realm: "epc.mnc001.mcc001.3gppnetwork.org",
    ip: "10.7.25.101",
    port: 3868,
    transport: :sctp,
    applications: [:gx]
  },

  # I-CSCF Peer Example
  %{
    host: "icscf01.ims.mnc001.mcc001.3gppnetwork.org",
    realm: "ims.mnc001.mcc001.3gppnetwork.org",
    ip: "10.7.25.102",
    port: 3868,
    transport: :tcp,
    applications: [:cx]
  }
]
```


Listen-Only Mode

For environments where peers initiate connections to the HSS:

```
# config/runtime.exs

diameter_config = %{
  # ... other config ...
  peers: [] # Empty - accept incoming connections only
}
```

Diameter Peer Connection Modes



Transport Protocol Selection

Transport	Advantages	Disadvantages	Recommendation
SCTP	Multi-streaming, better failure detection	Requires kernel support, firewall config	Preferred for Diameter
TCP	Universal support, simpler firewall rules	Single stream, slower failure detection	Use if SCTP unavailable

Network Configuration

Home PLMN Configuration

The home PLMN identifies your network operator:

```
# config/runtime.exs

config :hss, :home_plmn, %{
  mcc: System.get_env("HOME_PLMN_MCC", "001"), # Mobile Country
Code
  mnc: System.get_env("HOME_PLMN_MNC", "001") # Mobile Network
Code
}
```

HSS Core Configuration

These settings control HSS behavior and features:

```
# config/runtime.exs

config :hss,
  # Ecto repositories for database operations
  ecto_repos: [Hss.Repo],

  # CLR (Cancel Location Request) on MME change
  send_clr_on_mme_change: true,


  # Stop Diameter service during database outages
  stop_diameter_on_database_failure: true,

  # License enforcement configuration
  license_enforced: true,
  license_module: LicenseClient
```

HSS Core Parameters:

Parameter	Description	Default	Re
<code>ecto_repos</code>	List of Ecto repositories used by the application	<code>[Hss.Repo]</code>	Re da op
<code>send_clr_on_mme_change</code>	Send Cancel Location Request when subscriber changes MME	<code>true</code>	Ke pro
<code>stop_diameter_on_database_failure</code>	Disable Diameter service if database becomes unavailable	<code>true</code>	En col
<code>license_enforced</code>	Enable license enforcement	<code>true</code>	Re pro
<code>license_module</code>	Module handling license checks	<code>LicenseClient</code>	Do

PLMN Code Format



Examples:

- AT&T (USA): MCC=310, MNC=410
- Verizon (USA): MCC=311, MNC=480
- Vodafone (UK): MCC=234, MNC=15
- Test Network: MCC=001, MNC=01

Network Interface Binding


```
# config/runtime.exs

# Diameter interface
listen_ip: System.get_env("DIAMETER_LISTEN_IP", "0.0.0.0"), # All
interfaces
# Or specific interface:
# listen_ip: "10.7.25.186",

# API interface
config :hss, HssWeb.Api.Endpoint,
  http: [
    ip: {0, 0, 0, 0}, # All interfaces
    port: 8443
  ]

# Control Panel interface
config :hss, HssWeb.ControlPanel.Endpoint,
  http: [
    ip: {0, 0, 0, 0}, # All interfaces
    port: 7443
  ]
```

Interface Binding Options:



IMS Configuration




S-CSCF Selection Configuration

```
# config/runtime.exs

config :hss, :ims, %{
  scscf: %{
    # Selection method: :random_peer or :round_robin
    selection_method: :random_peer,

    # List of available S-CSCF peers
    peers: [
      %{
        host:
        "sip:scscf01.ims.mnc001.mcc001.3gppnetwork.org:5060",
        capabilities: [] # Optional: capability matching
      },
      %{
        host:
        "sip:scscf02.ims.mnc001.mcc001.3gppnetwork.org:5060",
        capabilities: []
      }
    ]
  }
}
```

S-CSCF Selection Methods



Selection Methods:

Method	Description	Use Case
<code>:random_peer</code>	Randomly selects an S-CSCF	Even load distribution
<code>:round_robin</code>	Sequentially assigns S-CSCFs	Predictable distribution

IMS Realm Configuration

Typically, IMS uses a separate realm from EPC:

```
# EPC Realm
"epc.mnc001.mcc001.3gppnetwork.org"

# IMS Realm
"ims.mnc001.mcc001.3gppnetwork.org"
```

EIR Configuration


See [EIR Documentation](#) for complete equipment identity checking details.

Equipment Identity Register Settings

```
# config/runtime.exs

config :hss, :eir, %{
  # Behavior for unknown equipment (no matching rule)
  unknown_equipment_behaviour: :whitelist
  # Options:
  #   :whitelist - Allow unknown equipment
  #   :blacklist - Block unknown equipment
  #   :greylist - Track but allow unknown equipment
  #   :reject_unknown_equipment - Reject with specific result code
}
```

Unknown Equipment Behavior



Behavior Options:

Option	Result	Use Case
<code>:whitelist</code>	Allow all unknown IMEI	Open network, testing
<code>:blacklist</code>	Block all unknown IMEI	Moderate security
<code>:greylist</code>	Allow but track unknown IMEI	Monitoring mode
<code>:reject_unknown_equipment</code>	Reject with specific code	High security

Recommendation: Start with `:whitelist` during testing, move to `:greylist` for production monitoring, then `:blacklist` for strict security.

API and Control Panel Configuration

API Endpoint Configuration

```
# config/config.exs

config :hss, HssWeb.Api.Endpoint,
  url: [host: "localhost"],
  render_errors: [view: HssWeb.ErrorView, accepts: ~w(json)],
  pubsub_server: Hss.PubSub,

# HTTPS configuration
https: [
  port: 8443,
  cipher_suite: :strong,
  certfile: "priv/cert/omnitouch.crt",
  keyfile: "priv/cert/omnitouch.pem"
]
```


Control Panel Configuration

```
# config/config.exs

config :hss, HssWeb.ControlPanel.Endpoint,
  url: [host: "localhost"],
  render_errors: [view: HssWeb.ErrorView, accepts: ~w(html json)],
  pubsub_server: Hss.PubSub,
  live_view: [signing_salt: "some-secret"],

# HTTPS configuration
https: [
  port: 7443,
  cipher_suite: :strong,
  certfile: "priv/cert/omnitouch.crt",
  keyfile: "priv/cert/omnitouch.pem"
]
```


TLS Certificate Configuration



Certificate Requirements:


- Valid X.509 certificate
- Matching private key
- Include intermediate certificates if needed
- CN or SAN must match hostname

For Production:

```
https: [  
  port: 8443,  
  cipher_suite: :strong,  
  certfile: System.get_env("TLS_CERT_FILE",  
    "/etc/ssl/certs/omnihss.crt"),  
  keyfile: System.get_env("TLS_KEY_FILE",  
    "/etc/ssl/private/omnihss.key"),  
  cacertfile: System.get_env("TLS_CA_FILE", "/etc/ssl/certs/ca-  
    bundle.crt")  
]
```

Configuration Workflow

Initial Deployment Configuration



Configuration Checklist

Essential Configuration

- ☐ Database connection (hostname, credentials)
- ☐ Home PLMN (MCC, MNC)
- ☐ Diameter host and realm
- ☐ Diameter listen IP and port
- ☐ TLS certificates for API and Control Panel
- ☐ License client configuration (server URLs, licensee, product_name)
- ☐ HSS core settings (send_clr_on_mme_change, stop_diameter_on_database_failure)

Network Element Integration

- ☐ Diameter peers configured (if using connect mode)

- ☐ Firewall rules allow Diameter traffic (port 3868)
- ☐ Firewall rules allow HTTPS traffic (ports 7443, 8443)
- ☐ DNS resolution for Diameter identities

IMS Configuration (if using IMS features)

- ☐ S-CSCF peer list configured
- ☐ S-CSCF selection method chosen
- ☐ IMS realm configured

Optional Configuration

- ☐ EIR behavior configured
- ☐ Database pool size tuned
- ☐ Network interface binding restricted

Verifying Configuration

After modifying configuration:

1. Syntax Check:

```
Check logs for configuration loading errors
```

2. Control Panel Access:

```
Access https://[hostname]:7443  
Verify Overview page loads
```

3. API Access:

```
curl -k https://[hostname]:8443/api/status
```

4. Diameter Status:

Check Control Panel Diameter page
Verify peer connections

5. **Database Connectivity:**

Check Control Panel for subscriber data
Or connect directly to SQL Database

Complete Runtime Configuration

Example

```
# config/runtime.exs - Complete production example

import Config

#
=====
# DATABASE CONFIGURATION
#
=====
config :hss, Hss.Repo,
  username: System.fetch_env!("DATABASE_USERNAME"),
  password: System.fetch_env!("DATABASE_PASSWORD"),
  hostname: System.get_env("DATABASE_HOSTNAME", "db.omnihss.internal"),
  database: System.get_env("DATABASE_NAME", "omnihss"),
  port: String.to_integer(System.get_env("DATABASE_PORT", "5432")),
  pool_size: String.to_integer(System.get_env("DATABASE_POOL_SIZE", "10")),
  timeout: 15_000,
  connect_timeout: 15_000,
  ssl: true,
  ssl_opts: [
    cacertfile: "/etc/ssl/certs/postgres-ca.pem",
    verify: :verify_peer
  ]

#
=====
# LICENSE CLIENT CONFIGURATION
#
=====
config :license_client,
  license_server_api_urls: [System.get_env("LICENSE_SERVER_URL",
"https://license.example.com:8443/api")],
  licensee: System.get_env("LICENSE_ORGANIZATION", "Your Organization"),
  product_name: "omnihss"

#
=====
# HOME PLMN AND HSS CORE CONFIGURATION
#
=====
```

```

config :hss,
  ecto_repos: [Hss.Repo],
  home_plmn: %{
    mcc: System.get_env("HOME_PLMN_MCC", "001"),
    mnc: System.get_env("HOME_PLMN_MNC", "001")
  },
  send_clr_on_mme_change: true,
  stop_diameter_on_database_failure: true,
  license_enforced: true,
  license_module: LicenseClient

#
=====
# DIAMETER CONFIGURATION
#
=====
diameter_config = %{
  service_name: :omnitouch_hss,
  listen_ip: System.get_env("DIAMETER_LISTEN_IP", "10.7.25.186"),
  listen_port: String.to_integer(System.get_env("DIAMETER_LISTEN_PORT",
"3868")),
  host: System.get_env("DIAMETER_HOST", "omnihss01"),
  realm: System.get_env("DIAMETER_REALM",
"epc.mnc001.mcc001.3gppnetwork.org"),
  product_name: "OmniHSS",
  vendor_id: 10415,
  supported_vendor_ids: [5535, 10415],
  request_timeout: 5000,
  peers: [
    %{
      host: "mme01.epc.mnc001.mcc001.3gppnetwork.org",
      realm: "epc.mnc001.mcc001.3gppnetwork.org",
      ip: "10.7.25.100",
      port: 3868,
      transport: :sctp,
      applications: [:s6a]
    }
  ]
}

config :hss, :diameter, diameter_config

#
=====

```

```
# IMS CONFIGURATION
```

```
#
```

```
=====
config :hss, :ims, %{
  scscf: %{
    selection_method: :random_peer,
    peers: [
      %{host: "sip:scscf01.ims.mnc001.mcc001.3gppnetwork.org:5060"},
      %{host: "sip:scscf02.ims.mnc001.mcc001.3gppnetwork.org:5060"}
    ]
  }
}
```

```
#
```

```
=====
# EIR CONFIGURATION
#
=====
config :hss, :eir, %{
  unknown_equipment_behaviour: :whitelist
}
```

```
#
```

```
=====
# API ENDPOINT CONFIGURATION
#
=====
config :hss, HssWeb.Api.Endpoint,
  http: [ip: {0, 0, 0, 0}, port: 8443],
  https: [
    port: 8443,
    cipher_suite: :strong,
    certfile: System.get_env("TLS_CERT_FILE", "/etc/ssl/certs/omnihss"),
    keyfile: System.get_env("TLS_KEY_FILE", "/etc/ssl/private/omnihss"),
  ],
  url: [host: System.get_env("API_HOST", "api.omnihss.internal"), port: 8443]
```

```
#
```

```
=====
# CONTROL PANEL ENDPOINT CONFIGURATION
#
=====
config :hss, HssWeb.ControlPanel.Endpoint,
```



```
http: [ip: {0, 0, 0, 0}, port: 7443],
https: [
  port: 7443,
  cipher_suite: :strong,
  certfile: System.get_env("TLS_CERT_FILE", "/etc/ssl/certs/omnihss"),
  keyfile: System.get_env("TLS_KEY_FILE", "/etc/ssl/private/omnihss"),
],
url: [host: System.get_env("CP_HOST", "hss.omnihss.internal"), port
```

[← Back to Operations Guide](#) | [Next: Entity Relationships](#) →

OmniHSS Control Panel Guide

[← Back to Operations Guide](#)

Table of Contents

- [Control Panel Overview](#)
 - [Accessing the Control Panel](#)
 - [Overview Page](#)
 - [Diameter Page](#)
 - [Application Page](#)
 - [Configuration Page](#)
 - [Navigation and Interface](#)
-

Control Panel Overview

The OmniHSS Control Panel is a web-based monitoring interface that provides real-time visibility into system status, subscriber activity, and Diameter connectivity. Built with Phoenix LiveView, it automatically updates without requiring page refreshes.


Key Features

- **Real-time Updates** - Auto-refreshes every second
- **Subscriber Monitoring** - View active subscribers and their current state
- **Diameter Status** - Monitor peer connections in real-time
- **System Resources** - Track application performance
- **Configuration Viewer** - Inspect runtime configuration

Access Information

URL: `https://[hostname]:7443`
Protocol: HTTPS Only
Port: 7443 (configurable)
Certificate: Configured in `config/config.exs`

Control Panel Architecture



Accessing the Control Panel

Initial Access

1. Open a web browser
2. Navigate to `https://[hostname]:7443`
3. Accept the TLS certificate (if self-signed)
4. You will be presented with the Overview page by default

TLS Certificate Warnings

If using self-signed certificates, browsers will show security warnings. This is expected for internal deployments.

For Production: Use certificates signed by a trusted Certificate Authority.

Network Requirements

- **Port 7443** must be accessible from your management network
- **HTTPS** is mandatory - HTTP is not supported
- **Firewall rules** must allow traffic to port 7443

Browser Compatibility

The Control Panel uses modern web technologies (LiveView, WebSockets):

- Chrome/Chromium (recommended)
- Firefox
- Safari
- Edge

Note: Internet Explorer is not supported.

Overview Page

URL: `https://[hostname]:7443/overview`

The Overview page displays all subscribers and their real-time state information.

Page Layout





Table Columns

Column	Description	Values
ID	Subscriber database ID	String (UUID)
Enabled	Service status	✓ (enabled) / ✗ (disabled)
IMSI	International Mobile Subscriber Identity	14-15 digits
ICCID	SIM card ID	19-20 digits or "N/A"
EPC Profile	Data service profile name	Profile name or ID
IMS Profile	Voice service profile name	Profile name, ID, or "N/A"
Roaming Profile	Roaming policy name	Profile name, ID, or "N/A"

Expandable Row Details

Click on any row to expand and view detailed subscriber state:

Location Information



Fields:

- **MCC** - Mobile Country Code (3 digits)
- **MNC** - Mobile Network Code (2-3 digits)
- **TAC** - Tracking Area Code
- **Cell ID** - Serving cell identifier
- **eNodeB ID** - Base station identifier
- **ECI** - E-UTRAN Cell Identifier

Network Information

Fields:

- **Last Seen MME** - Current serving MME hostname
- **Last Seen Realm** - Diameter realm of MME
- **RAT Type** - Radio Access Technology (e.g., "E-UTRAN" for LTE)
- **Last Seen At** - Timestamp of last Diameter message

IMS Information

Fields:


- **Assigned S-CSCF** - Currently assigned S-CSCF SIP URI
- **IMS Public Identity** - SIP URI (e.g., sip:+14155551234@ims.example.com)
- **Last Seen P-CSCF** - Last P-CSCF that contacted HSS
- **Last Seen I-CSCF** - Last I-CSCF that contacted HSS

Session Information

Fields:

- **PDN Sessions** - Number of active data connections
- **Active Calls** - Number of active VoLTE calls

State Indicators



How to identify state:

- **Idle:** No location information, no MME
- **Attached:** Last Seen MME present, location info available
- **PDN Active:** PDN sessions count > 0
- **IMS Registered:** Assigned S-CSCF present
- **In Call:** Active calls count > 0

Auto-Refresh

The Overview page automatically refreshes **every 1 second** to show real-time updates.

Visual indicators:

- New data appears without page reload
- Timestamps update in real-time
- No manual refresh needed

Use Cases

1. Monitor Active Subscribers

- See which subscribers are currently attached

- Check current serving network (for roaming)
- Verify IMS registration status

2. Troubleshooting

- Verify subscriber is enabled
- Check last seen timestamp (is subscriber responsive?)
- Confirm profile assignments
- View current location information

3. Capacity Monitoring

- Count total attached subscribers
- Monitor PDN session counts
- Track active VoLTE calls

Diameter Page

URL: `https://[hostname]:7443/diameter`

The Diameter page shows real-time status of all Diameter peer connections.

Page Layout





Table Columns

Column	Description	Values
Hostname	Diameter peer hostname	FQDN
Realm	Diameter realm	Domain name
IP:Port	Network address	IP address and port
Transport	Transport protocol	TCP or SCTP
Status	Connection status	Connected / Disconnected

Connection Status



Expandable Row Details

Click on any peer to view additional information:

Connection Information:


- **Connection Type** - Initiated by HSS or peer
- **Product Name** - Peer's product identification
- **Application IDs** - Supported Diameter applications

Application ID Examples:

- 16777251 - S6a (MME)

- 16777238 - Gx (P-GW)
- 16777216 - Cx (I-CSCF, S-CSCF)
- 16777217 - Sh (Application Server)
- 16777236 - Rx (P-CSCF)
- 16777252 - S13 (EIR client, if external)

Peer Connection Flow



Auto-Refresh

The Diameter page automatically refreshes **every 1 second**.

Use Cases

1. Verify Connectivity

- Ensure all expected peers are connected
- Identify disconnected peers immediately
- Monitor for flapping connections

2. Troubleshooting

- Check if peer is reachable
- Verify transport protocol (TCP vs SCTP)
- Confirm application IDs match expectations
- Identify which side initiated connection

3. Capacity Planning

- Count total connected peers
- Monitor for connection stability
- Plan for additional peer capacity

Common Issues

Peer Shows Disconnected

Possible Causes:

1. Network connectivity issue
2. Peer is down or restarting
3. Firewall blocking traffic
4. Diameter configuration mismatch
5. Certificate issue (if using TLS)

Troubleshooting Steps:

1. Check network connectivity: `ping [peer-ip]`
2. Verify port is reachable: `telnet [peer-ip] 3868`
3. Check firewall rules
4. Review HSS logs for error messages
5. Verify peer's Diameter configuration matches HSS

Peer Connects and Disconnects Repeatedly

Possible Causes:

1. Network instability
2. Keepalive timeout mismatch
3. Peer resource issues
4. Diameter application mismatch

Troubleshooting Steps:

1. Check network stability
 2. Review keepalive timers on both sides
 3. Check peer system resources
 4. Verify application IDs match on both sides
-

Application Page


URL: `https://[hostname]:7443/application`

The Application page provides system-level monitoring and resource usage information.

Features

- **Process Information** - Erlang VM process count and memory
- **System Memory** - Total and used memory
- **Application Uptime** - How long OmniHSS has been running
- **Erlang VM Version** - Runtime version information

Key Metrics



Use Cases

1. Health Monitoring

- Verify application is running
- Check for memory leaks (increasing memory over time)
- Monitor process count growth

2. Capacity Planning

- Track memory usage trends
- Plan for scale-out based on process count
- Verify adequate system resources

3. Troubleshooting

- Identify resource exhaustion
- Check if restart is needed
- Verify Erlang VM version

Configuration Page


URL: `https://[hostname]:7443/configuration`

The Configuration page displays the current runtime configuration of OmniHSS.

Features

- **View Configuration** - Inspect all configuration parameters
- **Search Configuration** - Find specific settings
- **Environment Variables** - See resolved values

Configuration Categories



Use Cases

1. Configuration Verification

- Verify runtime.exs settings are applied
- Confirm database connection parameters
- Check Diameter peer configuration

2. Troubleshooting

- Identify misconfiguration
- Verify environment variables are set correctly
- Compare expected vs actual configuration


3. Documentation

- Export current configuration for documentation
- Share configuration with support team

Security Note: Configuration page may display sensitive information (database passwords, keys). Restrict access appropriately.

Navigation and Interface

Top Navigation Bar



Navigation is always visible at the top of the page for quick access.

Keyboard Shortcuts

The Control Panel does not implement custom keyboard shortcuts. Standard browser shortcuts work:

- **Ctrl+R / F5** - Manual page refresh (though auto-refresh makes this unnecessary)
- **Ctrl+F** - Search on page
- **Ctrl+T** - Open new tab (for multiple pages)

Multi-Tab Monitoring

You can open multiple Control Panel pages in separate browser tabs for simultaneous monitoring:

Example Setup:

- Tab 1: Overview page (monitor subscribers)
- Tab 2: Diameter page (monitor connectivity)
- Tab 3: Application page (monitor resources)

All tabs will auto-update independently.

Responsive Design

The Control Panel is optimized for desktop browsers. Mobile browsers are supported but may require horizontal scrolling for tables.

Recommended Resolution: 1920x1080 or higher for comfortable viewing.

Monitoring Best Practices

Daily Operations

1. Start of Shift

- Open Control Panel Overview page
- Verify expected number of subscribers are attached
- Check Diameter page - all peers connected


2. During Shift

- Keep Overview page open for real-time monitoring
- Watch for unusual state changes
- Monitor for disconnected peers on Diameter page

3. End of Shift

- Verify system is stable
- Check Application page for resource usage trends
- Document any anomalies

Troubleshooting Workflow



Alert Thresholds

Establish monitoring thresholds for proactive alerting:

Metric	Warning	Critical
Disconnected Diameter Peers	1 peer	2+ peers or critical peer
Memory Usage	> 80%	> 90%
Subscriber Authentication Failures	> 5%	> 10%
Process Count	> 80% of limit	> 95% of limit

[← Back to Operations Guide](#) | [Next: Metrics & Monitoring →](#)

Database Replication

[← Back to Operations Guide](#)

Table of Contents

- [Overview](#)
 - [How It Works](#)
 - [Deployment Architectures](#)
 - [Configuration Reference](#)
 - [Peer Management](#)
 - [Monitoring](#)
 - [Troubleshooting](#)
-

Overview

OmniHSS uses **PostgreSQL** with **bidirectional logical replication** for multi-site high-availability deployments. Each site operates as an independent read/write primary. There is no single master or read-only replicas.

Key Characteristics

- **Both Sites Read/Write:** Every site has a full primary database. Local writes are instant regardless of inter-site link quality
- **Asynchronous Replication:** Changes replicate via PostgreSQL's Write-Ahead Log (WAL). No write is blocked waiting for a remote site to acknowledge
- **Partition Tolerant:** If the inter-site link goes down, both sites continue operating independently. WAL segments queue locally and replay automatically when the link recovers


- **No Quorum Required:** Unlike synchronous cluster approaches, there is no concept of quorum. A single-site deployment operates identically to a multi-site deployment
- **UUID Primary Keys:** All records use UUIDv4 primary keys, eliminating ID collisions between sites without coordination

How This Differs from Synchronous Replication

	Synchronous	Asynchronous Logical Replication
Write latency	Blocked by slowest node	Local only: sub-millisecond
Link failure	Minority site goes read-only	Both sites continue read/write
Quorum needed	Yes (majority of nodes)	No
Data consistency	Strong (all nodes identical)	Eventual (brief replication lag)
Suitable for satellite links	No (latency kills write performance)	Yes (WAL queues and catches up)

How It Works

Logical Replication Flow



Publication / Subscription Model

Each site has:

- A **publication** that broadcasts all table changes (except `schema_migrations`)
- A **subscription** to every peer site's publication



WAL Queuing During Link Outage

When the inter-site link is unavailable:

1. Local writes continue without interruption
2. WAL segments accumulate on the publishing side
3. The replication slot tracks where each subscriber left off
4. When the link recovers, queued WAL replays from the last acknowledged position
5. Both sites converge to identical state

WAL retention is bounded by `max_slot_wal_keep_size` to prevent unbounded disk growth during extended outages.

Conflict Prevention

UUID primary keys eliminate the primary source of conflicts in bidirectional replication. Since each site generates globally unique identifiers independently, INSERT operations never collide.

The `origin = none` subscription option prevents replication loops. Changes that arrived via replication are not re-published to other subscribers.

The `schema_migrations` table is excluded from publications because both sites run identical migrations independently.

Last-Write-Wins for Dynamic State

Dynamic state tables (`subscriber_state`, `pdn_session`, `lte_call`) are updated frequently by Diameter signalling. Every ULR updates the serving MME, every CCR updates the PGW session, and every AAR updates the active call.

In a multi-site deployment, a subscriber is served by one site at a time. When the subscriber moves between sites, both sites may have updates to the same `subscriber_state` row from different times. Without conflict resolution, the replication order would determine which value survives. This could overwrite the current serving MME with a stale value.

OmniHSS uses **Last-Write-Wins (LWW) triggers** on dynamic state tables:

```
CREATE TRIGGER lww_subscriber_state_trigger
  BEFORE UPDATE ON subscriber_state
  FOR EACH ROW
  EXECUTE FUNCTION lww_subscriber_state();
```

The trigger compares the `updated_at` timestamp of the incoming replicated update against the existing row. If the existing row is newer, the update is silently suppressed. This ensures:

- When a subscriber moves from Site A to Site B, Site B's newer update always wins
- Stale updates from Site A (from before the subscriber moved) are discarded
- Both sites converge to the same value: the most recent write


Tables with LWW triggers:

Table	Updated By	Frequency
subscriber_state	ULR, SAR, AIR, PUR	Every attach/location update
pdn_session	CCR-I, CCR-T	Every PDN session create/delete
lte_call	AAR, STR	Every VoLTE call setup/teardown

Static provisioning data (subscribers, profiles, keys, APNs) does not need LWW. The provisioning API only updates these records, typically from a single management plane.

Deployment Architectures


Single Site (No Replication)



Multiple HSS application instances share a single PostgreSQL database. Standard PostgreSQL streaming replication can be used for local database


failover if required.

Two-Site Deployment



Both sites are full primaries. Subscriber provisioning on either site replicates to the other. Each MME connects to its local HSS. There is no cross-site Diameter dependency.

Multi-Site Deployment



Each site subscribes to every other site's publication. Peers are auto-discovered from Ansible inventory. To add a site, add it to the `hss` inventory group and run the playbook.

Network Requirements

Port	Protocol	Purpose
5432	TCP	PostgreSQL client and replication connections

Configuration Reference

Ansible Variables

Replication is configured per HSS group in your inventory:

```
hss:
  hosts:
    site-a-hss01:
      ansible_host: 10.80.12.140
    site-a-hss02:
      ansible_host: 10.80.12.141
  vars:
    omnihss:
      database_type: postgres
      database_host: localhost
      database_port: 5432
      database_name: omnihss
      database_username: omnihss
      database_password: "secure_password"
      replication:
        enabled: true
```

Ansible Parameters

Parameter	Type	Required	Default	Description
<code>database_type</code>	String	No	<code>postgres</code>	Database backend. Must be <code>postgres</code> for replication.
<code>database_host</code>	String	No	<code>localhost</code>	PostgreSQL host. Use <code>localhost</code> when Postgres runs on the same host as OmniHSS.
<code>database_port</code>	Integer	No	<code>5432</code>	PostgreSQL port.
<code>database_name</code>	String	No	<code>omnihss</code>	Database name.
<code>database_username</code>	String	Yes	-	PostgreSQL user. Must have <code>CREATEDB</code> and <code>REPLICATION</code> privileges.
<code>database_password</code>	String	Yes	-	PostgreSQL password.

Parameter	Type	Required	Default	Description
<code>replication.enabled</code>	Boolean	No	<code>false</code>	Enable bidirectional logical replication. When <code>true</code> , the Ansible role configures publications, subscriptions, and <code>pg_hba.conf</code> entries automatically.

Peer Discovery

Peers are discovered automatically from two sources:

1. **Local inventory group:** All other hosts in the `hss` Ansible group
2. **Remote sites:** Entries in `connected_sites.hss` from `prod_master_peers.yml`

No per-host peer configuration is required. Adding a host to the `hss` group or to `connected_sites.hss` and running the playbook is sufficient.

Remote Site Peers (prod_master_peers.yml)

For inter-site replication across geographic locations:

```
# group_vars/prod_master_peers.yml
connected_sites:
  hss:
    - remote-site-hss01: 10.80.20.140
    - remote-site-hss02: 10.80.20.141
```

PostgreSQL Configuration

The Ansible role configures the following PostgreSQL parameters automatically when replication is enabled:

Parameter	Value	Purpose
<code>wal_level</code>	<code>logical</code>	Required for logical replication. Includes full row data in WAL.
<code>max_wal_senders</code>	<code>10</code>	Maximum concurrent WAL sender processes (one per subscriber).
<code>max_replication_slots</code>	<code>10</code>	Maximum replication slots. Each peer uses one slot.
<code>listen_addresses</code>	<code>*</code>	Accept connections from peer sites.

The role also adds `pg_hba.conf` entries to allow replication connections from each discovered peer IP.

Peer Management

Adding a New Site

1. Add the new host(s) to the `hss` inventory group, or add to `connected_sites.hss` in `prod_master_peers.yml`
2. Run the OmniHSS playbook

The role will:

- Install PostgreSQL and OmniHSS on the new host
- Run database migrations
- Create a publication for the new site
- Create subscriptions to all existing peers
- Update `pg_hba.conf` on all existing peers to allow the new site
- Create subscriptions from existing peers to the new site

Removing a Site

```
ansible-playbook -i hosts site.yml --tags hss-remove-peer \
  -e "peer_name=site_b confirm_remove=yes"
```

The `confirm_remove=yes` parameter is required as a safety measure. Without it, the playbook refuses to proceed and displays what would happen.

Removing a peer:

- Drops the subscription (stops incoming replication from that peer)
- Removes the peer's IP from `pg_hba.conf`
- Data already replicated from the peer remains in the local database
- The peer site's subscription to this site must be removed separately on the peer

Adding a Peer Ad-Hoc

For cases where you need to add a peer outside the standard playbook flow:

```
ansible-playbook -i hosts site.yml --tags hss-add-peer \
  -e "peer_name=site_b peer_host=10.80.20.140"
```

Monitoring

Prometheus Metrics

The **postgres_exporter** service runs on each HSS host on port 9187, exposing PostgreSQL metrics to Prometheus.

Replication Metrics

Metric	Type	Description
pg_replication_slots_active	Gauge	1 if the replication slot is active (peer connected), 0 if inactive
pg_replication_slots_pg_wal_lsn_diff	Gauge	Replication lag in bytes. Distance between current WAL position and the peer's last confirmed position
pg_stat_replication_pg_current_wal_lsn_bytes	Gauge	Current WAL position on this node

Example Prometheus Queries

```
# Replication slot active (1 = connected, 0 = disconnected)
pg_replication_slots_active{slot_name=~"sub_from_.*"}

# Replication lag in megabytes
pg_replication_slots_pg_wal_lsn_diff / 1048576

# Alert: replication slot inactive for more than 60 seconds
pg_replication_slots_active == 0
```

Recommended Alerts

Alert	Condition	Severity	Description
Replication Slot Inactive	<code>pg_replication_slots_active == 0</code> for 60s	Critical	Peer is disconnected. WAL is accumulating.
WAL Lag Excessive	<code>pg_replication_slots_pg_wal_lsn_diff > 104857600</code> for 5m	Warning	Replication lag exceeds 100MB. May be due to slow replication or link degradation.
WAL Slot Lost	WAL status is <code>lost</code>	Critical	Slot has become invalid. Peer requires a full recovery.

Ansible Validation

The OmniHSS playbook validates replication health at the end of every run. It asserts:

1. All subscription workers are alive
2. All replication slots are active

3. WAL lag is within threshold (100MB default)

4. WAL slot status is `reserved` or `extended` (not `lost`)

If any assertion fails, the playbook fails with a clear error message identifying the issue.

Manual Validation

```
# Check subscription workers are alive
sudo -u postgres psql -d omnihss -c \
    "SELECT subname, pid IS NOT NULL as worker_alive FROM
pg_stat_subscription;"

# Check replication slots and lag
sudo -u postgres psql -d omnihss -c \
    "SELECT slot_name, active,
        pg_wal_lsn_diff(pg_current_wal_lsn(), confirmed_flush_lsn) as
lag_bytes,
        wal_status
    FROM pg_replication_slots WHERE slot_type = 'logical';"

# Compare subscriber counts between sites
sudo -u postgres psql -d omnihss -c "SELECT count(*) FROM
subscriber;"
```

Troubleshooting

Subscription Worker Dead

Symptoms: `pg_stat_subscription` shows `pid IS NULL` for a subscription. Ansible validation fails with "Dead workers."

Common Causes:

- Table exists on publisher but not subscriber (DDL mismatch)
- Duplicate key conflict from a manually inserted record
- Peer unreachable for extended period causing WAL slot invalidation

Resolution:

1. Check PostgreSQL logs for the specific error:

```
journalctl -u postgresql | grep "logical replication" | tail -20
```

2. If DDL mismatch: apply the missing migration on this site, then the worker will auto-restart
3. If duplicate key: resolve the conflict manually, then re-enable the subscription:

```
ALTER SUBSCRIPTION sub_from_<peer> ENABLE;
```

Replication Slot Inactive

Symptoms: `pg_replication_slots` shows `active = false`. Prometheus alert fires.

Common Causes:

- Network connectivity issue between sites
- PostgreSQL on the peer site is stopped
- Firewall blocking port 5432 from the peer's IP

Resolution:

1. Verify network connectivity to the peer:

```
pg_isready -h <peer_ip> -U <db_user> -d omnihss
```

2. Check the peer site's PostgreSQL is running
3. Verify firewall rules allow port 5432 from this site's IP

The subscription worker will automatically reconnect when the peer becomes reachable.

WAL Slot Lost

Symptoms: `pg_replication_slots` shows `wal_status = 'lost'`. Ansible validation fails with "WAL SLOT CRITICAL."

Cause: The peer was disconnected for so long that the retained WAL exceeded `max_slot_wal_keep_size` and was cleaned up.

Resolution: The peer requires a full re-seed:

1. Drop the broken subscription on this site:

```
DROP SUBSCRIPTION sub_from_<peer>;
```

2. Drop the broken slot on the peer site:

```
SELECT pg_drop_replication_slot('sub_from_<this_site>');
```

3. Re-run the OmniHSS playbook. It recreates the subscription with `copy_data = true` to perform an initial sync.

Excessive WAL Lag

Symptoms: `pg_replication_slots_pg_wal_lsn_diff` is large and growing. Prometheus alert fires.

Common Causes:

- High-latency or congested inter-site link
- Peer site under heavy load (apply worker cannot keep up)
- Large bulk operation (e.g. mass provisioning) generating significant WAL volume

Resolution:

1. Check if the lag is growing or stable:

```
SELECT slot_name,  
       pg_wal_lsn_diff(pg_current_wal_lsn(), confirmed_flush_lsn) as  
lag_bytes  
FROM pg_replication_slots WHERE slot_type = 'logical';
```

2. If stable: the peer is applying changes but behind. It will catch up.
3. If growing: investigate the network link or peer site load.
4. For bulk operations: lag during the operation is expected and will resolve after the operation completes.

Schema Migration Coordination

Important: Database schema changes (migrations) do not replicate via logical replication. When deploying a new OmniHSS version that includes schema changes:

1. Apply the migration on **all sites** before deploying application code that depends on new columns/tables
2. The Ansible playbook handles this automatically. It runs migrations on every host
3. If deploying manually, run migrations on all sites first:

```
/opt/omnihss/bin/hss rpc "Hss.Command.Database.migrate()"
```

OmniHSS Entity Relationships

[← Back to Operations Guide](#)


Table of Contents

- [Entity Overview](#)
 - [Core Entities](#)
 - [Profile Entities](#)
 - [State Entities](#)
 - [Entity Relationship Diagrams](#)
 - [Entity Lifecycle](#)
 - [Data Flow Patterns](#)
-

Entity Overview

OmniHSS organizes subscriber data into logical entities with clear relationships. Understanding these entities is crucial for operational tasks like provisioning, troubleshooting, and capacity planning.


Entity Categories



Core Entities

Subscriber

The **Subscriber** is the central entity representing a mobile user.



Fields:

Field	Type	Description	Constraints
<code>id</code>	uuid	Primary key	UUID, generated (<code>gen_random_uuid()</code>)
<code>enabled</code>	boolean	Service enabled flag	Default: true
<code>ims_enabled</code>	boolean	IMS services enabled	Default: true
<code>imsi</code>	string	International Mobile Subscriber Identity	14-15 digits, unique
<code>custom_attributes</code>	map	Custom key-value data	Optional
<code>sim_id</code>	uuid	Foreign key to SIM	Required for authentication (may be null while dormant)
<code>key_set_id</code>	uuid	Foreign key to Key Set	Required
<code>epc_profile_id</code>	uuid	Foreign key to EPC Profile	Required for data service (may be null while dormant)
<code>ims_profile_id</code>	uuid	Foreign key to IMS Profile	Required for IMS/voice (may be null while dormant)
<code>roaming_profile_id</code>	uuid	Foreign key to Roaming Profile	Optional; if null, the subscriber cannot

Field	Type	Description	Constraints
			roam (home network only)
<code>subscriber_state_id</code>	uuid	Foreign key to Subscriber State	Auto-created

The "Constraints" column above states what each object is required **for a service**, not what the database needs to insert a row. The database accepts a subscriber that has only an IMSI and a Key Set. Such a subscriber is *dormant*: it exists, but no service works until you assign the matching object. Use this to pre-provision subscribers, then activate them later. See [Dormant Subscriber Pre-Provisioning](#).

What each object enables:

To make this work	The subscriber needs
Authentication (attach, IMS auth)	<code>key_set</code> and <code>sim</code>
LTE data service (S6a attach)	<code>epc_profile</code>
IMS / voice (Cx registration)	<code>ims_profile</code> , and at least one MSISDN
Roaming onto a visited network	a <code>roaming_profile</code> with a matching rule

If a required object is missing when the subscriber appears on the network, the HSS rejects the request and logs the exact reason. See [Dormant Subscriber Behaviour on the Network](#).


Key Points:

- Each subscriber must have exactly one IMSI.
- IMSI must be 14-15 digits (no letters or special characters).

- A subscriber can have multiple MSISDNs (phone numbers).
- Subscriber state is automatically created when the subscriber is created.
- The `enabled` flag controls all services (data and IMS).
- The `ims_enabled` flag controls only IMS services.
- The database needs only the IMSI and the Key Set to insert a subscriber. Every other object is needed for its own service, as listed above. A subscriber with no IMS profile cannot use IMS, even though the record saves without one.

SIM

The **SIM** entity represents a physical or embedded SIM card.



Fields:

Field	Type	Description	Security Level
<code>iccid</code>	string	Integrated Circuit Card ID	Public
<code>sim_vendor</code>	string	SIM manufacturer	Public
<code>batch_name</code>	string	Manufacturing batch	Public
<code>is_esim</code>	boolean	Embedded SIM flag	Public
<code>pin1</code> , <code>pin2</code>	string	PIN codes	Sensitive
<code>puk1</code> , <code>puk2</code>	string	PUK codes	Sensitive
<code>adm1</code> - <code>adm10</code>	string	Administrative codes	Highly Sensitive
<code>kic</code> , <code>kid</code>	binary	OTA security keys	Highly Sensitive

Key Points:

- ICCID uniquely identifies the SIM card
- One SIM can be assigned to one subscriber at a time
- PIN/PUK codes are for end-user SIM locking
- ADM codes are for administrative SIM operations
- KIC/KID are for SIM OTA (Over-The-Air) updates

Key Set

The **Key Set** contains cryptographic keys for authentication.

KEY_SET			
uuid	id	PK	
binary	ki		128-bit
binary	opc		128-bit
binary	op		128-bit
binary	amf		16-bit
bigint	sqn		48-bit sequence
string	authentication_algorithm		

used by




Fields:

Field	Type	Description	Size
ki	binary	Secret key	128 bits (16 bytes)
opc	binary	Operator variant key (derived)	128 bits
op	binary	Operator key (for deriving OPC)	128 bits
amf	binary	Authentication Management Field	16 bits (2 bytes)
sqn	bigint	Sequence number (anti-replay)	48 bits
authentication_algorithm	string	Algorithm name	Currently "milenage"
ota_counter	bigint	OTA operation counter	Integer

Key Points:

- Multiple subscribers can share the same key set
- Ki is the master secret shared with the SIM
- Either OPC or OP must be provided (OPC can be derived from OP)
- SQN is incremented with each authentication
- Milenage is currently the only supported algorithm

Authentication Algorithm:




Key Set, SIM, and Subscriber

The SIM, the Key Set, and the Subscriber are separate objects. Each object has its own lifecycle. The Subscriber is the record that links them.

- **SIM** - the physical card or the eSIM. It holds the ICCID and the PIN, PUK, and ADM codes. It is inventory.
- **Key Set** - the authentication keys (Ki, OPc, AMF, SQN). The network authenticates against these keys.
- **Subscriber** - the network identity and the service (IMSI, MSISDN, profiles, enabled state).

A Subscriber references one SIM (`sim_id`) and one Key Set (`key_set_id`). A Key Set does not reference a SIM. To find which SIM a Key Set belongs to, read the Subscriber that references both.



Why the objects are separate

The objects are separate because they do not map one-to-one in every case:

- **SIM swap.** A subscriber drops a phone and needs a new SIM. You keep the Subscriber, with its MSISDN, profiles, and IMS data. You point it at a new SIM and a new Key Set. The service continues.
- **Multi-IMSI SIM.** One ICCID carries several IMSIs. Each IMSI is a separate Subscriber. Some IMSIs share one Key Set. Some IMSIs have their own Key Set. Keys belong to an IMSI, not to a card. See [Multi-IMSI SIM Support](#).
- **Hosted or sponsored roaming.** The SIM applet authenticates with a visited IMSI. The host network translates the visited IMSI to your home IMSI

before the request reaches the HSS. The two IMSIs share one Key Set.

A Key Set can therefore serve more than one Subscriber. This is why the Key Set is a separate object, and not a field on the SIM.

Correlation at import

The SIM vendor file gives you the ICCID and the keys on one row. At import, you create the Key Set, create the SIM, and create the Subscriber that references both. The Subscriber is the connective record. For the import workflow, see [Dormant Subscriber Pre-Provisioning](#).

MSISDN

The **MSISDN** represents a phone number.

MSISDN			
uuid	id	PK	
string	msisdn	UK	1-15 digits

assigned to

JOIN_SUB_MSISDN		
uuid	subscriber_id	FK
uuid	msisdn_id	FK

belongs to




Fields:

Field	Type	Description	Format
msisdn	string	Mobile Station ISDN Number	1-15 digits, E.164 format

Key Points:

- MSISDN is the phone number in international format.
- One subscriber can have many MSISDNs (one IMSI, many numbers).
- One MSISDN can be assigned to many subscribers (many IMSIs, one number). Use this for a shared number, for example a phone and a smartwatch. The number is stored as one MSISDN record, and each subscriber holds a join row to it.
- A reverse lookup by MSISDN (for example the API `GET /subscriber/msisdn/:msisdn`, or a Diameter lookup keyed on the number) returns one subscriber. When a number is shared, use the IMSI or the ICCID to select a specific subscriber.
- Format: Country code + National number, digits only - no + prefix (e.g., `14155551234` not `+14155551234`)
- The + prefix is stripped automatically during Diameter Cx/Rx lookups when the S-CSCF or P-CSCF sends a SIP URI with or without the +

Multi-MSISDN Pattern:




Profile Entities

EPC Profile

The **EPC Profile** defines data service characteristics for LTE.


EPC_PROFILE			
uuid	id	PK	
string	name	UK	
integer	ue_ambr_dl_kbps		
integer	ue_ambr_ul_kbps		
string	network_access_mode		packet_only or packet_and_circuit
integer	tracking_area_update_interval_seconds		




Fields:

Field	Type	Description	
name	string	Profile name	Text
ue_ambr_dl_kbps	integer	Download bandwidth limit	Kbps
ue_ambr_ul_kbps	integer	Upload bandwidth limit	Kbps
network_access_mode	string	Access restrictions	"packet" "packet"
tracking_area_update_interval_seconds	integer	TAU interval	Seconds

Network Access Modes:



AMBR (Aggregate Maximum Bit Rate):



IMS Profile

The **IMS Profile** defines voice/video service characteristics.

IMS_PROFILE		
uuid	id	PK
string	name	UK
text	ifc_template	


assigned t



Fields:

Field	Type	Description	Format
name	string	Profile name	Text
ifc_template	text	Initial Filter Criteria XML template	XML with variables

IFC Template Variables:




Key Points:

- IFC (Initial Filter Criteria) controls call routing in IMS
- Template is rendered when subscriber registers
- Variables are substituted with actual subscriber data

- Sent to S-CSCF during IMS registration

APN Profile

The **APN Profile** defines characteristics for a specific data access point.




Related Entities:

APN Identifier

APN_IDENTIFIER			
uuid	id	PK	
string	apn	UK	
string	ip_version		ipv4, ipv6, ipv4v6, or ipv4_or_ipv6

Field	Type	Description	Example
apn	string	APN name	"internet", "ims", "mms"
ip_version	string	IP protocol support	See below

IP Version Options:




APN QoS Profile

APN_QOS_PROFILE		
uuid	id	PK
string	name	UK
integer	qci	
integer	allocation_retention_priority	
integer	apn_ambr_dl_kbps	
integer	apn_ambr_ul_kbps	
boolean	pre_emption_capability	
boolean	pre_emption_vulnerability	

QoS Parameters:

Parameter	Description	Range	Default Bearer
qci	QoS Class Identifier	1-9	QCI 9 (Internet)
allocation_retention_priority	ARP priority	1-15	8 (lower priority)
apn_ambr_dl_kbps	APN download limit	0+	Varies
apn_ambr_ul_kbps	APN upload limit	0+	Varies
pre_emption_capability	Can preempt others	true/false	false
pre_emption_vulnerability	Can be preempted	true/false	true

QCI Values:



Roaming Profile

The **Roaming Profile** controls access when subscriber visits other networks.


IMS_PROFILE		
uuid	id	PK
string	name	UK
text	ifc_template	



Roaming Rule:

ROAMING_RULE			
uuid	id	PK	
string	name	UK	
string	mcc		3 digits
string	mnc		2-3 digits
string	data_action		allow or deny
string	ims_action		allow or deny

Rule Evaluation:



State Entities

Subscriber State

The **Subscriber State** tracks real-time subscriber status.

SUBSCRIBER_STATE		
uuid	id	PK
string	last_seen_mme	
string	last_seen_realm	
integer	last_seen_rat_type	
datetime	last_seen_at	
string	last_seen_mcc	
string	last_seen_mnc	
string	last_seen_tac	
string	last_seen_cell_id	
string	last_seen_enodeb_id	
string	last_seen_eci	
string	assigned_scscf	
string	ims_public_identity	
text	sh_repository_data	

SUBSCRIBER

PDN_SESSION

CIRCUIT_SESSION

Key Fields:

Location Information:

- `last_seen_mcc`, `last_seen_mnc` - Visited network
- `last_seen_tac` - Tracking Area Code
- `last_seen_cell_id` - Cell ID
- `last_seen_enodeb_id` - eNodeB ID
- `last_seen_eci` - E-UTRAN Cell Identifier

Network Elements:

- `last_seen_mme` - Current MME serving subscriber
- `last_seen_realm` - Diameter realm of MME
- `last_seen_rat_type` - Radio Access Technology (LTE, 5G, etc.)

IMS Information:


- `assigned_scscf` - Current S-CSCF serving subscriber
- `ims_public_identity` - SIP URI (e.g.,
`sip:+14155551234@ims.example.com`)
- `sh_repository_data` - Custom IMS profile data

Timestamps:

- `last_seen_at` - Last Diameter message received
- Various `last*_at` timestamps for different procedures

PDN Session

The **PDN Session** represents an active data connection.



PDN Session Lifecycle:

APN_IDENTIFIER			
uuid	id	PK	
string	apn	UK	
string	ip_version		ipv4, ipv6, ipv4v6, or ipv4_or_ipv6

LTE Call


The **LTE Call** represents an active VoLTE voice/video call.

LTE_CALL		
uuid	id	PK
string	pcscf_session_id	
string	assigned_pcscf_host	
string	codec	
integer	type	
boolean	dedicated_bearer_active	
integer	dedicated_bandwidth_ul	
integer	dedicated_bandwidth_dl	
text	flow_rules	
datetime	created_at	

belongs to

PDN_SESSION

Call Types:




VoLTE Call Flow:

APN_QOS_PROFILE		
uuid	id	PK
string	name	UK
integer	qci	
integer	allocation_retention_priority	
integer	apn_ambr_dl_kbps	
integer	apn_ambr_ul_kbps	
boolean	pre_emption_capability	
boolean	pre_emption_vulnerability	


Entity Relationship Diagrams

Complete Entity Relationships




Provisioning Relationships

This diagram shows what must exist before creating a subscriber:




Session State Relationships



Entity Lifecycle

Subscriber Provisioning Lifecycle



Session Lifecycle

ROAMING_RULE			
uuid	id	PK	
string	name	UK	
string	mcc		3 digits
string	mnc		2-3 digits
string	data_action		allow or deny
string	ims_action		allow or deny

Data Flow Patterns

Authentication Flow

S6a AIR Request

Lookup Subscriber
by IMSI

Load Key Set

Check Roaming Profile

Generate Auth Vectors
using Milenage

S6a AIA Response

Location Update Flow

S6a ULR Request

Lookup Subscriber
by IMSI


Load EPC Profile
+ APN Profiles

Update Subscriber State
Location, MME, etc.

Build Subscription Data
AMBR, APNs, QoS

S6a ULA Response

IMS Registration Flow



Session Establishment Flow

Gx CCR-I Request

Lookup Subscriber
by IMSI

Load APN Profile
+ QoS Profile

Check Roaming Status

Create PDN Session
Record in State


Build QoS Rules
AMBR, QCI, ARP

Gx CCA-I Response

Query Optimization Patterns

OmniHSS optimizes database queries by selectively preloading only the necessary associations for each operation:

Minimal Query (Authentication)




Use Case: S6a AIR - Only needs crypto keys and roaming rules

Moderate Query (Location Update)



Use Case: S6a ULR - Needs complete EPC profile data

Full Query (IMS Registration)



Use Case: Cx SAR - Needs IMS profile and all phone numbers

[← Back to Operations Guide](#) | [Next: API Reference →](#)

Diameter Response Data Mapping

[← Back to Operations Guide](#)

This document provides detailed mermaid diagrams showing where each field in Diameter protocol responses is sourced from in the OmniHSS system.


Table of Contents

- [Update Location Answer \(S6a ULA\)](#)
 - [Authentication Information Answer \(S6a AIA\)](#)
 - [Server Assignment Answer \(Cx SAA\)](#)
 - [Credit Control Answer \(Gx CCA\)](#)
 - [User Data Answer \(Sh UDA\)](#)
 - [ME Identity Check Answer \(S13 ECA\)](#)
-

Update Location Answer (S6a ULA)

The Update Location Answer is sent by the HSS to the MME during LTE attach procedures. This diagram shows the complete data flow from database tables to Diameter AVPs.

Data Source Mapping



Detailed Field Mapping

Database Source	Field	Default Value
subscriber.enabled	true/false	Subscriber Status
msisdn.msisdn	'14155551234'	MSISDN Number
epc_profile.ue_ambr_ul_kbps	50000	Maximum UE Rate Bandwidth UL
epc_profile.ue_ambr_dl_kbps	100000	Maximum UE Rate Bandwidth DL
epc_profile.network_access_mode	'packet_only'	Network Access Mode
apn_identifier.apn	'internet'	Service Provider Name
apn_identifier.ip_version	'ipv4v6'	IP Version
apn_qos_profile.qci	9	QoS Identifier
apn_qos_profile.allocation_retention_priority	8	Priority Level

Database Source	Field	D
apn_qos_profile.pre_emption_capability	false	Pre en Ca
apn_qos_profile.pre_emption_vulnerability	true	Pre en Vu
apn_qos_profile.apn_ambr_ul_kbps	25000	AF UL
apn_qos_profile.apn_ambr_dl_kbps	50000	AF DL
static_ip.ipv4_static_ip	'100.64.1.1'	Se Pa Ac (IF
static_ip.ipv6_static_ip	'2606:4700::1111'	Se Pa Ac (IF

Key Transformations:

- AMBR bandwidth:** Database stores in kbps, Diameter expects bps (multiply by 1000)
- IP Version encoding:** 0=IPv4, 1=IPv6, 2=IPv4v6, 3=IPv4_or_IPv6
- Subscriber Status:** enabled: true → 0 (SERVICE_GRANTED), enabled: false → 1 (OPERATOR_DETERMINED_BARRING)
- Context-Identifier:** Sequential numbering (0, 1, 2...) for each APN in profile

5. **Static IP:** Only included if assigned via `static_ips` many-to-many relationship


Business Logic Validation:

- Roaming check: Match visited PLMN against `roaming_profile.roaming_rules`
 - Subscriber enabled check: `subscriber.enabled == true`
 - Filter APNs: May exclude IMS APNs if roaming policy denies IMS
-

Authentication Information Answer (S6a AIA)

The Authentication Information Answer provides authentication vectors for LTE/EPC subscribers.

Data Source Mapping



Key Components:

1. **Cryptographic Keys:** All keys stored as hex strings in `key_set` table
2. **SN Management:** Sequence number incremented after each auth vector generation (prevents replay attacks)
3. **Milenage Algorithm:** 3GPP TS 35.206 - generates authentication vectors
4. **KASME Derivation:** Key derived from CK||IK using KDF per TS 33.401


Security Features:

- SQN stored per subscriber (not global)
 - Ki/OPc never leave HSS (only derived values transmitted)
 - AUTN includes sequence number (SQN) and AMF for network authentication
 - Milenage algorithm provides mutual authentication between UE and network
-

Server Assignment Answer (Cx SAA)

The Server Assignment Answer is sent by the HSS to the S-CSCF during IMS registration.

Data Source Mapping



Key Features:

1. **IFC Template:** XML template stored in `ims_profile.ifc_template`
2. **Dynamic Substitution:** Replaces `{{msisdn}}`, `{{imsi}}`, `{{impu}}` at runtime
3. **S-CSCF Assignment:** Stores assigned S-CSCF in `subscriber_state.assigned_scsf`
4. **IMS Public Identity:** Format: `sip:+{msisdn}@{ims_domain}` or `tel:+{msisdn}`


IFC Template Parameters:

- `{{msisdn}}` - First MSISDN from subscriber
 - `{{imsi}}` - Subscriber IMSI
 - `{{impu}}` - IMS Public User Identity (from subscriber_state)
 - `{{impi}}` - IMS Private User Identity (typically IMSI@realm)
-

Credit Control Answer (Gx CCA)

The Credit Control Answer is sent by the PCRF function to the PGW during bearer establishment.

Data Source Mapping



Key Features:

1. **Session Tracking:** Creates/updates `pdn_session` record for each bearer
2. **QoS Enforcement:** Provides QCI and bandwidth limits from APN QoS profile
3. **Charging Rules:** Returns default charging rules for billing integration
4. **CC-Request-Type:** Handles INITIAL (1), UPDATE (2), TERMINATION (3)


Session State Management:

- `INITIAL_REQUEST`: Creates new PDN session record
 - `UPDATE_REQUEST`: Updates existing PDN session
 - `TERMINATION_REQUEST`: Deletes PDN session record
-

User Data Answer (Sh UDA)

The User Data Answer is sent by the HSS to the AS (Application Server) via Sh interface.

Data Source Mapping




Key Features:

1. **Repository Data:** Can store custom XML in `subscriber_state.sh_repository_data`
2. **Service Indication:** Filters data by requested service (e.g., presence, messaging)
3. **Public Identities:** Returns all IMS public identities for subscriber
4. **Reference vs Transparent:** Supports both reference and transparent data modes

ME Identity Check Answer (S13 ECA)

The ME Identity Check Answer is sent by the EIR function to the MME for IMEI validation.

Data Source Mapping



Key Features:

1. **IMEI Regex Matching:** Rules use regular expressions for flexible matching
2. **TAC-based Rules:** Can match Type Allocation Code (first 8 digits)
3. **Default Behavior:** Configurable for unknown IMEIs (accept or reject)
4. **Equipment Status Values:**
 - 0 = WHITELIST (explicitly allowed)
 - 1 = BLACKLIST (stolen/blocked)
 - 2 = GREYLIST (allowed but monitored)
 - 5 = UNKNOWN (no matching rule)

Use Cases:

- Block stolen devices by exact IMEI
- Block device models by TAC pattern
- Whitelist approved devices only
- Track grey market devices

Common Response Elements

All Diameter responses share these common AVPs:




Configuration Example:

```
config :diameter_ex,  
    diameter_host: "hss",  
    diameter_realm: "example.com",  
    diameter_service_name: "OmniHSS"
```

Data Flow Summary

Request Processing Pipeline



Implementation Notes

Protocol Handlers

The system implements handlers for the following Diameter protocols:

- **S6a** - LTE/MME interface for authentication and location updates
- **Cx** - IMS/CSCF interface for IMS registration and server assignment
- **Sh** - IMS/AS interface for subscriber data retrieval
- **Gx** - PCRF interface for policy and charging control
- **Rx** - IMS/AF interface for media authorization
- **S13** - EIR interface for IMEI validation
- **SWx** - WiFi/IMS interface for non-3GPP access authentication

Data Models

The database schema includes the following core entities:

- **Subscriber** - Core subscriber record with IMSI
- **Key Set** - Cryptographic keys for authentication
- **EPC Profile** - LTE service configuration
- **APN Profile** - Access point configuration
- **IMS Profile** - IMS service configuration with IFC templates

- **Roaming Profile** - Roaming rules and restrictions
 - **Subscriber State** - Dynamic session and state tracking
 - **PDN Session** - Active bearer session tracking
 - **Static IP** - Static IP address assignments
 - **EIR Rule** - IMEI validation rules
-

[← Back to Operations Guide](#) | [API Reference →](#) | [Protocol Flows →](#)

OmniHSS Metrics and Monitoring Guide

[← Back to Operations Guide](#)


Table of Contents

- [Monitoring Overview](#)
 - [Control Panel Monitoring](#)
 - [Database Monitoring](#)
 - [Log Monitoring](#)
 - [External Monitoring Integration](#)
 - [Key Performance Indicators](#)
 - [Alerting Strategies](#)
-

Monitoring Overview

OmniHSS provides several mechanisms for monitoring system health, performance, and subscriber activity. Operations staff should use a combination of these tools for full visibility.

Monitoring Layers




Control Panel Monitoring

The Control Panel provides the primary real-time monitoring interface.

Overview Page Monitoring

URL: `https://[hostname]:7443/overview`

Key Metrics Available



Monitored Subscriber States

State	Indicator	What It Means
Idle	No location info	Subscriber powered off or out of coverage
Attached	MME present	Subscriber registered to network
PDN Active	PDN session count > 0	Active data connection
IMS Registered	S-CSCF assigned	Voice services ready
In Call	Active call count > 0	VoLTE call in progress

Extracting Metrics from Overview


The Control Panel does not export metrics directly. You can:

1. **Count visible rows** for total subscribers
2. **Scan for green checkmarks** to count enabled subscribers
3. **Review expanded details** for state information
4. **Note last seen timestamps** for responsiveness

Diameter Page Monitoring

URL: `https://[hostname]:7443/diameter`

Key Metrics



Critical Peer Monitoring

Identify critical peers and monitor their status:

Peer Type	Criticality	Impact if Down
MME	High	No new LTE attachments
P-GW	High	No data sessions
S-CSCF	High	No IMS registrations
P-CSCF	High	No VoLTE calls
I-CSCF	Medium	IMS routing issues
AS	Low-Medium	Specific service unavailable

Application Page Monitoring

URL: `https://[hostname]:7443/application`

Key Metrics

Metric	Description	Normal Range	Action Threshold
Process Count	Active Erlang processes	Varies by load	> 90% of limit
Memory Usage	Total memory consumed	< 80%	> 90%
Uptime	Time since last restart	N/A	Track for stability

Database Monitoring

Direct Database Queries

Connect to SQL Database to extract detailed metrics:

Subscriber Counts

Query the database to retrieve:

- Total count of all subscribers
- Count of enabled subscribers
- Count of IMS-enabled subscribers

Session Statistics

Query the database to retrieve:

- Count of active PDN sessions
- Count of active VoLTE calls
- Breakdown of PDN sessions by APN profile

Location Statistics

Query the database to retrieve:

- Subscriber count grouped by visited network (MCC-MNC combination)
- Count of subscribers currently roaming (not on home PLMN 001-001)
- Distribution of subscribers across different visited networks

Recent Activity

Query the database to retrieve:

- Count of subscribers seen in the last hour
- Distribution of subscribers by serving MME
- Timestamp analysis of last subscriber activity

Database Health Monitoring

Monitor database health by querying:


- Total database size and growth trends
 - Individual table sizes and row counts
 - Current database connection count
 - Query performance and resource usage
-

Log Monitoring

Log Output

OmniHSS outputs logs to **stdout/stderr**, which should be captured by your process manager.

Log Levels



Key Log Patterns to Monitor

Diameter Peer Events:

```
[info] Diameter peer connected: mme01.epc.example.com  
[warn] Diameter peer disconnected: pgw01.epc.example.com  
[error] Diameter peer connection failed: timeout
```

Database Events:


```
[info] Database connection established  
[error] Database connection lost: timeout  
[error] Database query failed: deadlock detected
```

Authentication Events:

```
[info] Authentication successful: IMSI 001001123456789
[warn] Authentication failed: IMSI 001001123456789, invalid vector
[error] Roaming denied: IMSI 001001123456789, MCC 310 MNC 410
```

Log Aggregation

For production deployments, implement log aggregation:



External Monitoring Integration

Health Check Endpoint

API Health Check: GET /api/status

```
curl -k https://hss.example.com:8443/api/status
```

Expected Response:

```
{"status": "ok"}
```

HTTP Status: 200 OK

Monitoring Tool Integration

Nagios/Icinga Example

```
#!/bin/bash
# check_omnihss.sh

API_URL="https://hss.example.com:8443/api/status"

response=$(curl -k -s -o /dev/null -w "%{http_code}" "$API_URL" --max-time 5)

if [ "$response" = "200" ]; then
    echo "OK - OmniHSS API responding"
    exit 0
else
    echo "CRITICAL - OmniHSS API not responding (HTTP $response)"
    exit 2
fi
```

Prometheus Integration


Custom exporters can be created to export OmniHSS metrics to Prometheus by querying the API and database.

SNMP Integration

For SNMP-based monitoring, custom SNMP extension scripts can query the database or API for metrics and return values via SNMP OIDs.

Key Performance Indicators

Operational KPIs



Recommended KPI Thresholds


KPI	Target	Warning	Critical
System Uptime	99.99%	< 99.95%	< 99.9%
Diameter Peer Uptime	99.9%	< 99.5%	< 99%
Authentication Success Rate	> 99%	< 99%	< 95%
Diameter Response Time	< 100ms	> 200ms	> 500ms
Database Query Time	< 50ms	> 100ms	> 500ms
Error Rate	< 0.1%	> 0.5%	> 1%

Capacity KPIs

Metric	Monitor	Plan Action At
Total Subscribers	Current count	80% of expected capacity
Concurrent PDN Sessions	Active sessions	70% of expected maximum
Database Size	MB used	80% of allocated storage
Database Connections	Active connections	80% of pool size

Alerting Strategies

Alert Priorities



Alert Definitions

Critical Alerts (P1)

System Unavailable:

- API health check fails
- Control Panel inaccessible
- Database connection fails
- Action: Immediate investigation and escalation

All Diameter Peers Disconnected:

- Zero connected peers
- Action: Check network, restart if necessary

Database Down:

- Cannot connect to SQL Database
- Action: Investigate database server, restart if necessary

High Priority Alerts (P2)

Critical Diameter Peer Down:

- Primary MME disconnected
- Primary P-GW disconnected
- Primary S-CSCF disconnected
- Action: Investigate peer connectivity within 15 minutes

High Memory Usage:

- Memory > 95%
- Action: Investigate memory leak, plan restart

High Authentication Failure Rate:

- | 10% of auth requests fail
- Action: Check subscriber provisioning, investigate cause

Medium Priority Alerts (P3)

Non-Critical Peer Down:

- Secondary peer disconnected
- Application Server disconnected
- Action: Investigate within 1 hour

Elevated Memory Usage:

- Memory > 85%
- Action: Monitor trend, plan capacity upgrade

Elevated Error Rate:

- Error rate > 1%
- Action: Review logs, identify root cause

Low Priority Alerts (P4)

Capacity Warning:


- Subscribers > 80% of capacity
- Database > 80% of allocated storage

- Action: Plan capacity expansion

Performance Degradation:

- Response times elevated but acceptable
- Action: Monitor and optimize queries

Alert Notification Channels



Monitoring Checklist

Daily Checks

- ☐ Review Control Panel Overview - subscriber counts normal
- ☐ Review Diameter page - all critical peers connected
- ☐ Review Application page - memory and processes within limits
- ☐ Check for error logs - no critical errors in last 24 hours
- ☐ Verify backup completed successfully

Weekly Checks

- ☐ Review capacity trends - subscriber growth
- ☐ Review performance trends - response times
- ☐ Review database size - growth rate acceptable
- ☐ Review error rates - identify patterns
- ☐ Test alert notifications - ensure working

Monthly Checks

- ☐ Capacity planning review - project 6 months ahead
- ☐ Performance optimization review - identify slow queries
- ☐ Security review - certificate expiration, vulnerabilities
- ☐ Documentation review - update runbooks
- ☐ Disaster recovery test - verify backups restore correctly

[← Back to Operations Guide](#) | [Next: Multi-Features →](#)

OmniHSS Multi-MSISDN and Multi-IMSI Features

[← Back to Operations Guide](#)

Table of Contents

- [Overview](#)
 - [Multi-MSISDN: Multiple Phone Numbers](#)
 - [Multi-IMSI SIM: Multiple Network Identities](#)
 - [Combined Scenarios](#)
 - [Configuration Examples](#)
 - [Operational Procedures](#)
-


Overview

OmniHSS supports advanced provisioning capabilities that enable flexible service configurations:

Multi-MSISDN Support

One IMSI → Multiple Phone Numbers


A single subscriber (identified by one IMSI) can have multiple MSISDNs (phone numbers) assigned. All numbers ring on the same device and share the same service profiles.



Multi-IMSI SIM Support

One SIM → Multiple IMSIs

A single physical SIM card can contain multiple IMSIs, allowing the device to attach to different networks using different network identities. This is useful for international roaming and MVNO scenarios.



Multi-MSISDN: Multiple Phone Numbers


How It Works

One subscriber record in the HSS has multiple MSISDNs linked through a join table. When the subscriber registers to IMS, all MSISDNs are included in the IMS profile, allowing inbound calls to any number to reach the device.

Key Characteristics

- **One IMSI** - Subscriber has a single IMSI tied to their SIM card
- **Multiple MSISDNs** - Subscriber can have multiple phone numbers
- **IMS Integration** - All MSISDNs are registered in IMS
- **Shared Service** - All numbers share the same service profiles (EPC, IMS, Roaming)

Data Model




Important: One MSISDN can only be assigned to ONE subscriber at a time. However, one subscriber can have MANY MSISDNs.

Use Cases


1. Business and Personal Lines

A subscriber has both business and personal phone numbers on the same device:




2. International Numbers

A subscriber who travels frequently has numbers in multiple countries:



3. Family Plans


One parent manages multiple family member numbers:



Note: In OmniHSS, this would require multiple subscribers (one per SIM/IMSI), each potentially having multiple MSISDNs.

4. Legacy Line Porting

When a subscriber changes numbers but wants to keep the old number active during transition:



Configuration

Creating MSISDNs

MSISDNs must be created before assigning to subscribers.

```
# Create first MSISDN
curl -k -X POST https://hss.example.com:8443/api/msisdn \
  -H "Content-Type: application/json" \
  -d '{"msisdn": {"msisdn": "14155551001"}}'

# Create second MSISDN
curl -k -X POST https://hss.example.com:8443/api/msisdn \
  -H "Content-Type: application/json" \
  -d '{"msisdn": {"msisdn": "14155551002"}}'
```

Assigning MSISDNs to Subscribers


The assignment is done through the join table in the database.

Database Method:

1. Query the database to get the subscriber ID for the target IMSI
2. Query the database to get the MSISDN IDs for the phone numbers
3. Insert records into the join table linking subscriber_id to each msisdn_id

This creates the many-to-many relationship between the subscriber and their phone numbers.

Provisioning Workflow



Verifying Assignment

Query the database to retrieve the subscriber along with all linked MSISDNs by:

- Joining the subscriber table with the join table


- Joining the join table with the msisdn table
- Grouping results by subscriber to see all phone numbers together

This will show the subscriber ID, IMSI, and a list of all assigned MSISDNs.

IMS Integration

IMS Registration

When a subscriber registers to IMS, **all assigned MSISDNs are included** in the IMS profile sent to the S-CSCF.



IFC Template Rendering

The IMS IFC template can reference all MSISDNs using the `{{msisdns}}` variable.

Example IFC Template:

```

<ServiceProfile>
  <PublicIdentity>
    <Identity>sip:
{{imsi}}@ims.mnc{{mnc}}.mcc{{mcc}}.3gppnetwork.org</Identity>
  </PublicIdentity>
  <!-- Repeat for each MSISDN -->
  <PublicIdentity>
    <Identity>sip:+14155551001@ims.example.com</Identity>
  </PublicIdentity>
  <PublicIdentity>
    <Identity>tel:+14155551001</Identity>
  </PublicIdentity>
  <PublicIdentity>
    <Identity>sip:+14155551002@ims.example.com</Identity>
  </PublicIdentity>
  <PublicIdentity>
    <Identity>tel:+14155551002</Identity>
  </PublicIdentity>
  <!-- ... -->
</ServiceProfile>

```

Template Variable:

- `{{msisdns}}` - List of all MSISDNs assigned to subscriber


Public Identities

Each MSISDN typically results in two IMS public identities:



Inbound Call Routing

When someone calls one of the subscriber's numbers, the IMS network routes to the correct SIP URI:



Outbound Call Presentation

The phone can choose which number to present as caller ID for outbound calls.

SIP INVITE Example:

```
INVITE sip:+15105551234@ims.example.com SIP/2.0
From: "+14155551002" <sip:+14155551002@ims.example.com>;tag=123
To: <sip:+15105551234@ims.example.com>
P-Asserted-Identity: <sip:+14155551002@ims.example.com>
```

The **From** and **P-Asserted-Identity** headers indicate which of the subscriber's numbers is being used.

Troubleshooting Multi-MSISDN

Issue: MSISDN Not Appearing in IMS Registration

Symptoms:

- S-CSCF shows only one public identity
- Calls to second number fail

Troubleshooting Steps:

1. Verify MSISDN Assignment in Database:

- Query the database to retrieve all MSISDNs linked to the subscriber's IMSI
- Check the join table to ensure the relationships exist

2. Check IMS Profile Template:

- Verify template includes `{{msisdns}}` variable
- Confirm template syntax is valid XML

3. Review HSS Logs:

- Look for IMS registration (Cx SAR) messages
- Verify all MSISDNs are included in response

4. Test IMS Registration:

- Trigger re-registration on phone
- Check S-CSCF logs for public identities registered

Issue: Cannot Assign MSISDN to Subscriber

Symptoms:

- Database insert fails
- Error: "Duplicate entry" or "Foreign key constraint"

Possible Causes:

1. MSISDN Already Assigned:

- Query the database to check if the MSISDN is already linked to another subscriber
- **Solution:** Remove the existing assignment first, then create the new assignment

2. MSISDN Does Not Exist:

- Query the database to verify the MSISDN record exists
- **Solution:** Create the MSISDN record first via API or database insert

Issue: Calls to One Number Work, Other Does Not

Symptoms:

- Calls to primary number work
- Calls to secondary number fail or route incorrectly

Troubleshooting Steps:

1. Verify Both Numbers in IMS Registration:

- Check S-CSCF registered public identities
- Confirm both SIP URIs present

2. Check IMS Routing Rules:

- Verify IFC template routing rules apply to all identities
- Check if specific number needs special routing

3. Test Both Numbers:

```
# Test from SIP client
sip:+14155551001@ims.example.com # Should work
sip:+14155551002@ims.example.com # Should also work
```

Issue: API Lookup by MSISDN Returns Wrong Subscriber

Symptoms:

- API query `/api/subscriber/msisdn/:msisdn` returns unexpected subscriber

Verification:

Query the database to find which subscriber the MSISDN is assigned to. This should return exactly one subscriber. If it returns multiple or the wrong subscriber, the join table has incorrect data that needs to be corrected.

Best Practices

Provisioning Order

1. Create all MSISDNs first
2. Create subscriber
3. Assign MSISDNs to subscriber
4. Verify assignment before activation

MSISDN Management

- **Document primary vs secondary** numbers in subscriber custom_attributes
- **Port numbers sequentially** when porting to avoid service disruption
- **Test all numbers** after provisioning before giving to customer

IMS Configuration

- Ensure IFC template handles multiple public identities correctly
- Test inbound routing to all numbers
- Verify caller ID presentation for outbound calls

Migration

When migrating from single to multi-MSISDN:

Subscriber has 1
MSISDN

Add second MSISDN

Test both numbers

Both work?

Yes

No

Activate for customer

Debug issue

Complete

Multi-IMSI SIM: Multiple Network Identities


How It Works

A multi-IMSI SIM contains multiple complete subscriber profiles, each with its own IMSI, keys, and credentials. The device can switch between IMSIs to attach to different networks, often automatically based on location or network availability.

Important: Only **one IMSI can be active at any given time**. When a device switches to a different IMSI on the same SIM card, the HSS will automatically deregister the previously active IMSI.

OmniHSS Implementation

In OmniHSS, each IMSI on a multi-IMSI SIM is provisioned as a **separate subscriber record**, but all reference the **same SIM card**:



Use Cases

1. International Roaming Optimization

- Home IMSI: 001-001 (home network rates)
- US Roaming IMSI: 310-410 (local US rates)

- EU Roaming IMSI: 234-015 (local EU rates)
- Device switches IMSI based on location

2. MVNO Service

- Primary IMSI: MVNO network (reseller)
- Fallback IMSI: Host network (parent operator)
- Automatic failover if MVNO coverage unavailable

3. IoT/M2M Multi-Network

- IMSI 1: Primary carrier
- IMSI 2: Backup carrier for redundancy
- IMSI 3: Emergency/low-cost fallback
- Critical devices maintain connectivity

4. Regulatory Compliance

- Different IMSIs for different regulatory zones
- Comply with local data residency requirements
- Use local network identity per jurisdiction

Multi-IMSI Features

Independent Authentication

- Each IMSI has its own Ki, OPC, and key set
- Separate authentication vectors per IMSI
- Different security credentials per network

Separate Service Profiles

- Different EPC profiles (bandwidth, APNs)
- Different IMS profiles (voice services)
- Different roaming rules per IMSI

Shared Physical Identity

- All IMSIs reference same SIM (via sim_id)
- Same ICCID across all subscriber records
- Logical grouping via SIM card

Network Selection

- Device or SIM card decides which IMSI to use
- Based on available networks, location, policy
- HSS authenticates whichever IMSI device presents

Configuration

```
# 1. Create SIM card (multi-IMSI capable)
SIM_ID=$(curl -k -X POST https://hss.example.com:8443/api/sim \
  -d '{"sim": {"iccid": "8991101200003204510", "is_esim": false}}' \
  \
  | jq -r '.data.id')

# 2. Create key set for IMSI 1 (home network)
KEYSET1=$(curl -k -X POST https://hss.example.com:8443/api/key_set \
  \
  -d '{"key_set": {"ki": "0123456789ABCDEF...", "opc":
"FEDCBA9876..."}}' \
  | jq -r '.data.id')

# 3. Create subscriber 1 (home IMSI)
curl -k -X POST https://hss.example.com:8443/api/subscriber \
  -d '{"subscriber": {
    "imsi": "\"001001111111111\"",
    "sim_id": "\"$SIM_ID\"",
    "key_set_id": "\"$KEYSET1\"",
    "epc_profile_id": "\"e58ed763-928c-4155-bee9-fdbaaadc15f3\""
  }}'


# 4. Create key set for IMSI 2 (roaming partner)
KEYSET2=$(curl -k -X POST https://hss.example.com:8443/api/key_set \
  \
  -d '{"key_set": {"ki": "1111111111111111...", "opc":
"2222222222..."}}' \
  | jq -r '.data.id')

# 5. Create subscriber 2 (roaming IMSI)
curl -k -X POST https://hss.example.com:8443/api/subscriber \
  -d '{"subscriber": {
    "imsi": "\"310410222222222\"",
    "sim_id": "\"$SIM_ID\"",
    "key_set_id": "\"$KEYSET2\"",
    "epc_profile_id": "\"f47ac10b-58cc-4372-a567-0e02b2c3d479\""
  }}'

# 6. Repeat for additional IMSIs on the SIM...
```

Authentication Flow

When a multi-IMSI device attaches:



The HSS does not need to know it is a multi-IMSI SIM. It authenticates whatever IMSI the device presents.

IMSI Switching and Automatic Deregistration

When a multi-IMSI SIM switches from one IMSI to another, only one IMSI can be registered at a time on the network. OmniHSS automatically handles this by sending a **Cancel Location Request (CLR)** to deregister the previously active IMSI when a new IMSI from the same SIM card registers.

Single Active IMSI Rule


Key Concept: Only one subscriber (IMSI) per SIM card can be active at any given time.

- If a subscriber is registered on an MME using **IMSI X**

- And the HSS receives an Update Location Request for **IMSI Y** (on the same SIM as IMSI X)
- The HSS automatically sends a **Cancel Location Request** to deregister **IMSI X**

This ensures clean handoff between IMSIs and prevents conflicts in the network.

IMSI Switching Flow



Why This Matters

Network Integrity:

- Prevents duplicate registrations from the same physical SIM
- Ensures network resources are properly released
- Maintains accurate subscriber location data

Billing Accuracy:

- Only one IMSI is charged for network access at a time
- Clear session boundaries between IMSI switches
- Accurate CDR (Call Detail Record) generation

Resource Management:

- MME resources for old IMSI are freed
- PDP contexts and bearers are cleaned up
- Location tracking remains accurate

IMSI Switch Triggers

The device/SIM decides when to switch IMSIs based on:

1. Network Availability

- Home IMSI network not available
- Switch to roaming partner IMSI

2. Manual Selection

- User manually selects network
- SIM switches to corresponding IMSI

3. Policy-Based

- SIM card has internal rules (e.g., prefer local IMSI in certain countries)
- Automatic switching based on MCC/MNC


4. Cost Optimization

- Switch to IMSI with lower roaming rates

- Use local IMSI to avoid roaming charges

IMS Considerations

The same Cancel Location Request behavior applies to IMS registration:



Operational Impact


For Operations Staff:

1. **Subscriber appears offline:** When IMSI switches, the old IMSI will show as "deregistered" in the HSS. This is normal behavior.
 2. **Two subscriber records for one SIM:** Multi-IMSI SIMs will have multiple subscriber records sharing the same `sim_id`. Only one will be in "registered" state at a time.
 3. **Location tracking:** The `subscriber_state` table tracks which MME/SGSN each IMSI is registered with. When IMSI switches, the old location is cleared.
 4. **Troubleshooting:** If a device cannot be reached:
 - Check which IMSI is currently registered
 - Verify the correct IMSI is being used for the current network
 - Confirm only one IMSI per SIM is in registered state
-

Combined Scenarios

Multi-IMSI + Multi-MSISDN

You can combine both features: multiple IMSIs on one SIM, each with multiple MSISDNs.



Example Use Case:

- **Home Network (IMSI 1):**
 - Personal number: +1-415-555-1001
 - Business number: +1-415-555-1002
- **US Roaming Network (IMSI 2):**
 - Personal number: +1-212-555-2001
 - Business number: +1-212-555-2002

When device is in home territory, uses IMSI 1 with its MSISDNs. When roaming in US, switches to IMSI 2 with different MSISDNs optimized for US network.

Operational Procedures

Managing Multi-MSISDN Subscribers

View all MSISDNs for a subscriber:

```
Query via API: GET /api/subscriber/imsi/:imsi
```

The response includes all linked MSISDNs.

Troubleshooting Multi-IMSI

Device not attaching with second IMSI:

1. Verify second subscriber record exists for that IMSI
2. Check key_set is configured correctly for that IMSI
3. Verify EPC profile is assigned
4. Confirm roaming rules allow attachment

Device switching IMSIs unexpectedly:

- This is controlled by device/SIM logic, not HSS
- HSS authenticates whatever IMSI is presented
- Check device IMSI selection settings

Troubleshooting Multi-MSISDN

Second number not ringing:

1. Verify MSISDN is linked in join table
2. Check IMS profile template includes `{{msisdns}}` variable
3. Confirm IMS registration includes all public identities
4. Review S-CSCF logs for registered identities

Outbound calls only show one number:

- Device selects which number to present as caller ID
 - This is device configuration, not HSS
 - HSS provides all identities; device chooses
-

Benefits Summary

Multi-MSISDN Benefits

✓ One SIM, multiple phone numbers ✓ Separate business and personal lines ✓ International local presence ✓ Simplified device management ✓ All numbers share same data service ✓ Centralized billing per IMSI

Multi-IMSI SIM Benefits

✓ Optimized roaming costs ✓ Automatic network selection ✓ Redundancy and failover ✓ Local network identity ✓ Regulatory compliance ✓ Service continuity across networks

Combined Benefits

✓ Maximum flexibility ✓ Different number sets per network ✓ Optimized for each use case ✓ Complex business scenarios ✓ International and local optimization


[← Back to Operations Guide](#)

OmniHSS Profile Management


[← Back to Operations Guide](#)

Overview

OmniHSS uses **profiles** to define service characteristics for subscribers. Profiles allow you to create reusable service templates that can be assigned to multiple subscribers, simplifying provisioning and ensuring consistency.



Profile Types



EPC Profiles

EPC (Evolved Packet Core) Profiles define data service characteristics for LTE subscribers.

Key Parameters

Parameter	Description	Typical Value
ue_ambr_dl_kbps	Download speed limit	10,000 - 1,000,0 Kbps
ue_ambr_ul_kbps	Upload speed limit	5,000 - 500,000 Kbps
network_access_mode	Service type	"packet_only" or "packet_and_circ
tracking_area_update_interval_seconds	TAU timer	54 seconds (typi

Creating EPC Profiles

```
curl -k -X POST https://hss.example.com:8443/api/epc/profile \
-H "Content-Type: application/json" \
-d '{
  "apn_profiles": [],
  "name": "Premium 100Mbps",
  "network_access_mode": "packet_only",
  "tracking_area_update_interval_seconds": 600,
  "ue_ambr_dl_kbps": 100000,
  "ue_ambr_ul_kbps": 50000
}'
```

Common EPC Profile Templates

Basic Internet:

- Download: 10 Mbps (10,000 Kbps)
- Upload: 5 Mbps (5,000 Kbps)

Standard:

- Download: 50 Mbps (50,000 Kbps)
- Upload: 25 Mbps (25,000 Kbps)

Premium:

- Download: 100 Mbps (100,000 Kbps)
- Upload: 50 Mbps (50,000 Kbps)

Unlimited:

- Download: 1 Gbps (1,000,000 Kbps)
 - Upload: 500 Mbps (500,000 Kbps)
-

IMS Profiles

IMS Profiles define voice service characteristics, primarily through IFC (Initial Filter Criteria) templates.

IFC Templates

IFC templates are XML documents that define call routing rules for the S-CSCF.

Template Variables:

- `{{imsi}}` - Subscriber IMSI
- `{{msisdns}}` - List of phone numbers
- `{{mcc}}` - Home country code
- `{{mnc}}` - Home network code

Creating IMS Profiles

```
curl -k -X POST https://hss.example.com:8443/api/ims/profile \
-H "Content-Type: application/json" \
-d '{
  "ims_profile": {
    "name": "Standard VoLTE",
    "ifc_template": "<InitialFilterCriteria>...
</InitialFilterCriteria>"
  }
}'
```


IFC Template Example

```
<ServiceProfile>
  <PublicIdentity>
    <Identity>sip:
{{imsi}}@ims.mnc{{mnc}}.mcc{{mcc}}.3gppnetwork.org</Identity>
  </PublicIdentity>
  <InitialFilterCriteria>
    <Priority>0</Priority>
    <TriggerPoint>
      <ConditionTypeCNF>0</ConditionTypeCNF>
      <SPT>
        <ConditionNegated>0</ConditionNegated>
        <Group>0</Group>
        <Method>INVITE</Method>
      </SPT>
    </TriggerPoint>
    <ApplicationServer>
      <ServerName>sip:as.ims.example.com</ServerName>
      <DefaultHandling>0</DefaultHandling>
    </ApplicationServer>
  </InitialFilterCriteria>
</ServiceProfile>
```

APN Profiles

APN (Access Point Name) Profiles define network access points for data connections.

APN Components



APN Identifier

Defines the APN name and IP protocol support.

Common APNs:

- `internet` - General internet access
- `ims` - IMS/VoLTE signaling
- `mms` - Multimedia messaging
- `vzwadmin` - Carrier-specific

IP Version Options:

- `"ipv4"`: IPv4 only
- `"ipv6"`: IPv6 only
- `"ipv4v6"`: IPv4v6 (dual stack)
- `"ipv4_or_ipv6"`: IPv4 or IPv6 (network choice)

APN QoS Profile

Defines quality of service parameters.

QCI (QoS Class Identifier) Values:

QCI	Type	Use Case	Priority
1	GBR	Conversational voice	Highest
2	GBR	Conversational video	High
4	GBR	Video streaming	High
5	Non-GBR	IMS signaling	Medium
9	Non-GBR	Internet (default)	Lowest

Session-Level Charging Method (optional):

The APN QoS profile can also pin the default charging method for the IP-CAN session, sent as the top-level `Online/Offline` AVPs in the Gx CCA-I.

Field	Type	Default	Description
<code>online_charging_enabled</code>	boolean	<code>null</code>	When set, forces the session-level <code>Online</code> AVP (<code>true</code> = enable, <code>false</code> = disable). When <code>null</code> , the PCRF echoes the value the PGW sent in the CCR-I.
<code>offline_charging_enabled</code>	boolean	<code>null</code>	When set, forces the session-level <code>Offline</code> AVP (<code>true</code> = enable, <code>false</code> = disable). When <code>null</code> , the PCRF echoes the value the PGW sent in the CCR-I.

See [PCRF: Session-Level Online/Offline Charging](#) for the full behaviour and AVP value reference.

Creating Complete APN Configuration

```
# 1. Create APN Identifier
APN_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/identifier \
-H "Content-Type: application/json" \
-d '{"apn": "internet", "ip_version": "ipv4v6"}' \
| jq -r '.response.id')

# 2. Create APN QoS Profile
QOS_ID=$(curl -k -X POST
https://hss.example.com:8443/api/apn/qos_profile \
-H "Content-Type: application/json" \
-d '{
  "name": "Best Effort",
  "allocation_retention_priority": 8,
  "apn_ambr_dl_kbps": 50000,
  "apn_ambr_ul_kbps": 25000,
  "pre_emption_capability": false,
  "pre_emption_vulnerability": true,
  "qci": 9
}' | jq -r '.response.id')

# 3. Create APN Profile
curl -k -X POST https://hss.example.com:8443/api/apn/profile \
-H "Content-Type: application/json" \
-d "{
  \"apn_identifier_id\": \"$APN_ID\",
  \"apn_qos_profile_id\": \"$QOS_ID\",
  \"name\": \"Internet APN\"
}"
```

Assigning APNs to EPC Profile

APNs are linked to EPC Profiles through the `join_epc_profile_to_apn_profile` table.


Insert records into the join table to link APN profile IDs to the EPC profile ID. Multiple APN profiles can be assigned to one EPC profile.

Roaming Profiles

See detailed documentation in [Roaming Control Guide](#).

Profile Assignment

Subscriber Profile Relationships



Assigning Profiles to Subscribers

```
# Assign EPC and IMS profiles during subscriber creation
curl -k -X POST https://hss.example.com:8443/api/subscriber \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "imsi": "001001123456789",
    "key_set_id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
    "epc_profile_id": "e58ed763-928c-4155-bee9-fdbaaadc15f3",
    "ims_profile_id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
    "roaming_profile_id": "9c858901-8a57-4791-81fe-4c455b099bc9"
  }
}'

# Update subscriber profile
curl -k -X PUT
https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-
90e6-d701748f0851 \
-H "Content-Type: application/json" \
-d '{
  "subscriber": {
    "epc_profile_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479"
  }
}'
```

Profile Management Best Practices

Design Principles

1. **Create Standard Profiles** - Define common service tiers (Basic, Standard, Premium)
2. **Reuse Profiles** - Assign same profile to multiple subscribers
3. **Document Changes** - Track profile modifications
4. **Test Before Production** - Verify profile works with test subscriber first

Profile Naming Convention


[Service Tier]-[Speed]-[Features]

Examples:

- "Basic-10Mbps-Internet"
- "Premium-100Mbps-VoLTE"
- "Enterprise-1Gbps-MultiAPN"

Profile Migration

When changing a subscriber's profile:



Important: Profile changes take effect on the next:

- Tracking Area Update (TAU)
- Attach
- IMS Registration (for IMS profile changes)

Troubleshooting Profile Issues

Subscriber not getting expected speed:

1. Check assigned EPC profile AMBR values
2. Check APN QoS profile AMBR values
3. Verify MME/P-GW enforcing QoS correctly
4. Check for network congestion

IMS registration fails:

1. Verify IMS profile assigned
2. Check IFC template XML validity
3. Review S-CSCF logs for IFC processing errors
4. Confirm S-CSCF selection configuration

APN not available:

1. Verify APN profile linked to EPC profile
2. Check APN identifier matches network request
3. Review PDN connectivity request from UE

[← Back to Operations Guide](#) | [Next: Roaming Control →](#)

OmniHSS Protocol Flows

[← Back to Operations Guide](#)


Overview

This document details the Diameter protocol message flows supported by OmniHSS. Understanding these flows is essential for troubleshooting and operations.

S6a Interface (LTE/EPC)

Authentication Information Request (AIR/AIA)

MME requests authentication vectors for subscriber.




Key AVPs:

- Request: User-Name (IMSI), Visited-PLMN-Id, Number of Requested Vectors
- Response: Authentication-Info (RAND, AUTN, XRES, KASME)

Update Location Request (ULR/ULA)

MME notifies HSS of subscriber location and retrieves subscription data.




Key AVPs:

- Request: User-Name (IMSI), RAT-Type, ULR-Flags, Visited-PLMN-Id, UE-SRVCC-Capability
- Response: Subscription-Data (AMBR, APN-Configuration, Network-Access-Mode)


Purge UE Request (PUR/PUA)

MME notifies HSS when subscriber context is deleted.



Notify Request (NOR/NOA)

MME informs HSS of various events.




Cancel Location Request (CLR/CLA)

HSS initiates location cancellation to inform MME that subscriber should be detached. OmniHSS supports both automatic and programmatic CLR sending.

Automatic CLR (MME Handover)

When a subscriber performs an Update Location Request from a new MME, OmniHSS automatically sends a CLR to the previous MME to clean up stale registrations.




Key AVPs (Automatic CLR):

- User-Name: IMSI of subscriber
- Destination-Host: Previous MME hostname
- Destination-Realm: Previous MME realm
- Cancellation-Type: 0 (MME Update Procedure)

- CLR-Flags: 0
- Subscription-Data: Full subscription profile

Programmatic CLR (API-Triggered)

Administrators can trigger CLR via the programmatic API to forcibly detach subscribers (e.g., for subscription withdrawal, fraud prevention, or administrative actions).



Key AVPs (Programmatic CLR):

- User-Name: IMSI of subscriber
- Destination-Host: Last seen MME hostname
- Destination-Realm: Last seen MME realm
- Cancellation-Type: `:subscription_withdrawal` (encoded as integer per 3GPP TS 29.272)
- CLR-Flags:
 - s6a_indicator: 1 (indicates S6a interface)
 - reattach_required: 1 (UE must re-authenticate to reattach)

Cancellation Types

OmniHSS supports multiple cancellation types per 3GPP TS 29.272:

Type	Value	Description	Use Case
MME Update Procedure	0	Normal MME change	Automatic during ULR from new MME
SGSN Update Procedure	1	SGSN handover	3G/2G handover scenarios
Subscription Withdrawal	2	Admin termination	Manual detach via API
Update Procedure IWF	3	Interworking function update	Legacy network interop
Initial Attach Procedure	4	Fresh registration	Force re-authentication

CLR-Flags

The CLR-Flags AVP is a bitmask with the following fields:

Flag	Bit	Description
S6a/S6d Indicator	0	1 = S6a interface used
Reattach Required	1	1 = UE must perform new attach

Example CLR-Flags Configuration:

```
clr_flags: %{
  s6a_indicator: 1,      # Using S6a interface
  reattach_required: 1   # Force re-authentication
}
```

Multi-IMSI Scenarios

OmniHSS tracks MME registration **per subscriber (IMSI)**, not per MSISDN. This is critical for understanding CLR behavior in multi-IMSI scenarios:

Scenario 1: Multiple MSISDNs, Single IMSI

Subscriber A:

- IMSI: 999000123456789
- MSISDNs: ["+1234567890", "+9876543210"]
- last_seen_mme: "mme01.operator.com"

When this subscriber moves to a new MME:

- **One CLR sent** to "mme01.operator.com" with IMSI 999000123456789
- Both MSISDNs are affected (same subscriber, same SIM)
- User-Name AVP contains the IMSI, not MSISDNs

Scenario 2: Multiple Subscribers (Different IMSIs), Same MSISDN

OmniHSS enforces **unique MSISDN constraint** (one MSISDN cannot belong to multiple subscribers simultaneously). However, during porting/migration:

Subscriber A:

- IMSI: 9990001111111111
- MSISDN: "+1234567890"
- last_seen_mme: "mme01.operator.com"

Subscriber B (after porting):

- IMSI: 9990002222222222
- MSISDN: "+1234567890" # Same MSISDN, different SIM/IMSI
- last_seen_mme: "mme02.operator.com"

When Subscriber B registers:

- **No CLR sent** (different IMSI = different subscriber)
- Subscriber A remains registered at mme01
- Subscriber B registers at mme02
- Both can be active simultaneously (different physical devices)

Scenario 3: Programmatic CLR for Multi-MSISDN Subscriber

Result:

- **One CLR sent** to the subscriber's last_seen_mme
- **All MSISDNs** associated with that IMSI are effectively detached
- The IMSI is the primary key for tracking MME registration

Important Notes


1. **IMSI is the Key:** CLR operations are always **per IMSI**, never per MSISDN. The `subscriber_state` table tracks `last_seen_mme` by subscriber (IMSI).
 2. **Atomic Operation:** Each subscriber can only be registered at one MME at a time. The automatic CLR ensures this by cleaning up the old registration.
 3. **No CLR if No Previous MME:** If `last_seen_mme` is `nil` (subscriber never registered), no CLR is sent during ULR.
 4. **Subscription Data Included:** The automatic CLR (during ULR) includes the full `Subscription-Data` AVP to help the old MME properly clean up context.
 5. **Asynchronous:** The CLR is sent asynchronously (fire-and-forget). The ULA response to the new MME does not wait for CLA from the old MME.
 6. **CLA Handling:** OmniHSS receives CLA responses but currently discards them. This prevents message loops and is standard HSS behavior.
-

SWx Interface (Non-3GPP Access / WiFi Calling)

The SWx interface enables WiFi calling by connecting the ePDG (Evolved Packet Data Gateway) to the HSS for subscriber authentication and authorization over non-3GPP access networks.

Multimedia Auth Request (MAR/MAA)

ePDG requests EAP-AKA authentication vectors for WiFi calling registration.




Key AVPs:

- Request: User-Name (IMSI or IMSI@realm), SIP-Auth-Data-Item (authentication scheme), SIP-Number-Auth-Items
- Response: SIP-Auth-Data-Item (SIP-Authenticate, SIP-Authorization, Confidentiality-Key, Integrity-Key)

SQN Resynchronization: When the UE detects an authentication failure due to SQN mismatch, the ePDG includes resync data in the SIP-Authorization AVP. OmniHSS extracts AUTS from this field and recalculates SQN using IND-length-aware computation per 3GPP TS 33.102.

Server Assignment Request (SAR/SAA)

ePDG registers or deregisters the subscriber for WiFi calling services.



Server Assignment Types:


Type	Value	Description
NO_ASSIGNMENT	0	Query only, no state change
REGISTRATION	1	Initial WiFi calling registration
RE_REGISTRATION	2	Registration refresh
UNREGISTERED_USER	3	Services for unregistered user
TIMEOUT_DEREGISTRATION	4	Registration timeout
USER_DEREGISTRATION	5	User-initiated deregistration
AUTHENTICATION_FAILURE	7	Auth failed, clear state
ADMINISTRATIVE_DEREGISTRATION	8	Admin-initiated deregistration

Key AVPs:

- Request: User-Name (IMSI), Server-Assignment-Type, Server-Name (ePDG identity), Service-Selection (APN)
- Response: User-Data (IFC profile XML), Non-3GPP-User-Data

WiFi Calling Registration Flow


Complete end-to-end WiFi calling registration.



Cx Interface (IMS)


User Authorization Request (UAR/UAA)

I-CSCF queries if user is authorized to register.



Server Assignment Request (SAR/SAA)

S-CSCF registers/deregisters user and retrieves IMS profile.




IFC Template Rendering:

- `{{imsi}}` → Actual IMSI
- `{{msisdns}}` → List of phone numbers
- `{{mcc}}`, `{{mnc}}` → Home PLMN codes


Multimedia Auth Request (MAR/MAA)

S-CSCF requests authentication vectors for IMS registration.



Location Info Request (LIR/LIA)

I-CSCF queries which S-CSCF is serving the user.




Sh Interface (IMS Profile Data)

See [Sh RepositoryData \(Transparent Data\)](#) for the data model, SequenceNumber/concurrency rules, and the REST provisioning API for MMTEL-Services / IMS-ODB-Information documents.


User Data Request (UDR/UDA)

Application Server requests subscriber profile data.




Profile Update Request (PUR/PUA)

Application Server updates subscriber profile data.



Subscribe Notifications Request (SNR/SNA)

Application Server subscribes to profile changes.




Gx Interface (Policy Control)

OmniHSS functions as the PCRF (Policy and Charging Rules Function) via the Gx interface.

See [PCRF Documentation](#) for detailed architecture, policy configuration, and QoS management.

Credit Control Request - Initial (CCR-I/CCA-I)

P-GW requests policy rules when PDN session is established.




Key AVPs:

- Request: Subscription-Id (IMSI), Called-Station-Id (APN), RAT-Type, IP-CAN-Type
- Response: QoS-Information (QCI, ARP, AMBR), Charging-Rule-Install


Credit Control Request - Update (CCR-U/CCA-U)

P-GW notifies of session changes.




Credit Control Request - Terminate (CCR-T/CCA-T)

P-GW notifies when PDN session ends.



Re-Auth Request (RAR/RAA)

OmniHSS (PCRF) initiates policy update to P-GW.




Rx Interface (IMS Media Policy)

OmniHSS functions as the PCRF via the Rx interface for IMS media authorization.

See **PCRF Documentation** for detailed VoLTE call flows and media authorization.

AA Request (AAR/AAA)

P-CSCF requests media authorization for IMS session.




Key Information:

- Parse SDP to determine codec and bandwidth
- Calculate required bandwidth (UL/DL)
- Create SDF filters for media flows
- Trigger dedicated bearer via Gx RAR

Session Termination Request (STR/STA)

P-CSCF notifies when IMS session ends.



Sy Interface (Spending Limit Control)

OmniHSS, acting as the PCRF, uses the Sy interface to obtain subscriber spending limit status from an external OCS (Online Charging System) and apply spend-driven policy over Gx. Sy uses Diameter application ID 16777302 (3GPP TS 29.219). The HSS is the Sy client; the OCS is the server. See [Sy Interface](#) for the full reference (policy counter mapping, AVPs, configuration).

Spending Limit Request (SLR/SLA)

The PCRF opens a per-subscriber Sy session to fetch the current status of the OCS's policy counters, then folds the resulting rules into the Gx CCA it already returns.


Parse error on line 9: ... counter identifier;
install/remove -----
 ---^ Expecting 'SPACE', 'NEWLINE', 'create', 'box', 'end', 'autonumber',
 'activate', 'deactivate', 'title', 'legacy_title', 'acc_title', 'acc_descr',
 'acc_descr_multiline_value', 'loop', 'rect', 'opt', 'alt', 'par', 'par_over', 'critical',

'break', 'option', 'and', 'else', 'participant', 'participant_actor', 'destroy', 'note', 'links', 'link', 'properties', 'details', 'ACTOR', got 'INVALID'

Try again


Spending Status Notification (SNR/SNA)

When a counter's status changes (for example a data allowance is exhausted), the OCS notifies the PCRF, which pushes the policy change to the PGW with a Gx RAR.



Session Termination (STR/STA)

When the subscriber's last data session ends, the PCRF closes the Sy session.




S13 Interface (EIR)

OmniHSS functions as the EIR (Equipment Identity Register) via the S13 interface.

See **EIR Documentation** for detailed equipment identity checking, IMEI validation, and blacklist management.

ME Identity Check Request (ECR/ECA)

External EIR client (or MME) requests equipment validation.



Equipment Status Values:


- **Equipment Unknown (0)** - Device allowed (whitelist)
 - **Equipment Blacklisted (1)** - Device blocked
 - **Equipment Greylisted (2)** - Device allowed but tracked
-

SLh Interface (LCS / Location Services)

OmniHSS answers SLh `LCS-Routing-Info-Request` (RIR) so a GMLC can discover which MME currently serves a subscriber before requesting their location over SLg. The serving MME is the one recorded at S6a registration (Update-Location). SLh uses Diameter application id `16777291` (3GPP TS 29.173).

LCS Routing Info Request (RIR/RIA)

GMLC requests the serving node for a subscriber.



Notes:

- The IMSI is taken from `User-Name`; an MSISDN lookup is used as a fallback.
- The returned `Serving-Node` carries the `MME-Name/MME-Realm` last recorded by the S6a AIR/ULR handlers (`subscriber_state.last_seen_mme` /

last_seen_realm) - no extra provisioning is required.


- A GMLC typically follows a successful RIA with an SLg Provide-Location-Request to the returned MME.

Result Codes:

- **2001** - Success; Serving-Node returned.
- **5001** - DIAMETER_ERROR_USER_UNKNOWN; IMSI/MSISDN not provisioned.
- **4201** - DIAMETER_ERROR_ABSENT_USER; subscriber known but no serving MME on record (never attached, or location cancelled).

Complete Call Flow: VoLTE Call

End-to-end VoLTE call setup showing multiple interfaces.




Zh Interface (Generic Bootstrapping Architecture)

The Zh interface enables Generic Bootstrapping Architecture (GBA) by connecting the Bootstrapping Server Function (BSF) to the HSS for subscriber authentication and key derivation.

Multimedia Auth Request (MAR/MAA)

BSF requests GBA authentication vectors for bootstrapping.



Key AVPs:

- Request: User-Name (IMPI), Public-Identity, SIP-Auth-Data-Item (authentication scheme), Destination-Realm
- Response: SIP-Auth-Data-Item (SIP-Authenticate, SIP-Authorization, Confidentiality-Key, Integrity-Key), GBA-UserSecSettings

GBA Use Cases:


Application	Description
MBMS	Mobile Broadcast Multicast Service key management
HTTPS	GBA-based certificate provisioning
NAF	Generic Network Application Function authentication
Presence	Secure presence service authentication

SWm Interface (Untrusted Non-3GPP Access)

The SWm interface enables EAP-AKA authentication for untrusted non-3GPP access networks (e.g., WiFi via ePDG) by connecting the 3GPP AAA Server to the HSS.

Diameter-EAP-Request (DER/DEA)

EAP authentication exchange for WiFi access.




Key AVPs:

- Request: Session-Id, Auth-Application-Id, EAP-Payload, Auth-Request-Type, User-Name (optional)
- Response: EAP-Payload, EAP-Master-Session-Key (MSK), APN-Configuration, Session-Timeout

AA-Request (AAR/AAA)

Authorization after successful EAP authentication.




Key AVPs:

- Request: Session-Id, Auth-Application-Id, User-Name, Auth-Request-Type, AAR-Flags
- Response: APN-Configuration, 3GPP-Charging-Characteristics, Session-Timeout

Session-Termination-Request (STR/STA)

WiFi session termination notification.



Termination Causes:

Cause	Value	Description
DIAMETER_LOGOUT	1	User logout
DIAMETER_SERVICE_NOT_PROVIDED	2	Service unavailable
DIAMETER_BAD_ANSWER	3	Protocol error
DIAMETER_ADMINISTRATIVE	4	Admin termination
DIAMETER_LINK_BROKEN	5	Connection lost
DIAMETER_AUTH_EXPIRED	6	Auth timeout
DIAMETER_USER_MOVED	7	User moved to other access
DIAMETER_SESSION_TIMEOUT	8	Session timeout

Troubleshooting Protocol Issues

Authentication Failures (S6a AIR)

Check:

1. Key set configured correctly (Ki, OPC, AMF)
2. SQN synchronization (if repeated failures)
3. Roaming rules allow visited network

Location Update Failures (S6a ULR)

Check:

1. EPC profile exists and has APNs configured
2. Roaming allowed for data services
3. MME identity format correct

IMS Registration Failures (Cx SAR)

Check:

1. IMS profile assigned to subscriber
2. IFC template valid XML
3. S-CSCF selection configured
4. MSISDNs assigned if used in template

PDN Connection Failures (Gx CCR-I)

Check:

1. APN exists in EPC profile's APN list
 2. APN QoS profile configured
 3. PDN session table not full (if limits exist)
-

[← Back to Operations Guide](#)


OmniHSS Roaming Control

[← Back to Operations Guide](#)

Overview


OmniHSS provides granular roaming control, allowing you to define which networks subscribers can access for both data and IMS services when roaming.

Roaming Control Flow



Roaming Profile Structure

Components



Roaming Rule

Each rule specifies action for a specific network (MCC/MNC combination).

Fields:

- `name` - Descriptive name
- `mcc` - Mobile Country Code (3 digits)
- `mnc` - Mobile Network Code (2-3 digits)
- `data_action` - "allow" or "deny"
- `ims_action` - "allow" or "deny"

Roaming Profile

Defines default behavior and links to rules.

Fields:

- `name` - Profile name
 - `data_action_if_no_rules_match` - "allow" or "deny"
 - `ims_action_if_no_rules_match` - "allow" or "deny"
-

Configuration Examples

Allow All Roaming

```
# Create profile that allows everything
curl -k -X POST https://hss.example.com:8443/api/roaming/profile \
-H "Content-Type: application/json" \
-d '{
  "roaming_profile": {
    "name": "Allow All",
    "data_action_if_no_rules_match": "allow",
    "ims_action_if_no_rules_match": "allow",
    "roaming_rules": []
  }
}'
```

Deny All Roaming

```
# Create profile that blocks everything
curl -k -X POST https://hss.example.com:8443/api/roaming/profile \
-H "Content-Type: application/json" \
-d '{
  "roaming_profile": {
    "name": "No Roaming",
    "data_action_if_no_rules_match": "deny",
    "ims_action_if_no_rules_match": "deny",
    "roaming_rules": []
  }
}'
```

Allow Specific Networks (Whitelist)

```
# Create AT&T rule
RULE1=$(curl -k -X POST
https://hss.example.com:8443/api/roaming/rule \
-H "Content-Type: application/json" \
-d '{
  "roaming_rule": {
    "name": "Allow AT&T",
    "mcc": "310",
    "mnc": "410",
    "data_action": "allow",
    "ims_action": "allow"
  }
}' | jq -r '.response.id')

# Create Verizon rule
RULE2=$(curl -k -X POST
https://hss.example.com:8443/api/roaming/rule \
-H "Content-Type: application/json" \
-d '{
  "roaming_rule": {
    "name": "Allow Verizon",
    "mcc": "311",
    "mnc": "480",
    "data_action": "allow",
    "ims_action": "allow"
  }
}' | jq -r '.response.id')

# Create profile with deny-by-default and link rules
curl -k -X POST https://hss.example.com:8443/api/roaming/profile \
-H "Content-Type: application/json" \
-d "{
  \"roaming_profile\": {
    \"name\": \"US Carriers Only\",
    \"data_action_if_no_rules_match\": \"deny\",
    \"ims_action_if_no_rules_match\": \"deny\",
    \"roaming_rules\": [$RULE1, $RULE2]
  }
}"
```

Allow Data, Block Voice

```
# Create rule that allows data but blocks IMS
curl -k -X POST https://hss.example.com:8443/api/roaming/rule \
-H "Content-Type: application/json" \
-d '{
  "roaming_rule": {
    "name": "Data Only - T-Mobile",
    "mcc": "310",
    "mnc": "260",
    "data_action": "allow",
    "ims_action": "deny"
  }
}'
```

Block Specific Networks (Blacklist)


```
# Create expensive network blocking rule
RULE=$(curl -k -X POST
https://hss.example.com:8443/api/roaming/rule \
-H "Content-Type: application/json" \
-d '{
  "roaming_rule": {
    "name": "Block Expensive Network",
    "mcc": "206",
    "mnc": "01",
    "data_action": "deny",
    "ims_action": "deny"
  }
}' | jq -r '.response.id')

# Create profile with allow-by-default
curl -k -X POST https://hss.example.com:8443/api/roaming/profile \
-H "Content-Type: application/json" \
-d "{
  \"roaming_profile\": {
    \"name\": \"Block Expensive Networks\",
    \"data_action_if_no_rules_match\": \"allow\",
    \"ims_action_if_no_rules_match\": \"allow\",
    \"roaming_rules\": [$RULE]
  }
}"
```

Common Roaming Scenarios

Scenario 1: Domestic Roaming Only

Subscriber can roam within home country but not internationally.




Configuration:

- Default: Deny all
- Rules: Allow all USA MCC codes (310, 311, 312, 313, 314, 315, 316)

Scenario 2: Roaming Partners Only

Subscriber can only roam on networks with commercial agreements.




Configuration:

- Default: Deny all
- Rules: Allow each partner network explicitly (by MCC/MNC)

Scenario 3: Data Roaming, No Voice Roaming

Subscriber can use data abroad but must use WiFi for voice calls.



Configuration:

- Rules: `data_action: "allow"`, `ims_action: "deny"`

Scenario 4: Emergency Service Access

Always allow emergency services, even if roaming is blocked.

Note: Emergency service handling is typically done at the MME/network level. OmniHSS roaming rules apply to normal services.

MCC/MNC Reference

Common Country Codes (MCC)

MCC	Country	Networks
310-316	USA	AT&T, Verizon, T-Mobile, etc.
302	Canada	Rogers, Bell, Telus
234-235	United Kingdom	Vodafone, O2, EE
262	Germany	Deutsche Telekom, Vodafone
208	France	Orange, SFR, Bouygues
222	Italy	TIM, Vodafone, Wind
214	Spain	Movistar, Vodafone

Common US Carriers (MCC 310-316)


MCC	MNC	Carrier
310	410	AT&T
311	480	Verizon
310	260	T-Mobile
310	120	Sprint
313	380	(Example test network)

Full Lists: See [ITU-T E.212](#) or [MCC/MNC databases](#)

Roaming Enforcement Points


S6a Interface (Data)

When subscriber attaches to visited network:



Cx Interface (IMS)

When subscriber registers to IMS in visited network:



Troubleshooting Roaming Issues

Subscriber Cannot Attach in Visited Network

Check roaming profile assignment:

- Query the database to view subscriber's assigned roaming profile

- Verify the profile name and default action settings

Check if rule exists for visited network:

- Query the database for roaming rules matching the visited network's MCC/MNC
- Verify if a rule exists for the subscriber's roaming profile
- Check the data_action value for that specific network

Subscriber Can Attach But Not Register IMS

Check IMS action separately:

- Query the roaming rules for the visited network
- Verify both data_action and ims_action values
- Look for cases where data is allowed but IMS is denied

Unexpected Roaming Behavior

Review logs for roaming checks:

```
[info] Roaming check: IMSI 001001123456789, Visited PLMN 310-410  
[info] Roaming rule matched: "Allow AT&T"  
[info] Data action: allow, IMS action: allow
```

Best Practices

Profile Design

1. **Start restrictive** - Default deny, explicitly allow partners
2. **Test thoroughly** - Verify rules in lab before production
3. **Document rules** - Maintain list of allowed networks and why
4. **Review regularly** - Update as roaming agreements change

Rule Management

1. **Use descriptive names** - "Allow-ATT-Data-Only" not "Rule1"
2. **Verify MCC/MNC** - Double-check codes against official databases
3. **Consider both services** - Think about data and IMS separately
4. **Monitor usage** - Track which networks subscribers actually visit

Operational Procedures

1. **Emergency Changes** - Have procedure to quickly enable/disable roaming
2. **Bulk Updates** - Plan for updating multiple subscribers' roaming profiles
3. **Reporting** - Track roaming usage and denied attempts
4. **Customer Communication** - Notify customers of roaming policy changes

[← Back to Operations Guide](#) | [Next: Protocol Flows →](#)

Sh RepositoryData (Transparent Data)

OmniHSS acts as a **transparent repository** for service data that Application Servers (AS) store against a subscriber over the [Sh interface](#). Documents such as **MMTEL-Services** (supplementary services / call diversion, call waiting, OIP/OIR, barring) and **IMS-ODB-Information** (operator-determined barring) are written by the AS, kept by the HSS, and read back on demand.

"Transparent" has a precise meaning in [3GPP TS 29.328](#): the HSS understands this data **syntactically but not semantically**. It is opaque XML owned by the AS. OmniHSS stores and returns the `ServiceData` payload **byte-for-byte**. It never re-parses or re-serialises the payload. A document that an AS etags or checksums (for example XCAP/MMTel) is returned exactly as written.

The same documents can also be managed out-of-band by provisioning/CRM systems through the [REST Provisioning API](#).

Table of Contents


- [Concepts](#)
- [Data Model](#)
- [Sh Message Flows](#)
- [SequenceNumber and Concurrency](#)
- [REST Provisioning API](#)
- [Reference Tables](#)
- [Troubleshooting](#)

Concepts

A subscriber may hold any number of independent **transparent documents**, each identified by a **Service-Indication** (the "filename"). A document has three parts:

Element	Owner	Meaning
Service-Indication	HSS-managed	Names the document (e.g. <code>MMTEL-Services</code> , <code>IMS-ODB-Information</code>).
SequenceNumber	HSS-managed	Version counter used for optimistic concurrency. See SequenceNumber and Concurrency .
ServiceData	AS-owned (opaque)	The XML payload itself. Stored and returned verbatim.

The HSS only interprets Service-Indication and SequenceNumber. The `ServiceData` body is treated as opaque bytes.



Data Model

All of a subscriber's transparent documents are held in a single field, `subscriber_state.sh_repository_data`, as a JSON object keyed by Service-Indication. Each entry stores the version and the verbatim payload:

```
{
  "MMTEL-Services": { "sequence_number": "0", "service_data":
    "<MMTelServices ...>...</MMTelServices>" },
  "IMS-ODB-Information": { "sequence_number": "1", "service_data":
    "<OdbForImsOrientedServices xmlns=\"odb.mmtel.omnitou.ch\"/>" }
}
```

Field	Description
<code>sequence_number</code>	The current version of this document, as last accepted by the HSS. Returned in every <code>UDA</code> and used to validate updates.
<code>service_data</code>	The opaque XML body, stored exactly as the AS sent it (no namespace, attribute-order or whitespace normalisation). A document with no <code>ServiceData</code> element (the spec's <i>empty repository data</i>) omits this field.


This model means a single subscriber can hold many distinct documents, each versioned independently, with no fixed schema imposed by the HSS.

Sh Message Flows

RepositoryData is carried in the `User-Data` AVP as a `Sh-Data` XML document. RepositoryData is selected with **Data-Reference value 0**. An optional **Service-Indication** AVP narrows a request to a single document.

User Data Request (UDR/UDA): Read


The AS reads one or all transparent documents. With a Service-Indication, only the matching document is returned; without one, every stored document is returned, each as its own `<RepositoryData>` element.



An unknown or non-IMS subscriber is answered with **Experimental-Result 5001 (DIAMETER_ERROR_USER_UNKNOWN)**.

Profile Update Request (PUR/PUA): Write


The AS creates or updates a single document. The `ServiceData` payload is stored verbatim. The update is accepted only if its SequenceNumber is valid (see below).



When a PUR resolves to multiple subscribers (a wildcarded Public Identity), the update is applied atomically: if any document is out of sync, none are persisted.

Subscribe Notifications Request (SNR/SNA): Subscribe

The AS subscribes to a subscriber's data and may request the current value be returned immediately (`Send-Data-Indication`). OmniHSS answers the SNR and, when requested, includes the current RepositoryData.



SequenceNumber and Concurrency

The SequenceNumber provides optimistic concurrency control so two Application Servers cannot silently overwrite each other, per [3GPP TS 29.328](#).

- **Creating** a new document uses **SequenceNumber 0** (value `0` is reserved exclusively for newly-added data).
- **Updating** an existing document must carry the **immediate successor** of the stored SequenceNumber (stored + 1).
- The counter **wraps from 65535 back to 1** (not 0, since 0 is reserved).
- An update whose SequenceNumber is not the expected successor is rejected with **Experimental-Result 5105 (DIAMETER_ERROR_TRANSPARENT_DATA_OUT_OF_SYNC)** and the stored document is left unchanged.



Absent

PUR SequenceNumber
0 (create)

Stored0

PUR SequenceNumber
1 (stored+1) DELETE (REST)

Stored1

PUR SequenceNumber
n+1

StoredN

PUR with wrong
SequenceNumber
→ 5105, no change

Example: a document is stored at SequenceNumber 0. A PUR carrying SequenceNumber 5 is rejected with 5105 and nothing changes. A PUR carrying SequenceNumber 1 is accepted and the document advances to version 1.

REST Provisioning API

The same documents can be read and written directly by provisioning/CRM systems. The subscriber is addressed by IMSI in the path; the document is identified by `service_indication` (in the request body for updates, or the

query string for reads/deletes). The opaque `service_data` is round-tripped byte-for-byte, exactly as over Sh.

All responses use the standard API envelope:

```
{ "status": "success", "response": { } }
```

Unlike the Sh path, the REST API is authoritative provisioning access and does **not** apply the SequenceNumber out-of-sync check. A write sets the document directly.

List All Documents

Returns every stored document for the subscriber.

Endpoint: `GET /api/subscriber/repository_data/:imsi`

```
curl -k  
https://hss.example.com:8443/api/subscriber/repository_data/001001123
```

```
{  
  "status": "success",  
  "response": {  
    "MMTEL-Services": { "sequence_number": "0",  
"service_data": "<MMTelServices .../>" },  
    "IMS-ODB-Information": { "sequence_number": "1",  
"service_data": "<OdbForImsOrientedServices  
xmlns=\"odb.mmtel.omnitou.ch\"/>" }  
  }  
}
```

Get a Single Document

Returns one document by Service-Indication.

Endpoint: `GET /api/subscriber/repository_data/:imsi?
service_indication=:service_indication`

```
curl -k
"https://hss.example.com:8443/api/subscriber/repository_data/001001123
service_indication=MMTEL-Services"
```

```
{
  "status": "success",
  "response": { "sequence_number": "0", "service_data": "
<MMTelServices .../>" }
}
```

Create or Update a Document

Creates the document if absent, or overwrites it.

Endpoint: PUT /api/subscriber/repository_data/:imsi

```
curl -k -X PUT
https://hss.example.com:8443/api/subscriber/repository_data/001001123
\
-H "Content-Type: application/json" \
-d '{
  "service_indication": "MMTEL-Services",
  "service_data": "<MMTelServices version=\"1\"/>",
  "sequence_number": "0"
}'
```

Field	Type	Required	Default	Description
<code>service_indication</code>	String	Yes	-	The document name to create/update (e.g. <code>MMTEL-Services</code>).
<code>service_data</code>	String	No	-	The opaque XML payload, stored verbatim. Omit to store an empty document (Service-Indication and SequenceNumber only).
<code>sequence_number</code>	String	No	<code>0</code>	The version to record for the document.

The response echoes the stored document:

```
{
  "status": "success",
  "response": { "sequence_number": "0", "service_data": "<MMTelServices version=\"1\"/>" }
}
```

Delete a Document

Removes a single document by Service-Indication.

Endpoint: `DELETE /api/subscriber/repository_data/:imsi`

```
curl -k -X DELETE
https://hss.example.com:8443/api/subscriber/repository_data/001001123
\
-H "Content-Type: application/json" \
-d '{ "service_indication": "MMTEL-Services" }'
```

Field	Type	Required	Default	Description
<code>service_indication</code>	String	Yes	-	The document to remove.

The response returns the remaining documents for the subscriber.

Reference Tables

Data-Reference Values (RepositoryData)

Value	Name	Description	Reference
0	RepositoryData	Transparent service data identified by Service-Indication	3GPP TS 29.328 §7.6

Result and Experimental-Result Codes

Code	Name	Meaning
2001	DIAMETER_SUCCESS	UDR/PUR/SI processed successfully
5001	DIAMETER_ERROR_USER_UNKNOWN	Subscriber not found or not enabled
5105	DIAMETER_ERROR_TRANSPARENT_DATA_OUT_OF_SYNC	Update SequenceN is not the successor of stored value

Application ID

ID	Interface	Description	Reference
16777217	Sh	AS ↔ HSS user data	3GPP TS 29.329

Common Service-Indications

Service-Indication	Typical Content
MMTEL - Services	MMTel supplementary services (call diversion, communication waiting/hold/barring, OIP/OIR, conferencing): simservs XML
IMS - ODB - Information	Operator-determined barring information for IMS-oriented services

Service-Indication values are defined by the Application Server and its corresponding XML schema; the HSS imposes no fixed list.

Troubleshooting

Application Server receives 5105 on update

Symptoms: A PUR is answered with Experimental-Result 5105 and the document is unchanged.

Possible causes:

- The AS sent a SequenceNumber that is not the immediate successor of the value stored at the HSS (its cached copy is stale).
- A concurrent update from another AS advanced the SequenceNumber.

Resolution:

1. Read the current document with a UDR to obtain the up-to-date SequenceNumber.
2. Re-issue the PUR with SequenceNumber = stored + 1.
3. To force a value administratively, set it via the **REST API**, which does not apply the concurrency check.

Returned ServiceData differs from what was written

Symptoms: The AS believes the payload was altered by the HSS.

Possible causes:

- This should not occur. OmniHSS stores and returns `ServiceData` byte-for-byte. Apparent differences usually come from the AS's own XML library re-serialising the document (changing namespace prefixes, attribute order or whitespace) before comparison.

Resolution:

1. Compare the raw bytes returned in the `UDA/REST` response against the raw bytes sent, not a re-parsed representation.
2. Confirm the AS is not normalising the XML on its side before the comparison.

Document not found via REST

Symptoms: `GET .../repository_data/:imsi?service_indication=...` returns an error.

Possible causes:

- No document with that Service-Indication is stored for the subscriber.
- The IMSI does not correspond to an existing subscriber.

Resolution:

1. List all documents with `GET /api/subscriber/repository_data/:imsi` to see what is stored.
2. Verify the IMSI with [Get Subscriber by IMSI](#).

SRVCC - Single Radio Voice Call Continuity

[← Back to Operations Guide](#)

Overview

SRVCC (Single Radio Voice Call Continuity) lets a UE hand an active VoLTE call over to a 2G/3G CS (Circuit-Switched) bearer when LTE coverage fails. The MME orchestrates the transfer over the **Sv interface** (TS 29.280). To build the Sv PS-to-CS Request, the MME needs two values sourced from the HSS:

AVP	Code	Purpose
STN-SR	1433	Session Transfer Number for SRVCC. The MSC-Server dials this E.164 number to reach the TAS/S-CSCF, which executes a SIP REFER to move the active VoLTE session to the CS bearer.
C-MSISDN	1452	Correlation MSISDN. The TAS uses this to match the incoming STN-SR call to the correct active session when the subscriber has multiple calls in flight.


OmniHSS delivers **STN-SR** in the S6a **Update Location Answer** (ULA) **Subscription-Data** AVP. The MME reads it from the ULA and forwards it in the Sv PS-to-CS Request.

Reference specifications:

Specification	Title
TS 23.216	SRVCC PS-to-CS procedure
TS 29.272	S6a interface (STN-SR §7.3.89, Subscription-Data §7.3.2)
TS 23.003	STN-SR number format (§13.4)

How It Works

OmniHSS uses a prefix-based approach. You configure a single operator-wide STN-SR prefix. The HSS computes the full STN-SR number at ULA time by concatenating the prefix with the subscriber's MSISDN. The result is TBCD-encoded and placed in the **STN-SR** AVP inside **Subscription-Data**.



This approach requires no per-subscriber provisioning. All subscribers on the HSS receive the same prefix, so a single config change enables SRVCC for the entire subscriber base.

If the prefix is not configured, OmniHSS omits the **STN-SR** AVP entirely. The ULA is otherwise unaffected. Non-SRVCC deployments see no change in behavior.

Configuration

Add the `srvcc` key to the `:hss` application config in `config/runtime.exs`.

```
config :hss, :srvcc,  
  stn_sr_prefix: "9"
```

Parameters

Parameter	Type	Required	Default	Description
<code>stn_sr_prefix</code>	String	No	(none)	Operator-assigned STN-SR prefix prepended to each subscriber's MSISDN to form the full E.164 STN-SR number. When not set, OmniHSS omits the <code>STN-SR</code> AVP from all ULA responses.

STN-SR Number Format

The full STN-SR number is:

```
STN-SR = stn_sr_prefix + subscriber MSISDN
```

The number is encoded as **TBCD** (Telephony Binary Coded Decimal, per [TS 24.008 §10.5.4.7](#)) and placed in the `STN-SR` AVP (code 1433, vendor 10415).

Example:

Input	Value
Configured prefix	9
Subscriber MSISDN	61412345678
Computed STN-SR	961412345678

The MSC-Server dials 961412345678. The call arrives at the TAS, which uses the MSISDN portion to locate the active IMS session and issues the SIP REFER to transfer it to the CS bearer.

Configuration Example

SRVCC Enabled

```
# config/runtime.exs

config :hss, :srvcc,
  # Prefix dialled by the MSC-Server to reach the TAS over
  PSTN/CS.
  # STN-SR = stn_sr_prefix + subscriber MSISDN.
  stn_sr_prefix: "9"
```


How it works: Every ULA response includes STN-SR in Subscription-Data. The value is the TBCD encoding of the prefix concatenated with the subscriber's MSISDN. The MME stores the value and forwards it in Sv PS-to-CS Requests when SRVCC is triggered.

SRVCC Disabled (default)

When the `srvcc` key is absent or `stn_sr_prefix` is not set, OmniHSS omits the STN-SR AVP. The ULA is otherwise identical. Use this for deployments that do not require SRVCC.

Interaction with the MME

The MME (OmniMME) reads `STN-SR` from the ULA `Subscription-Data` and stores it in the subscriber context. When SRVCC is triggered, it includes `STN-SR` in the Sv **PS-to-CS Request** sent to the MSC-Server. See [Omnitouch/omnimme#426](#) for the MME implementation.



Troubleshooting

STN-SR Not Present in ULA

Symptoms: The MME cannot populate the Sv PS-to-CS Request. SRVCC handovers fail.

Possible causes:

- `stn_sr_prefix` is not set in `config/runtime.exs`.
- The HSS service started before the config change took effect.

Resolution:

1. Verify the `srvcc` block is present in `config/runtime.exs` with a non-empty `stn_sr_prefix`.
2. Restart the OmniHSS service to apply the configuration change.
3. Trigger a new ULR from the MME (for example by forcing a TAU). Confirm the ULA `Subscription-Data` now contains `STN-SR`.

Incorrect STN-SR Value

Symptoms: The MSC-Server receives a malformed or unroutable number.

Possible causes:

- The prefix is incorrect or missing leading digits.
- The subscriber MSISDN stored in the HSS is not in international E.164 format (digits only, no +).

Resolution:

1. Check the subscriber's MSISDN via the API (GET `/api/subscriber/imsi/:imsi`).
 2. Verify the expected STN-SR: concatenate `stn_sr_prefix` with the stored MSISDN.
 3. Confirm the MSC-Server's routing table handles that number range.
-

[← Back to Operations Guide](#)

Sy Interface (Spending Limit Control)

Overview

The Sy interface connects the HSS (acting as the **PCRF**, Policy and Charging Rules Function) to an external **OCS** (Online Charging System) for **subscriber spending limit control**. It lets the PCRF base its policy decisions - for example which charging rule to apply, or whether to throttle a subscriber - on the status of **policy counters** that the OCS maintains for each subscriber (data allowance consumed, spend against a monthly cap, and so on).

The OmniHSS PCRF installs charging rules and QoS over **Gx** and authorizes IMS media over **Rx**. Over Sy it subscribes to the status of a subscriber's policy counters at the OCS and is notified when they change, so those Gx decisions can account for the subscriber's current spend and quota.


Sy is defined by **3GPP TS 29.219** and uses Diameter application ID **16777302**.

Property	Value
Application ID	16777302
Specification	3GPP TS 29.219
HSS role	PCRF (Diameter client for SLR/STR, server for SNR)
Peer	OCS (Online Charging System)
Transport	TCP or SCTP, port 3868

Sy vs Gy. Sy is not online charging. Gy (**TS 32.299**) is where the PGW asks the OCS to grant credit for live traffic. Sy is a separate, lightweight interface where the **PCRF** subscribes to the **status** of the OCS's policy

counters and is notified when they change, so it can adjust policy. The OCS is the server on both.

Architecture



The HSS is the **Sy client**: it opens an Sy session to the OCS when it first needs spend status for a subscriber, and tears it down when the subscriber's last data session ends. The OCS is the **Sy server**: it answers status requests and, whenever a counter's status changes, notifies the PCRF so it can re-apply policy over Gx.

Policy Counters and Charging Rules

The OCS maintains one or more **policy counters** per subscriber. Each counter has:

- a **Policy-Counter-Identifier** (AVP 2901) - a stable name for the counter, and
- a **Policy-Counter-Status** (AVP 2902) - a label describing where the counter currently sits (for example `active`, `over_quota`, `throttled`). The set of status values is not defined by 3GPP; it is configured jointly by the operator on both the OCS and the PCRF ([TS 29.219 §3.1](#)).

OmniHSS binds these to the [charging rules](#) already in its database:

Sy AVP	Nature	Maps to	Role
<code>Policy-Counter-Identifier</code> (2901)	Static - names the counter	A Charging Rule name in the HSS database	Selects <i>which</i> charging rule the counter governs
<code>Policy-Counter-Status</code> (2902)	Dynamic - changes at thresholds	An enforcement action	Decides <i>what to do</i> with that rule now: install, remove, or select a tier

The identifier is stable for the life of the counter, so on its own it cannot express "under quota" versus "over quota". The **status** is the value that changes when the subscriber crosses a threshold, so it drives the action:


- the fixed status `enforced` installs the named charging rule (`Charging-Rule-Install` over Gx);
- any other status removes it (`Charging-Rule-Remove`).

Sy carries no charging rules of its own. Sy has no Charging-Rule, QoS or Flow AVPs - those exist only on Gx. The OCS therefore cannot hand the PCRF a rule definition; it can only *name* the rule (via the counter identifier) and signal *when* to apply it (via the status). The rule definition itself is provisioned in the HSS. This is why `Policy-Counter-Identifier` must match a charging rule name, and the OCS must emit those exact names with the status `enforced` when the rule is to be applied.



Sy Session Lifecycle

An Sy session is **per subscriber**, not per data bearer. The PCRF keeps one Sy session (identified by a single Diameter `Session-Id`) for a subscriber for as long as any of that subscriber's data sessions depends on spend status (TS 29.219 §4.4.1).



- **Establish (SLR, INITIAL_REQUEST).** On the first Gx CCR-I where the subscriber's policy depends on spend status, the PCRF opens the Sy session and requests the relevant policy counters. The OCS answers with the current status of each in the SLA.
- **Update (SLR, INTERMEDIATE_REQUEST).** If the PCRF later needs additional counters, it re-uses the same Sy session with an intermediate request.
- **Notify (SNR / SNA).** When a counter's status changes, the OCS sends a Spending-Status-Notification-Request. The PCRF acknowledges with an SNA and applies the change over Gx.
- **Terminate (STR / STA).** When the subscriber's last data session ends, the PCRF closes the Sy session with a Session-Termination-Request.

Message Flows

Flow 1: Initial Spending Limit Report at PDN Setup

Parse error on line 14: ...all/remove by status PCRF-->>PGW: Gx -----
-----^ Expecting 'SOLID_OPEN_ARROW', 'DOTTED_OPEN_ARROW',
'SOLID_ARROW', 'BIDIRECTIONAL_SOLID_ARROW', 'DOTTED_ARROW',
'BIDIRECTIONAL_DOTTED_ARROW', 'SOLID_CROSS', 'DOTTED_CROSS',
'SOLID_POINT', 'DOTTED_POINT', got 'NEWLINE'

Try again

The PCRF folds the spend-derived rules into the **same CCA-I** it already builds for the Gx session. If the OCS does not answer in time, the PCRF falls back to the APN's default policy so a Sy outage never blocks attach.


Flow 2: Spending Status Change (OCS -> PCRF -> Gx RAR)

Parse error on line 11: ... rule by identifier;
new status -> i -----
----^ Expecting 'SPACE', 'NEWLINE', 'create', 'box', 'end', 'autonumber',
'activate', 'deactivate', 'title', 'legacy_title', 'acc_title', 'acc_descr',
'acc_descr_multiline_value', 'loop', 'rect', 'opt', 'alt', 'par', 'par_over', 'critical',
'break', 'option', 'and', 'else', 'participant', 'participant_actor', 'destroy', 'note',
'links', 'link', 'properties', 'details', 'ACTOR', got 'INVALID'

Try again

This re-uses the PCRF's existing **Gx Re-Auth** machinery - the same path that installs VoLTE dedicated bearers - to push the spend-driven policy change to the PGW without waiting for the next CCR.

Flow 3: Sy Session Termination



Configuration

Sy Application

The Sy application is registered on the HSS Diameter service alongside Gx and Rx (`config/runtime.exs`):

```
%{
  application_name: :sy,
  application_dictionary: :diameter_gen_3gpp_sy,
  vendor_specific_application_ids: [
    %{vendor_id: 10415, auth_application_id: 16_777_302,
    acct_application_id: nil}
  ]
}
```

Parameter	Type	Required	Default	
<code>application_name</code>	Atom	Yes	-	Inter inter for tl
<code>application_dictionary</code>	Atom	Yes	-	Dian mod :dia (3GP
<code>vendor_specific_application_ids</code>	List	Yes	-	Adve appl capa See
<code>vendor_id</code>	Integer	Yes	-	Venc 3GPI
<code>auth_application_id</code>	Integer	Yes	-	Auth appl 16_7
<code>acct_application_id</code>	Integer nil	No	<code>nil</code>	Acco ID. N to n:

Sy Settings

Sy behaviour is configured under the `:hss, :sy` key (`config/runtime.exs`):

```
config :hss,  
  sy: %{  
    enabled: false  
  }
```

Parameter	Type	Required	Default	Description
<code>enabled</code>	Boolean	No	<code>false</code>	Master switch. When <code>true</code> , the PCRF opens a per-subscriber Sy session on Gx CCR-I. When <code>false</code> , Sy is completely bypassed.

The `Policy-Counter-Status` value that installs the named charging rule is the fixed convention **enforced**; any other value removes the rule. This is agreed with the OCS and is not configurable.

OCS Routing

The HSS does **not** pin an OCS host or realm. Originated SLR and STR carry the HSS's **own** `Destination-Realm` and no `Destination-Host`, and are routed by realm plus the Sy Application-Id (16777302). Whichever peer advertises the Sy application in that realm receives the request - typically the **DRA**, which forwards to an available OCS. This works identically whether the OCS is reached through the DRA or peered directly, and it lets the routing layer pick among multiple OCSs.

The only requirement is that a peer advertising the Sy application exists in the realm. In a DRA deployment that is the DRA peer already configured for the HSS; no Sy-specific peer entry is needed.

Policy Counter Mapping

For the identifier-to-rule binding to work, the operator configures **both** ends consistently:

- On the **OCS**: each policy counter's `Policy-Counter-Identifier` is set to the exact `name` of a **Charging Rule** defined in the HSS, and the counter reports the status `enforced` when that rule should be applied.
- On the **HSS**: the referenced charging rules exist in the database.

See [Policy Counters and Charging Rules](#) for the mapping model.

Metrics

Sy exposes Prometheus metrics alongside the other HSS interface metrics (see [Metrics & Monitoring](#)).

Metric: `hss_sy_messages_total` **Type:** Counter **Description:** Sy messages processed, by command, direction and result. **Labels:**

- `command` - `slr`, `sla`, `snr`, `sna`, `str`, or `sta`
- `direction` - `incoming` (received from the OCS) or `outgoing` (sent to the OCS)
- `result` - `sent`, `received`, `success`, or `error`

Metric: `hss_sy_policy_updates_total` **Type:** Counter **Description:** Gx charging-rule changes driven by a Sy policy counter status, by action and result. **Labels:**

- `action` - `install` or `remove`
- `result` - `success` or `error` (the outcome of the Gx RAR to the PGW)

Example queries:

```
# Sy notification rate from the OCS
rate(hss_sy_messages_total{command="snr", direction="incoming"}
[5m])

# Rate of throttle/enforcement rule installs driven by spending
limits
rate(hss_sy_policy_updates_total{action="install",
result="success"}[5m])

# Sy Gx RAR failure ratio
sum(rate(hss_sy_policy_updates_total{result="error"}[5m]))
/ sum(rate(hss_sy_policy_updates_total[5m]))
```


Reference

Commands

Command	Abbreviation	Code	Direction	Purpose
Spending-Limit-Request	SLR	8388635	PCRF -> OCS	Request policy counter status; subscribe to changes
Spending-Limit-Answer	SLA	8388635	OCS -> PCRF	Return current counter status
Spending-Status-Notification-Request	SNR	8388636	OCS -> PCRF	Notify a counter status change
Spending-Status-Notification-Answer	SNA	8388636	PCRF -> OCS	Acknowledge a notification
Session-Termination-Request	STR	275	PCRF -> OCS	Close the Sy session (final report)
Session-Termination-Answer	STA	275	OCS -> PCRF	Confirm session closure

All commands carry Application-ID `16777302`, including the re-used STR/STA ([RFC 6733](#) session termination).

Key AVPs

AVP	Code	Type	Description
Policy-Counter-Identifier	2901	UTF8String	Names a policy counter. Bound to a Charging Rule name in OmniHSS.
Policy-Counter-Status	2902	UTF8String	Operator-defined status label for the counter. Drives the enforcement action.
Policy-Counter-Status-Report	2903	Grouped	One counter's identifier + status (+ any pending statuses).
SL-Request-Type	2904	Enumerated	INITIAL_REQUEST (0) for the first request, INTERMEDIATE_REQUEST (1) thereafter.
Pending-Policy-Counter-Information	2905	Grouped	A future status and the time it becomes current.
Pending-Policy-Counter-Change-Time	2906	Time	When a pending status takes effect.
SN-Request-Type	2907	Unsigned32	Bitmask on an SNR. Bit 0 = normal report, bit 1 = abort (OCS asks to end the Sy session).
Subscription-Id	443	Grouped	Subscriber identity (IMSI and/or MSISDN) on the SLR.

Result Codes

Code	Name	Meaning
2001	DIAMETER_SUCCESS	Request processed successfully
5030	DIAMETER_USER_UNKNOWN	OCS does not know the subscriber; the Sy session is not created
5570	DIAMETER_ERROR_UNKNOWN_POLICY_COUNTERS	One or more requested policy counters are unknown to the OCS
4241	DIAMETER_ERROR_NO_AVAILABLE_POLICY_COUNTERS	The OCS has no policy counters for the subscriber

Codes 5570 and 4241 are Sy-specific Experimental-Result-Code values ([TS 29.219 §5.5](#)); 5030 is defined by [RFC 4006](#).

Related Documentation

- [PCRF](#) - Gx and Rx policy control that Sy feeds into
- [Diameter Protocols](#) - Message flows across all HSS interfaces
- [Architecture](#) - Overall HSS architecture

OmniHSS

Troubleshooting Guide


[← Back to Operations Guide](#)

Table of Contents

- [Troubleshooting Overview](#)
 - [Authentication Failures](#)
 - [Diameter Connectivity Issues](#)
 - [Database Issues](#)
 - [EPC Registration Failures](#)
 - [IMS Registration Failures](#)
 - [VoLTE Call Failures](#)
 - [Roaming Issues](#)
 - [EIR Problems](#)
 - [Performance Problems](#)
 - [Subscriber State Issues](#)
 - [API Issues](#)
 - [Diagnostic Tools and Commands](#)
-

Troubleshooting Overview

General Troubleshooting Approach



Information to Gather

Before troubleshooting any issue, collect:

1. **Subscriber Information** (if subscriber-specific)

- IMSI
- MSISDN (phone number)
- Last known state
- Error messages from device

2. **Timing Information**

- When did the issue start?
- Is it intermittent or constant?
- Time of last successful operation

3. **Scope of Impact**

- Single subscriber or multiple?
- Specific network or all networks?
- Specific service (data/voice) or both?

4. **System State**

- Check **Control Panel** for system status
 - Review Diameter peer status
 - Verify database connectivity
-

Authentication Failures

Symptoms

- Subscriber cannot attach to network
- "Authentication rejected" errors
- Repeated authentication attempts

Common Causes and Solutions

Cause 1: Incorrect Key Set

Symptoms:

- Consistent authentication failure for specific subscriber
- Works for other subscribers with same profile

Diagnostic Steps:

1. Query subscriber to verify key_set_id:

```
curl -k https://hss.example.com:8443/api/subscriber/imsi/[IMSI]
```

2. Verify key set exists and has correct values:

```
curl -k https://hss.example.com:8443/api/key_set/[KEY_SET_ID]
```

3. Compare Ki and OPC values with SIM card documentation

Solution:

- Update subscriber with correct **key set**
- If keys are correct, SIM card may be faulty

Cause 2: SQN Out of Sync

Symptoms:

- Authentication fails after previously working
- Error: "SQN synchronization failure"
- Works intermittently

Diagnostic Steps:

1. Check subscriber state for SQN value in database
2. Look for SQN-related errors in logs

3. Verify subscriber's key set SQN value

Solution:

- SQN will automatically resynchronize after subscriber sends AUTS
- If persistent, reset SQN to 0 in key set (requires subscriber re-attach)

Warning: Resetting SQN can cause security issues. Only do during maintenance.

Cause 3: Subscriber Disabled

Symptoms:

- Authentication rejected immediately
- No authentication vectors generated

Diagnostic Steps:

1. Check subscriber enabled status:

```
curl -k https://hss.example.com:8443/api/subscriber/imsi/[IMSI]
```

2. Verify `enabled` field is `true`

Solution:

- **Enable subscriber:**

```
curl -k -X PUT https://hss.example.com:8443/api/subscriber/[ID] \
-H "Content-Type: application/json" \
-d '{"subscriber": {"enabled": true}}'
```

Cause 4: Missing EPC Profile

Symptoms:

- Subscriber lookup succeeds but authentication fails
- Error: "No EPC profile assigned"

Diagnostic Steps:


1. Check subscriber's `epc_profile_id` field
2. Verify EPC profile exists:

```
curl -k  
https://hss.example.com:8443/api/epc/profile/[PROFILE_ID]
```

Solution:

- Assign valid **EPC profile** to subscriber

Authentication Troubleshooting Flowchart



Diameter Connectivity Issues

Symptoms

- Diameter peers showing as disconnected in [Control Panel](#)
- "No route to host" errors
- Services failing for all subscribers

Common Causes and Solutions

Cause 1: Network Connectivity

Symptoms:

- Peer never connects
- Connection timeout errors
- Ping fails to peer

Diagnostic Steps:

1. Verify network connectivity from OmniHSS to peer:

```
ping [PEER_IP]
```

2. Check if Diameter port is reachable:

```
telnet [PEER_IP] 3868
```

3. Verify firewall rules allow Diameter traffic (port 3868)

Solution:

- Fix network routing
- Update firewall rules
- Verify peer is running and listening

Cause 2: Incorrect Diameter Configuration

Symptoms:

- Connection attempts fail
- CER/CEA exchange fails
- Peer rejects connection

Diagnostic Steps:

1. Review runtime.exs Diameter configuration:
 - Verify peer origin_host matches peer's expected value
 - Check origin_realm configuration
 - Verify peer IP address is correct
2. Check logs for CER/CEA errors
3. Verify peer's configuration expects OmniHSS's origin_host

Solution:

- Update runtime.exs with correct **Diameter configuration**
- Restart OmniHSS after configuration change
- Coordinate with peer administrator to verify settings

Cause 3: Certificate Issues (TLS Diameter)

Symptoms:

- Connection fails during TLS handshake
- Certificate validation errors
- "Certificate expired" or "Certificate invalid" errors

Diagnostic Steps:

1. Verify certificate files exist in `priv/cert/`
2. Check certificate expiration:

```
openssl x509 -in priv/cert/diameter.crt -noout -dates
```

3. Verify certificate chain is complete
4. Check peer's certificate if mutual TLS

Solution:

- Renew expired certificates
- Install correct certificate chain
- Update certificate files and restart OmniHSS

Cause 4: Peer Application Support Mismatch**Symptoms:**

- Peer connects but does not support required applications
- Capabilities exchange succeeds but operations fail
- "Application not supported" errors


Diagnostic Steps:

1. Check [Control Panel Diameter page](#) for peer applications
2. Verify peer supports required application (S6a, Cx, Sh, etc.)
3. Review CER/CEA exchange in logs

Solution:

- Verify peer configuration includes required Diameter applications
- Check that peer type matches expected functionality:
 - MME must support S6a (16777251)
 - S-CSCF must support Cx (16777216)
 - P-GW must support Gx (16777238)

Diameter Troubleshooting Flowchart



Database Issues

Symptoms

- API returns 500 errors
- Control Panel fails to load
- "Database connection failed" errors
- Slow query performance

Common Causes and Solutions

Cause 1: Database Server Down

Symptoms:

- All API calls fail
- Control Panel shows error
- "Connection refused" errors

Diagnostic Steps:

1. Test database connectivity:

```
# Connect to the database  
psql -h [DB_HOST] -U [DB_USER] -d [DB_NAME]
```

2. Check database service status on database server
3. Verify network connectivity to database server

Solution:

- Start database service
- Fix database server issues
- Verify network routing to database server

Cause 2: Incorrect Database Credentials

Symptoms:

- "Authentication failed" errors
- OmniHSS cannot connect at startup

Diagnostic Steps:

1. Review database configuration in runtime.exs
2. Test credentials manually with database client
3. Check database user permissions

Solution:

- Update **database configuration** in runtime.exs
- Grant correct permissions to database user
- Restart OmniHSS after configuration change

Cause 3: Connection Pool Exhausted

Symptoms:

- Intermittent 500 errors
- "No available connections" errors
- High load periods trigger failures

Diagnostic Steps:

1. Check current connection count in database
2. Review database pool size in runtime.exs
3. Monitor connection usage during peak load

Solution:

- Increase pool size in runtime.exs configuration
- Investigate connection leaks if pool exhausts repeatedly
- Consider database scaling if load is consistently high

Cause 4: Slow Queries

Symptoms:

- API responses very slow
- Timeouts on subscriber lookups
- Database CPU high


Diagnostic Steps:

1. Query database for slow query log
2. Identify specific slow queries
3. Check for missing indexes
4. Verify subscriber count and table sizes

Solution:

- Optimize slow queries
- Add missing indexes
- Consider database performance tuning
- Plan for database scaling if needed

Database Troubleshooting Flowchart



EPC Registration Failures

Symptoms

- Subscriber cannot attach to LTE network
- MME rejects attachment
- No PDN session established

Common Causes and Solutions

Cause 1: Roaming Denied

Symptoms:

- Subscriber works on home network but fails when roaming
- "Roaming not allowed" errors
- Works for some networks but not others

Diagnostic Steps:

1. Check subscriber's roaming_profile_id
2. Query roaming profile and rules
3. Verify MCC/MNC of visited network
4. Check if roaming rule exists for that network

Solution:

- Add [roaming rule](#) for visited network MCC/MNC
- Or update roaming profile default action to allow
- See [Roaming Documentation](#) for configuration

Cause 2: Missing APN Configuration

Symptoms:

- Attachment succeeds but PDN session fails
- "Unknown APN" errors from MME
- Subscriber cannot get data connection

Diagnostic Steps:

1. Check EPC profile has APN profiles linked
2. Verify APN identifier matches what device requests
3. Query APN profile configuration

Solution:

- Link [APN profiles](#) to subscriber's EPC profile
- Ensure APN name matches device configuration
- Verify APN QoS profile exists

Cause 3: MME Not Connected

Symptoms:

- All subscribers fail to attach
- No communication with MME
- Diameter peer down

Diagnostic Steps:

1. Check [Control Panel Diameter page](#)
2. Verify MME peer status is "Connected"
3. Check MME supports S6a application

Solution:

- Troubleshoot [Diameter connectivity](#)
- Verify MME configuration
- Contact MME administrator

Cause 4: Subscriber State Corruption

Symptoms:

- Subscriber shows as attached but cannot attach again
- State does not match reality
- Detach and re-attach fails


Diagnostic Steps:

1. Query subscriber state from database
2. Check for stale MME assignments
3. Verify last update timestamp

Solution:

- Clear subscriber state (detach procedure)
- Reset serving MME in subscriber state
- May require subscriber power cycle

EPC Registration Troubleshooting Flowchart



IMS Registration Failures

Symptoms

- Subscriber cannot register for VoLTE
- "IMS registration failed" on device
- Data works but voice does not

Common Causes and Solutions

Cause 1: IMS Disabled for Subscriber

Symptoms:

- Subscriber has data but no IMS
- Registration rejected immediately

Diagnostic Steps:

1. Query subscriber and check `ims_enabled` field
2. Verify subscriber has `ims_profile_id` assigned

Solution:

- **Enable IMS** for subscriber
- Assign **IMS profile**

Cause 2: S-CSCF Not Connected

Symptoms:

- All IMS registrations fail
- No IMS-related Diameter traffic

Diagnostic Steps:

1. Check **Control Panel Diameter page**

2. Verify S-CSCF peer connected
3. Check S-CSCF supports Cx application

Solution:

- Fix **Diameter connectivity** to S-CSCF
- Verify S-CSCF configuration

Cause 3: Missing or Invalid IFC Template**Symptoms:**

- Registration fails during User-Authorization-Answer
- IFC-related errors in logs

Diagnostic Steps:

1. Query subscriber's IMS profile
2. Verify IFC template is present
3. Check IFC XML syntax

Solution:

- Update **IMS profile** with valid IFC template
- See **Profiles Documentation** for IFC examples

Cause 4: Roaming Denied for IMS**Symptoms:**

- IMS works on home network
- Fails when roaming
- Data roaming works but not IMS


Diagnostic Steps:

1. Check roaming profile IMS action
2. Verify roaming rules have correct `ims_action`

Solution:

- Update **roaming rules** to allow IMS
- Or update roaming profile default IMS action

IMS Registration Troubleshooting Flowchart



VoLTE Call Failures

Symptoms

- IMS registration succeeds but calls fail
- One-way audio
- Call drops immediately
- "Call failed" error on device

Common Causes and Solutions

Cause 1: P-CSCF Not Connected

Symptoms:

- Registration works but calls fail
- Media authorization fails

Diagnostic Steps:

1. Check [Control Panel Diameter page](#)
2. Verify P-CSCF peer connected
3. Check P-CSCF supports Rx application (OmniHSS PCRF function)

Solution:

- Fix [Diameter connectivity](#) to P-CSCF
- Verify P-CSCF configuration points to OmniHSS for Rx

Cause 2: Missing Media Authorization

Symptoms:

- Call setup starts but fails
- AAR/AAA exchange fails
- Rx interface errors

Diagnostic Steps:

1. Check logs for Rx Diameter messages
2. Verify AAR (AA-Request) received
3. Check AAA (AA-Answer) response

Solution:

- Verify P-CSCF is sending AAR for media authorization
- Check OmniHSS Rx application configuration
- Verify subscriber has active IMS registration

Cause 3: QoS/Bearer Issues**Symptoms:**

- Call connects but no audio
- One-way audio
- Quality issues


Diagnostic Steps:

1. Check APN QoS profile for voice APN
2. Verify QCI is set correctly (typically QCI 1 for voice)
3. Check P-GW is connected for Gx (PCRF function)

Solution:

- Verify **APN QoS profile** for IMS APN
- Ensure QCI 1 is configured for voice bearer
- Fix **Diameter connectivity** to P-GW if needed

VoLTE Call Troubleshooting Flowchart



Roaming Issues

Symptoms

- Subscriber works at home but not when roaming

- Some roaming networks work, others do not
- Roaming data works but not voice (or vice versa)

Common Causes and Solutions

Cause 1: No Roaming Profile Assigned

Symptoms:

- Roaming fails for subscriber
- Other subscribers roam successfully

Diagnostic Steps:

1. Query subscriber's `roaming_profile_id`
2. Check if field is null

Solution:

- Assign **roaming profile** to subscriber

Cause 2: Roaming Denied by Policy

Symptoms:

- Roaming fails consistently on specific network
- Error indicates policy rejection

Diagnostic Steps:

1. Identify visited network MCC/MNC from subscriber device or MME
2. Query subscriber's roaming profile
3. Check roaming rules for matching MCC/MNC
4. Check profile's default action

Solution:

- Add **roaming rule** to allow visited network:


```
curl -k -X POST https://hss.example.com:8443/api/roaming/rule \
-H "Content-Type: application/json" \
-d '{
  "roaming_rule": {
    "name": "Allow Visited Network",
    "mcc": "310",
    "mnc": "410",
    "data_action": "allow",
    "ims_action": "allow"
  }
}'
```

Cause 3: Data Allowed but IMS Denied

Symptoms:

- Data roaming works
- Voice/IMS roaming fails
- Split service availability

Diagnostic Steps:

1. Query roaming rules for visited network
2. Check `data_action` vs `ims_action` values
3. Verify roaming profile default actions

Solution:

- Update roaming rule to allow IMS:
 - Set `ims_action: "allow"`
- Or update profile's `ims_action_if_no_rules_match` to `"allow"`

See [Roaming Documentation](#) for detailed configuration.

EIR Problems

Symptoms

- Devices blocked unexpectedly
- Stolen devices not blocked
- EIR check failing

Common Causes and Solutions

Cause 1: Incorrect IMEI Regex

Symptoms:

- Wrong devices blocked/allowed
- Rule matches incorrectly

Diagnostic Steps:

1. Query EIR rules
2. Identify which rule is matching
3. Test regex pattern against actual IMEI
4. Check rule priority/order

Solution:

- Update **EIR rule** with correct regex
- Test regex thoroughly before applying
- Consider rule order (first match wins)

Cause 2: MME Not Sending S13 Requests

Symptoms:

- EIR check never happens
- All devices allowed regardless of rules

Diagnostic Steps:

1. Check if MME is configured to use S13 interface
2. Verify MME Diameter peer connected
3. Check for S13 application support
4. Review MME configuration

Solution:

- Configure MME to perform EIR checks via S13
- Verify Diameter peer supports S13 application (16777252)
- Contact MME administrator if needed

Cause 3: No Default Rule**Symptoms:**

- Devices not matching any rule have unexpected behavior

Diagnostic Steps:

1. Query all EIR rules
2. Check if catch-all rule exists
3. Verify rule ordering

Solution:

- Add default rule with regex `.*` to match all IMEIs
 - Set appropriate action (whitelist or blacklist)
 - Ensure specific rules are checked before catch-all
-

Performance Problems

Symptoms

- Slow API responses
- Diameter request timeouts
- High CPU or memory usage

- Control Panel slow to load

Common Causes and Solutions

Cause 1: High Database Load

Symptoms:

- All operations slow
- Database CPU high
- Query timeouts

Diagnostic Steps:

1. Check database server resource usage
2. Identify slow queries
3. Check for missing indexes
4. Monitor query patterns

Solution:

- Optimize slow queries
- Add database indexes
- Increase database resources
- Consider database scaling
- See [Database Issues](#)

Cause 2: High Subscriber Count

Symptoms:

- Performance degraded over time
- Slowness correlates with subscriber growth
- List operations especially slow

Diagnostic Steps:

1. Query total subscriber count

2. Check table sizes
3. Review query execution plans
4. Monitor resource usage trends

Solution:

- Plan capacity upgrade
- Optimize queries for large datasets
- Consider pagination for large results
- Implement caching if needed

Cause 3: Diameter Peer Issues**Symptoms:**

- Diameter operations slow
- Timeouts on specific peer
- Some peers fast, others slow

Diagnostic Steps:

1. Check [Control Panel Diameter page](#)
2. Identify slow peer
3. Test network latency to peer
4. Check peer resource usage

Solution:

- Investigate peer performance issues
- Check network path for congestion
- Consider adding redundant peers
- Increase Diameter timeout if needed

Cause 4: Memory Issues**Symptoms:**

- OmniHSS memory usage high

- Out of memory errors
- Performance degrades over time

Diagnostic Steps:

1. Check OmniHSS memory usage on Application page
2. Monitor memory trend
3. Check for memory leaks
4. Review Erlang VM settings

Solution:

- Restart OmniHSS to clear temporary condition
 - Investigate memory leak if usage continuously grows
 - Adjust Erlang VM memory settings in runtime.exs
 - Plan for hardware upgrade if consistently high
-

Subscriber State Issues

Symptoms

- Subscriber shows as attached but is not
- Stale state information
- Location information incorrect
- Cannot detach subscriber

Common Causes and Solutions

Cause 1: MME Crash/Restart**Symptoms:**

- Subscriber shows serving MME that is no longer serving
- Subscriber cannot attach after MME restart
- State is stale

Diagnostic Steps:

1. Check subscriber state for serving MME
2. Verify if MME has restarted
3. Check MME's last connection time

Solution:

- Wait for subscriber to attach again (state will update)
- Or manually clear subscriber state
- MME should send Cancel-Location on restart

Cause 2: Network Detach Not Received**Symptoms:**

- Subscriber powered off but shows as attached
- PDN sessions remain in database
- Location not cleared

Diagnostic Steps:

1. Check subscriber's last_seen timestamp
2. Verify if old state (hours or days old)
3. Check if subscriber device is reachable

Solution:

- State will clear when subscriber attaches again
- Or wait for state timeout (if implemented)
- Manual cleanup may be required for very stale state

Cause 3: Database Corruption**Symptoms:**

- Inconsistent state across tables
- Foreign key violations
- State does not make sense

Diagnostic Steps:

1. Query subscriber state directly from database
2. Check for orphaned records
3. Verify referential integrity

Solution:

- Identify and fix inconsistent data
 - May require manual database cleanup
 - Contact support if corruption is widespread
-

API Issues

Symptoms

- API returns errors
- Slow API responses
- Cannot create/update entities
- 500 errors

Common Causes and Solutions

Cause 1: Invalid Request Data

Symptoms:

- 400 or 422 errors
- Validation error messages
- Field rejected

Diagnostic Steps:

1. Review error response for specific field errors
2. Check API request format

3. Verify required fields present
4. Check data types

Solution:

- Fix request data to match [API reference](#)
- Ensure all required fields included
- Verify foreign key references exist (profile IDs, etc.)

Cause 2: Foreign Key Constraint**Symptoms:**

- Cannot create subscriber
- Error: "key_set_id does not exist"
- Referenced entity not found

Diagnostic Steps:

1. Identify which foreign key is failing
2. Verify referenced entity exists:
 - key_set_id → key sets
 - epc_profile_id → EPC profiles
 - ims_profile_id → IMS profiles

Solution:

- Create referenced entity first
- Or use existing entity ID
- Follow [complete provisioning workflow](#)

Cause 3: Database Connectivity**Symptoms:**

- 500 errors
- All API calls fail
- Database connection errors

Solution:

- See [Database Issues](#)
-

Diagnostic Tools and Commands

Control Panel Quick Checks

1. System Overview

- URL: `https://[hostname]:7443/overview`
- Check: Subscriber counts, active sessions, system status

2. Diameter Status

- URL: `https://[hostname]:7443/diameter`
- Check: All critical peers connected

3. Application Health

- URL: `https://[hostname]:7443/application`
- Check: Memory usage, process count, uptime

API Diagnostic Commands

Check System Health:

```
curl -k https://hss.example.com:8443/api/status
```

Query Subscriber:

```
# By IMSI
curl -k https://hss.example.com:8443/api/subscriber/imsi/001001123456789

# By MSISDN
curl -k https://hss.example.com:8443/api/subscriber/msisdn/14155551234

# By ID
curl -k https://hss.example.com:8443/api/subscriber/d290f1ee-6c54-4b01-90e6-d701748f0851
```

List All Subscribers:

```
curl -k https://hss.example.com:8443/api/subscriber
```

Check Profile Configuration:

```
# EPC Profile
curl -k https://hss.example.com:8443/api/epc/profile/e58ed763-928c-4155-bee9-fdbaaadc15f3

# IMS Profile
curl -k https://hss.example.com:8443/api/ims/profile/7c9e6679-7425-40de-944b-e07fc1f90ae7

# Roaming Profile
curl -k https://hss.example.com:8443/api/roaming/profile/9c858901-8a57-4791-81fe-4c455b099bc9
```

Network Diagnostic Commands

Test Diameter Port Connectivity:

```
telnet [PEER_IP] 3868
```

Check TLS Certificate:

```
openssl s_client -connect [hostname]:8443 -showcerts
```

Test Database Connectivity:

```
psql -h [DB_HOST] -U [DB_USER] -d [DB_NAME] -c "SELECT COUNT(*)  
FROM subscriber;"
```

Log Analysis

Search Logs for Specific IMSI:

```
grep "001001123456789" /var/log/omnihss/omnihss.log
```

Find Authentication Failures:

```
grep "authentication.*fail" /var/log/omnihss/omnihss.log
```

Check Diameter Peer Events:

```
grep "Diameter peer" /var/log/omnihss/omnihss.log
```

Find Database Errors:

```
grep -i "database.*error" /var/log/omnihss/omnihss.log
```

Escalation Guidelines

When to Escalate

Escalate to engineering/vendor support when:

1. **System-wide failures** that cannot be resolved with documented procedures
2. **Data corruption** or inconsistent database state
3. **Suspected software bugs** or unexpected behavior
4. **Performance issues** that cannot be resolved with tuning
5. **Security incidents** or unauthorized access
6. **Questions about undocumented behavior**

Information to Provide

When escalating, include:

1. **Detailed symptoms** - What is failing, when, for whom
2. **Steps taken** - What troubleshooting you have already done
3. **Logs** - Relevant log excerpts showing the issue
4. **Configuration** - Relevant portions of runtime.exs (redact sensitive data)
5. **Environment** - OmniHSS version, database version, OS version
6. **Impact** - How many subscribers affected, business impact
7. **Subscriber examples** - Specific IMSIs showing the problem

Critical vs Non-Critical

Critical Issues (Escalate Immediately):

- System completely down
- All subscribers unable to attach
- Database corruption
- Security breach

Non-Critical Issues (Document and Escalate During Business Hours):

- Single subscriber issues that can be worked around
 - Performance degradation that is manageable
 - Enhancement requests
 - Documentation questions
-

Common Error Messages Reference

Authentication Errors

Error Message	Cause	Solution
"Authentication vectors generation failed"	Missing or invalid key set	Check key set configuration
"SQN synchronization failure"	SQN out of sync	Wait for resync
"Subscriber not found"	Invalid IMSI	Verify IMSI, provision subscriber
"Subscriber disabled"	enabled=false	Enable subscriber

Diameter Errors

Error Message	Cause	Solution
"Diameter peer connection timeout"	Network issue	Check network connectivity
"CER/CEA exchange failed"	Configuration mismatch	Verify Diameter config
"Application not supported"	Peer does not support required app	Check peer applications
"TLS handshake failed"	Certificate issue	Check certificates

Database Errors

Error Message	Cause	Solution
"Connection refused"	Database down	Start database
"Authentication failed"	Wrong credentials	Fix credentials
"No connections available"	Pool exhausted	Increase pool size
"Query timeout"	Slow query	Optimize queries

API Errors

Error Message	Cause	Solution
"key_set_id does not exist"	Invalid foreign key	Create key set first
"IMSI has already been taken"	Duplicate IMSI	Use different IMSI or delete existing
"Validation error"	Invalid input	Check field format and requirements

OmniHSS Webhook Integration

[← Back to Operations Guide](#)

Table of Contents


- [Overview](#)
 - [How Webhooks Work](#)
 - [Webhook Events](#)
 - [Webhook Payload](#)
 - [Configuration](#)
 - [Use Cases](#)
 - [Security Considerations](#)
 - [Troubleshooting](#)
-

Overview

OmniHSS supports **webhooks** to notify external systems about subscriber events in real-time. When specific events occur (such as location updates, authentication requests, or IMS registrations), OmniHSS can send an HTTP POST request to your configured webhook endpoint with the complete subscriber profile data.

What Are Webhooks?

Webhooks are HTTP callbacks that allow OmniHSS to push event notifications to your application as they happen, rather than requiring your application to poll the HSS API for changes.



Key Benefits

- **Real-time notifications** - Get instant updates when subscriber events occur
- **Complete subscriber data** - Each webhook includes the full subscriber profile (same as `GET /api/subscriber`)
- **Event-driven automation** - Trigger workflows, analytics, or provisioning based on network events
- **Reduced polling** - No need to continuously query the API for subscriber status changes
- **Integration flexibility** - Connect OmniHSS to billing systems, analytics platforms, or custom applications

How Webhooks Work

Event Flow

1. **Event occurs** - A subscriber performs an action (attach, location update, IMS registration, etc.)

2. **HSS processes event** - OmniHSS handles the Diameter request/response normally
3. **Webhook triggered** - If a webhook is registered for this event type, HSS sends HTTP POST to your endpoint
4. **Subscriber data included** - The webhook payload contains the complete subscriber profile as JSON
5. **Your application responds** - Your endpoint should return HTTP 200-299 to acknowledge receipt

Delivery Guarantees

- **Best effort delivery** - Webhooks are sent asynchronously and do not block network operations
- **Timeout** - Webhook requests timeout after 5 seconds
- **No retries** - If your endpoint is unavailable or returns an error, the webhook is not retried
- **Order not guaranteed** - Events may arrive out of order under high load

Important: Network operations (authentication, location updates, etc.) are **not** dependent on webhook delivery. If your webhook endpoint is down, subscriber service continues normally.

Webhook Events

OmniHSS can trigger webhooks for the following events:

EPC/LTE Events

Event	Trigger	Description
update_location_request	S6a ULR	Subscriber attaches or performs Tracking Area Update
authentication_information_request	S6a AIR	Network requests authentication vectors for subscriber
purge_request	S6a PUR	MME removes subscriber context (device powered off, detached)
cancel_location_answer	S6a CLA	MME acknowledges subscriber deregistration

IMS Events

Event	Trigger	Description
ims_registration	Cx SAR	Subscriber registers for IMS/VoLTE service
ims_deregistration	Cx SAR (de-reg)	Subscriber deregisters from IMS
ims_profile_request	Sh UDR	Application Server requests subscriber IMS profile

Policy Events (PCRF)

Event	Trigger	Description
<code>policy_request</code>	Gx CCR	P-GW requests policy for subscriber data session
<code>media_authorization</code>	Rx AAR	P-CSCF requests media authorization for IMS call

Multi-IMSI Events

Event	Trigger	Description
<code>imsi_switch</code>	ULR for different IMSI on same SIM	Device switches to different IMSI on multi-IMSI SIM

Webhook Payload

Request Format

When an event occurs, OmniHSS sends an HTTP POST request to your configured webhook URL:

POST /your-webhook-endpoint HTTP/1.1
Host: your-server.com
Content-Type: application/json
X-OmniHSS-Event: update_location_request
X-OmniHSS-Event-ID: 550e8400-e29b-41d4-a716-446655440000
X-OmniHSS-Timestamp: 2025-01-15T14:30:00Z

```
{
  "event": "update_location_request",
  "event_id": "550e8400-e29b-41d4-a716-446655440000",
  "timestamp": "2025-01-15T14:30:00Z",
  "subscriber": {
    "id": "d290f1ee-6c54-4b01-90e6-d701748f0851",
    "imsi": "001001123456789",
    "enabled": true,
    "ims_enabled": true,
    "msisdns": [
      {"id": "16fd2706-8baf-433b-82eb-8c7fada847da", "msisdn":
"14155551001"},
      {"id": "27ae3807-9cbf-4a4c-93fc-9d8afdb958eb", "msisdn":
"14155551002"}
    ],
    "sim": {
      "id": "3f2504e0-4f89-41d3-9a0c-0305e82c3301",
      "iccid": "8991101200003204510",
      "is_esim": false
    },
    "key_set": {
      "id": "6ba7b810-9dad-41d1-80b4-00c04fd430c8",
      "amf": "8000"
    },
    "epc_profile": {
      "id": "e58ed763-928c-4155-bee9-fdbaaadc15f3",
      "name": "Premium 100Mbps",
      "ue_ambr_dl_kbps": 100000,
      "ue_ambr_ul_kbps": 50000
    },
    "ims_profile": {
      "id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
      "name": "Standard VoLTE"
    },
    "roaming_profile": {
      "id": "9c858901-8a57-4791-81fe-4c455b099bc9",
```

```
    "name": "International Roaming Allowed"
  },
  "subscriber_state": {
    "mme_host": "mme-01.example.com",
    "mme_realm": "epc.mnc001.mcc001.3gppnetwork.org",
    "visited_plmn": "001001",
    "last_update": "2025-01-15T14:30:00Z"
  },
  "custom_attributes": {
    "account_type": "premium",
    "billing_plan": "unlimited"
  }
},
"event_context": {
  "visited_plmn": "310410",
  "mme_host": "mme-roaming.example.com",
  "location_update_type": "initial_attach"
}
}
```

Payload Structure

Field	Type	Description
<code>event</code>	string	Event type (e.g., <code>update_location_request</code>)
<code>event_id</code>	string	Unique UUID for this webhook delivery
<code>timestamp</code>	string	ISO 8601 timestamp when event occurred
<code>subscriber</code>	object	Complete subscriber profile (same as <code>GET /api/subscriber/:id</code>)
<code>event_context</code>	object	Additional event-specific context data

Event Context Fields

The `event_context` object contains event-specific information:

For `update_location_request`:

```
{
  "visited_plmn": "310410",
  "mme_host": "mme-roaming.example.com",
  "mme_realm": "epc.mnc410.mcc310.3gppnetwork.org",
  "location_update_type": "initial_attach"
}
```

For `imsi_switch`:

```
{
  "previous_imsi": "001001111111111",
  "new_imsi": "310410222222222",
  "sim_id": "3f2504e0-4f89-41d3-9a0c-0305e82c3301",
  "previous_mme_host": "mme-home.example.com",
  "new_mme_host": "mme-roaming.example.com"
}
```

For `ims_registration`:

```
{
  "scscf_host": "scscf-01.ims.example.com",
  "public_identities": [
    "sip:001001123456789@ims.mnc001.mcc001.3gppnetwork.org",
    "sip:+14155551001@ims.example.com",
    "tel:+14155551001"
  ]
}
```

HTTP Headers

Header	Description	Example
Content-Type	Always application/json	application/json
X-OmniHSS-Event	Event type	update_location_request
X-OmniHSS-Event-ID	Unique event identifier	UUID
X-OmniHSS-Timestamp	Event timestamp	ISO 8601 format
User-Agent	OmniHSS version	OmniHSS/1.0

Configuration

Registering Webhooks

Webhooks are configured via the OmniHSS API.

Register a Webhook


```
curl -k -X POST https://hss.example.com:8443/api/webhook \
-H "Content-Type: application/json" \
-d '{
  "webhook": {
    "url": "https://your-server.com/omnihss-webhook",
    "events": [
      "update_location_request",
      "ims_registration",
      "imsi_switch"
    ],
    "enabled": true,
    "description": "Production billing system webhook"
  }
}'
```

Response:

```
{
  "data": {
    "id": "4e5d6c7b-8a9f-4b0c-8d1e-2f3a4b5c6d7e",
    "url": "https://your-server.com/omnihss-webhook",
    "events": [
      "update_location_request",
      "ims_registration",
      "imsi_switch"
    ],
    "enabled": true,
    "description": "Production billing system webhook",
    "created_at": "2025-01-15T14:00:00Z"
  }
}
```

List Webhooks

```
curl -k https://hss.example.com:8443/api/webhook
```

Update Webhook

```
curl -k -X PUT https://hss.example.com:8443/api/webhook/4e5d6c7b-8a9f-4b0c-8d1e-2f3a4b5c6d7e \
  -H "Content-Type: application/json" \
  -d '{
    "webhook": {
      "enabled": false
    }
  }'
```

Delete Webhook

```
curl -k -X DELETE
https://hss.example.com:8443/api/webhook/4e5d6c7b-8a9f-4b0c-8d1e-2f3a4b5c6d7e
```

Webhook Endpoint Requirements

Your webhook endpoint must:

1. **Accept POST requests** with `Content-Type: application/json`
2. **Respond quickly** - Return HTTP 200-299 within 5 seconds
3. **Be idempotent** - Handle duplicate deliveries gracefully
4. **Use HTTPS** - For security, use TLS/SSL endpoints (recommended)
5. **Validate payloads** - Verify the request is from OmniHSS (see Security section)

Example Webhook Handler (Node.js/Express):

```
const express = require('express');
const app = express();

app.post('/omnihss-webhook', express.json(), (req, res) => {
  const { event, subscriber, event_context } = req.body;

  console.log(`Received event: ${event}`);
  console.log(`Subscriber IMSI: ${subscriber.imsi}`);

  // Process the subscriber data
  // ... your business logic here ...

  // Respond immediately to acknowledge receipt
  res.status(200).json({ received: true });

  // Handle async processing after response
  processWebhook(req.body).catch(console.error);
});


async function processWebhook(payload) {
  // Your async processing logic
  // e.g., update billing system, trigger analytics, etc.
}

app.listen(3000);
```

Use Cases

1. Real-Time Billing and Usage Tracking

Track subscriber network usage and trigger billing events in real-time.



Benefits:

- Instantly detect when subscribers roam internationally
- Apply appropriate roaming charges in real-time
- Track session start/end times accurately
- Generate usage alerts when thresholds are reached

2. Analytics and Monitoring

Feed subscriber activity data into analytics platforms for real-time dashboards and reporting.

Use Case: Track active subscribers by region

```
// Webhook handler feeding data to analytics platform
app.post('/omnihss-webhook', async (req, res) => {
  const { event, subscriber, event_context } = req.body;

  if (event === 'update_location_request') {
    await analytics.track({
      event: 'subscriber_location_update',
      imsi: subscriber.imsi,
      visited_plmn: event_context.visited_plmn,
      timestamp: req.body.timestamp,
      profile: subscriber.epc_profile.name
    });
  }


  res.status(200).send();
});
```

Analytics Dashboard:

- Active subscribers per MME
- Roaming subscribers by country
- Service tier distribution
- IMS registration success rates

3. Fraud Detection and Security

Detect suspicious activity patterns in real-time and trigger automated responses.



Fraud Detection Scenarios:

1. Rapid Location Changes

- Subscriber attaches in Country A
- 30 minutes later, attaches in Country B (physically impossible)
- Action: Flag account, send alert to security team

2. IMSI Switch Abuse

- Multiple rapid IMSI switches on same SIM
- Possible SIM cloning or unauthorized multi-IMSI usage
- Action: Disable all IMSIs on SIM, notify fraud team

3. Unauthorized Roaming

- Subscriber roams to blocked country (sanctions, fraud risk)
- Action: Auto-disable subscriber, block network access

Example Implementation:

```

@app.route('/omnihss-webhook', methods=['POST'])
def webhook_handler():
    data = request.json
    subscriber = data['subscriber']
    event_context = data.get('event_context', {})

    if data['event'] == 'update_location_request':
        visited_plmn = event_context.get('visited_plmn')

        # Check for blocked countries
        if visited_plmn in BLOCKED_PLMNS:
            disable_subscriber(subscriber['imsi'])
            alert_security_team(subscriber, 'Roaming to blocked
PLMN')

        # Check for impossible travel
        if is_impossible_travel(subscriber['imsi'], visited_plmn):
            flag_for_review(subscriber['imsi'])
            alert_fraud_team(subscriber, 'Impossible travel
detected')

    return jsonify({'status': 'ok'}), 200

```

4. Provisioning Automation

Automatically provision or update subscriber services based on network events.

Use Case: Auto-enable IMS when subscriber first uses VoLTE

```

app.post('/omnihss-webhook', async (req, res) => {
  const { event, subscriber } = req.body;

  if (event === 'ims_registration' && !subscriber.ims_enabled) {
    // First-time IMS user - enable IMS permanently
    await omnihss.updateSubscriber(subscriber.id, {
      ims_enabled: true,
      custom_attributes: {
        ...subscriber.custom_attributes,
        volte_activated_at: new Date().toISOString()
      }
    });

    // Update CRM
    await crm.updateCustomer(subscriber.imsi, {
      features: ['volte']
    });
  }


  res.status(200).send();
});

```

5. Customer Notifications

Send real-time notifications to customers about their service.

Use Case: Welcome message when roaming internationally



Example Notifications:

- "Welcome to [Country]! Roaming rates apply."
- "You have used 80% of your data allowance"
- "VoLTE service now active on your device"
- "Your account has been upgraded to Premium"

6. Multi-IMSI SIM Management

Track and manage subscribers with multi-IMSI SIMs, receiving notifications when they switch IMSIs.

```
app.post('/omnihss-webhook', async (req, res) => {
  const { event, subscriber, event_context } = req.body;

  if (event === 'imsi_switch') {
    const { previous_imsi, new_imsi, sim_id } = event_context;

    // Log IMSI switch for analytics
    await db.logImsiSwitch({
      sim_id,
      from_imsi: previous_imsi,
      to_imsi: new_imsi,
      timestamp: req.body.timestamp
    });

    // Update billing system
    await billing.endSession(previous_imsi);
    await billing.startSession(new_imsi);

    // Alert if excessive switching (potential fraud)
    const switchCount = await db.getSwitchCount(sim_id, '24h');
    if (switchCount > 10) {
      await alertFraudTeam(`Excessive IMSI switching: SIM
${sim_id}`);
    }
  }

  res.status(200).send();
});
```

7. Integration with External Systems

Connect OmniHSS to third-party systems without polling.

Example Integrations:

- **CRM Systems** - Update customer records with service usage
 - **Network Monitoring** - Feed subscriber data to network analytics platforms
 - **Billing Systems** - Trigger charges based on network events
 - **Ticketing Systems** - Auto-create tickets for failed authentications
 - **Data Warehouses** - Stream subscriber events for big data analysis
-

Security Considerations

Webhook Secret/Signature

To verify webhooks are from OmniHSS, implement signature verification:

```
# Configure webhook with secret
curl -k -X POST https://hss.example.com:8443/api/webhook \
  -H "Content-Type: application/json" \
  -d '{
    "webhook": {
      "url": "https://your-server.com/omnihss-webhook",
      "events": ["update_location_request"],
      "secret": "your-secret-key-here"
    }
  }'
```

OmniHSS will include an `X-OmniHSS-Signature` header:

```
X-OmniHSS-Signature:
sha256=5d7a8f9b2c1e3a4d6f7e8b9c0a1b2c3d4e5f6a7b8c9d0e1f2a3b4c5d6e7f8a
```

Verify the signature:

```
const crypto = require('crypto');

function verifyWebhook(req) {
  const signature = req.headers['x-omnihss-signature'];
  const secret = process.env.WEBHOOK_SECRET;
  const payload = JSON.stringify(req.body);

  const expectedSignature = 'sha256=' +
    crypto.createHmac('sha256', secret)
      .update(payload)
      .digest('hex');

  return crypto.timingSafeEqual(
    Buffer.from(signature),
    Buffer.from(expectedSignature)
  );
}

app.post('/omnihss-webhook', (req, res) => {
  if (!verifyWebhook(req)) {
    return res.status(401).json({ error: 'Invalid signature' });
  }

  // Process webhook...
  res.status(200).send();
});
```

Best Practices

1. **Use HTTPS** - Always use TLS for webhook endpoints
2. **Validate signatures** - Verify webhook signatures to prevent spoofing
3. **Rate limiting** - Implement rate limiting on webhook endpoints
4. **IP allowlisting** - Restrict webhook access to OmniHSS IP addresses
5. **Monitor failures** - Track webhook delivery failures and errors
6. **Sanitize data** - Validate and sanitize webhook payloads before processing
7. **Secure credentials** - Store webhook secrets in secure configuration (environment variables, secrets manager)

Data Privacy

Webhook payloads contain **sensitive subscriber information**:

- IMSI (subscriber identity)
- MSISDNs (phone numbers)
- Location data (visited PLMN, MME)
- Service profile information

Compliance Requirements:

- **GDPR** - Ensure webhook data is processed in compliance with GDPR
 - **Data retention** - Implement appropriate data retention policies
 - **Access control** - Restrict webhook endpoint access
 - **Encryption** - Use TLS for webhook transport
 - **Audit logging** - Log all webhook deliveries for compliance
-

Troubleshooting

Webhook Not Received

Symptoms:

- Events occur but webhook is not triggered
- Webhook endpoint never receives requests

Troubleshooting Steps:

1. Verify webhook is enabled:

```
curl -k https://hss.example.com:8443/api/webhook  
# Check "enabled": true
```

2. Check webhook events configuration:

- Ensure the event type is included in the webhook's `events` list
- Example: If you want `ims_registration` events, verify it is in the events array

3. Review HSS logs:

- Check for webhook delivery errors
- Look for network connectivity issues
- Verify no DNS resolution failures

4. Test endpoint accessibility:

```
curl -X POST https://your-server.com/omnihss-webhook \
-H "Content-Type: application/json" \
-d '{"test": true}'
```

Webhook Timing Out

Symptoms:

- HSS logs show webhook timeout errors
- Webhook endpoint receives request but HSS marks as failed

Solution:

1. Respond immediately:

- Return HTTP 200 within 5 seconds
- Process data asynchronously after responding

2. Optimize endpoint performance:

```
// BAD - Slow synchronous processing
app.post('/webhook', (req, res) => {
  processData(req.body); // Blocks for 10 seconds
  res.status(200).send();
});

// GOOD - Async processing after response
app.post('/webhook', (req, res) => {
  res.status(200).send(); // Respond immediately
  processData(req.body); // Process async
});
```

Duplicate Webhooks

Symptoms:

- Same event delivered multiple times
- `event_id` is identical for duplicate deliveries

Cause:

- Network retries (though OmniHSS does not retry, network infrastructure might)
- Multiple webhooks registered for same event

Solution:

Implement idempotency using `event_id`:

```
const processedEvents = new Set();

app.post('/omnihss-webhook', (req, res) => {
  const eventId = req.body.event_id;

  if (processedEvents.has(eventId)) {
    // Already processed, skip
    return res.status(200).json({ status: 'duplicate' });
  }

  processedEvents.add(eventId);

  // Process webhook...
  processWebhook(req.body);

  res.status(200).json({ status: 'processed' });
});
```

Webhook Returns Error

Symptoms:

- Endpoint returns HTTP 4xx or 5xx
- HSS logs webhook delivery failure

Common Errors:

1. **401 Unauthorized** - Signature verification failed

- Check webhook secret matches configuration
- Verify signature calculation algorithm

2. **400 Bad Request** - Invalid payload

- Check webhook payload parsing
- Ensure Content-Type header is handled

3. **500 Internal Server Error** - Endpoint crashed

- Review endpoint error logs

- Add error handling and logging

Solution:

Add comprehensive error handling:

```
app.post('/omnihss-webhook', async (req, res) => {
  try {
    // Verify signature
    if (!verifyWebhook(req)) {
      return res.status(401).json({ error: 'Invalid signature' });
    }

    // Validate payload
    if (!req.body.event || !req.body.subscriber) {
      return res.status(400).json({ error: 'Invalid payload' });
    }

    // Process webhook
    await processWebhook(req.body);

    res.status(200).json({ status: 'ok' });

  } catch (error) {
    console.error('Webhook processing error:', error);
    // Return 200 to prevent retry, log error for investigation
    res.status(200).json({ status: 'error', message: error.message });
  }
});
```

Missing Subscriber Data

Symptoms:

- Webhook received but subscriber object is incomplete
- Expected fields are null or missing

Possible Causes:

1. **Subscriber not fully provisioned** - Some profiles may be optional (IMS, roaming)
2. **Data race condition** - Subscriber updated between event trigger and webhook send

Solution:

Handle optional fields gracefully:

```
const { subscriber } = req.body;

// Check for optional fields
const imsProfile = subscriber.ims_profile || { name: 'No IMS' };
const roamingProfile = subscriber.roaming_profile || { name: 'No Roaming' };

// Handle missing MSISDNs
const msisdns = subscriber.msisdns || [];
```

Monitoring and Observability

Webhook Metrics

Track webhook performance and reliability:

Metrics to Monitor:

- Webhook delivery rate (successful vs. failed)
- Webhook latency (time from event to endpoint response)
- Endpoint response times
- Error rates by endpoint
- Events per second

Example Dashboard Query (Prometheus/Grafana):

```
# Webhook success rate
rate(omnihss_webhook_success_total[5m]) /
rate(omnihss_webhook_attempts_total[5m])

# Webhook latency
histogram_quantile(0.95, omnihss_webhook_duration_seconds)
```

Webhook Logs

Enable detailed webhook logging for troubleshooting:

Log Format:

```
{
  "timestamp": "2025-01-15T14:30:00Z",
  "level": "info",
  "component": "webhook",
  "event_id": "550e8400-e29b-41d4-a716-446655440000",
  "webhook_id": "4e5d6c7b-8a9f-4b0c-8d1e-2f3a4b5c6d7e",
  "event_type": "update_location_request",
  "subscriber_imsi": "001001123456789",
  "endpoint": "https://your-server.com/omnihss-webhook",
  "http_status": 200,
  "duration_ms": 145,
  "error": null
}
```

[← Back to Operations Guide](#) | [Next: API Reference →](#)

